MIL-D-36259A
10 September 1973
SUPERSEDING
MIL-D-36259(DM)
11 August 1964

MILITARY SPECIFICATION

DIVIDERS, TRAY CHEST

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers three sizes of lightweight aluminum dividers intended for use with the aluminum trays specified in 6.1.

1.2 Classification. The dividers covered by this specification shall be of the following sizes, as specified (see 6.2):

Size	Width (inches)	Height (exclusive of tabs) inches
A	11-9/16	5-5/8
B	16-11/16	5-5/8
C	16-11/16	9-5/8

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-A-250/8	Aluminum Alloy, 5052, Plate and Sheet.
QQ-S-763	Steel Bars, Shapes, and Forgings, Corrosion-Resisting.
MMM-A-250	Adhesive, Water-resistant, (For Sealing Fiberboard Boxes).
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Boxes, Set-Up, Paperboard.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (for Carton Sealing).

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

STANDARDS

Federal

Fed. Test Method Std. No. 151	Metals; Test Methods.

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

DRAWING

Defense Personnel Support Center (DPSC)

10121 Dividers, Tray Chest (and Bill of Materials).

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Component parts. Component parts shall consist of the divider with two lock rod supports and two lock rods.

3.2 Material. Except as specified herein, materials shall conform to the applicable portions of the specifications, standards, and drawing (with bill of materials) specified herein, and shall be capable of meeting the requirements specified therein. In addition, the metals shall conform to the chemical requirements of their applicable specifications when tested as specified in Section 4. When materials to be used are not specifically designated, those used shall be of the highest commercial quality, and entirely suitable for the purpose intended.

3.2.1 Aluminum alloy. Aluminum alloy sheets shall conform to Specification QQ-A-250/8 and shall be temper H-34.

3.2.2 Corrosion-resisting steel. Corrosion-resisting steel rods shall conform to class 302 of Specification QQ-S-763.

3.3 Construction. The dividers shall conform in all details to the requirements specified herein, and as shown in the drawing. Construction shall be sound and durable in all respects. The assembly shall be welded on jigs cabable of maintaining tolerance on finished dividers.

3.3.1 Dividers. Dividers and lock rod supports shall be formed from aluminum alloy sheet as specified in 3.2.1. The lock rod shall be made of corrosion-resisting steel as specified in 3.2.2.

3.4 Welding. Welding shall be durable, sound in every detail and in accordance with latest practices recommended by the American Welding Society. All welds shall be produced by qualified welding operators with satisfactory welding equipment using satisfactory filler metal or electrode where applicable to provide the best possible weld. Surfaces to be welded shall be free from grease, oil, oxides or any other foreign matter; any cleaning method which will remove these substances and leave the surface clean is satisfactory. All weld joints shall blend into the adjacent metal in gradual, smooth curves. Welds shall not be oxidized. All welds shall be continuous with no visible voids, pin holes, or cracks, and have more strength than required for purpose intended.

3.5 Tolerances. Tolerances shall be as specified in the drawing. In forming dividers, particular accuracy shall be maintained in locating the divider projections and the lock rods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

3.6 Finish. Completed dividers shall have a finish characteristics of the cleaning process used in 3.4.

3.7 Identification marking. Each divider shall be permanently and legibly marked with the appropriate item identification and size (A, B, or C); the name or registered trademark of the manufacturer; and the contract or order number. Decalcomanias shall not be employed.

3.8 Workmanship. Workmanship shall be first class throughout. Sharp edges and burs shall be removed. Dividers shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during performance of the contract and for a period of three (3) years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the aluminum sheet, and corrosion resisting steel rod, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Quality conformance inspection. The examinations and tests required to assure conformance of those items or lots of items to be offered for acceptance are classified as specified in tables I and II (see 4.2.1 and 4.2.2) and 4.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

4.2.1 Sampling for examination. Sampling for examination shall be conducted in accordance with MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in table I. Unit of product for examination purposes shall be one divider.

Table I, Sampling for Examination

Examination	Inspection Level	AQL (percent defective)
For visual examination		
Major	II	2.5
Minor	II	6.5
For dimensional examination	S-1	4.0

4.2.2 Examination. The divider shall be examined for defects including, but not limited to, those listed in table II.

Table II Classification of Defects

Major	
101	Any component missing.
102	Spotwelds not located as per drawing.
103	Lock rod does not slide freely.
104	Tabs not bent.
105	Burrs on divider.
106	Sharp edges on divider
107	Marking on divider missing or incomplete.
Minor	
201	Divider not free of scratches.
202	Marking on divider not completely legible.
203	Finish not uniform.

4.2.3 Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, Inspection Level S-1, Acceptable Quality Level 1.0, except that the minimum sample size shall be 3 dividers of the same size. Unit of product for test purposes shall be one divider.

4.2.4 For chemical testing of metals. Four ounces of each lot of each metal used in the construction of the dividers shall be selected for chemical analysis as specified in 4.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

4.3 Tests. Tests shall be conducted to determine compliance with specification requirements.

4.3.1 Chemical analysis of the metals. The samples selected in accordance with 4.2.4 shall be analyzed in conformance with methods 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, method 111 shall be used for referee analysis.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) divider, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in the following table shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table III. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	48 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Each unit shall be wrapped in neutral paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

5.1.3.2 Intermediate package. Intermediate package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class weather-resistant. Boxes shall be closed by taping the top and bottom flaps with 2 inch wide tape conforming to PPP-T-76. Closing of bottom flap with adhesive conforming to MMM-A-250 or metal stitches is permitted.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Closure and strapping shall be as specified in the appendix of the applicable box specification. Special requirements of applicable Table shall apply for PPP-B-636 box.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification. Fiberboard box shall be closed by method II of PPP-B-636. Special requirements of applicable Table shall apply for PPP-B-636 box.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery called for in the contract or purchase order.

5.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The dividers are intended for use with the size of tray as indicated below for the appropriate National stock number and item identification.

Divider NSN	Size	Tray NSN	Item Identification
6545-00-925-9205	A	6545-00-925-9200	TRAY, MEDICAL INSTRUMENT AND SUPPLY SET CHEST, 23-25/32 inches Long by 11-3/4 inches Wide by 5-27/32 inches High.
6545-00-925-9215	B	6545-00-925-9210	TRAY, MEDICAL INSTRUMENT AND SUPPLY SET CHEST, 29 inches Long by 16-27/32 inches Wide by 5-27/32 inches High.
6545-00-925-9225	C	6545-00-925-9220	TRAY, MEDICAL INSTRUMENT AND SUPPLY SET CHEST, 29 inches Long by 16-27/32 inches Wide by 9-27/32 inches High.

Copies of Defense Medical Purchase Descriptions covering the above referenced items may be obtained from the procuring activity or as directed by the contracting officer.

6.2 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.

(b) Size required (see 1.2).

(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 This specification does not include all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, which are normally procured to meet military requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project number: 6545-0014

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation shall be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-D-36259A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:17Z
Check the source to verify that this is the current version before use.