MIL-F-36297(DM)
7 October 1964

MILITARY SPECIFICATION

FUEL, SOLIDIFIED HYDROCARBON

1. SCOPE

1.1 This specification covers one type of solidified hydrocarbon compound fuel suitable for use with a pressure sterilizer and heater assembly used in the sterilization of dental, laboratory and surgical instruments, supplies, dressings and flasked solutions.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-636	Box, Fiberboard.
PPP-C-96	Cans, Metal, 28 Gage and Lighter.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (for Carton Sealing).

Military

MIL-L-10547	Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. The solidified hydrocarbon fuel shall have the following properties:

(a) Shall produce 19,500 British Thermal Units (BTU) per pound when tested as specified in 4.4.

(b) Shall be capable of ignition by spark at minus 60° Fahrenheit (F.) when tested as specified in 4.4.

(c) Shall withstand prolonged storage at temperatures ranging from minus 60°F to plus 150°F without deterioration.

(d) Shall produce an explosive vapor concentration not exceeding 4 percent of the lower explosive limit of 1.4 percent of vapor in air by volume, when tested as specified in 4.4.

(e) Shall produce a toxicity concentration not exceeding 4500 parts per million when tested as specified in 4.4.

(f) Shall not melt while burning, and shall not produce objectionable odors and smoke.

3.2 Unit (Can and contents). The fuel shall be packaged in a metal can as specified in 5.1.3. Each can shall contain not less than 0.585 pounds of fuel. The can and its contents shall be approved for shipment by parcel post.

3.3 Identification marking. Each container shall bear a marking, inconspicuously located, containing the following data:

(1) Name of manufacturer or registered trade-mark.

(2) Contract or purchase order number.

(3) U. S.

Marking secured by adhesive shall not be used.

3.4 Workmanship. Workmanship shall be first class throughout. The fuel shall be free from defects which detract from their appearance or may impair their serviceability. The occurrence of defects shall not exceed the limits set by the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, auditory, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the end item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105.

4.2.2 For tests. Sufficient sample of the fuel shall be selected from each lot to perform each test two times.

4.3 Examination. The fuel shall be examined to determine compliance with all requirements contained in this specification.

4.4 Tests.

4.4.1 Ignition test. A can containing the solidified hydrocarbon fuel shall be placed in an enclosure having a temperature of - 60°F for 24 hours. The fuel shall be ignited by means of a spark-type ignitor.

4.4.2 Bomb calorimeter test. The BTU content of the solidified hydrocarbon fuel shall be determined by the use of a Parr bomb calorimeter.

4.4.3 Explosive vapors test. An open can, having a surface area of not less than 18.84 square inches, containing four ounces of fuel, shall be placed in an enclosed compartment having a total volume of 330 cubic feet. Temperature shall be maintained at 100°F. ± 5°F. for a five day period. The percentage of explosive vapor shall be determined by means of a Davis vaportester using the 1-1 scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.4.4 Toxicity. The test procedure outlined in 4.4.3 shall be repeated except that the sample shall be taken after a four day period. The concentration of vapor shall be determined by means of the Davis vaportester.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One (1) can, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table I shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table I. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	6 units	24 units

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Material shall be packaged in a can conforming to PPP-C-96, type III, plan A. The dimensions of the can shall be 4-1/4-inches ± 1/8-inch in diameter by 2 inches ± 1/8-inch in height. A suitable corrosion-resisting key shall be attached to one end of the can.

5.1.3.2 Intermediate package. Intermediate package shall be a carton of appropriate size constructed in accordance with PPP-B-636. Closure shall be adequate to prevent spillage of contents under normal handling.

Source: https://assist.dla.mil -- Downloaded: 20260-21T08:21Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather resistant.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix of PPP-B-636. In addition, all seams, including manufacturer's joint, shall be closed by tape conforming to the requirements of PPP-T-76. The tape shall be not less than 2 inches wide. Three strips shall be applied to both top and bottom so that all seams and joints shall be covered their full length. Tape applied over the lengthwise seams shall extend a minimum of 2 inches onto each of the end panels. Tape applied over the end edge seams shall extend a minimum of 2 inches along the side and top, and side and bottom panels.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic.

5.3 Marking.

5.3.1 Unit container. Each can shall contain information in accordance with commercial practice and shall include the following:

(a) Federal stock number.
(b) Quantity of contents.
(c) Directions for use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

(d) The statement: "Flammable - Keep away from open flame."
(e) Item Identification.
(f) The statement: "Store in a cool place."
(g) Name of contractor.

5.3.2 Intermediate packages. Each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown. Marking shall include the legends: "Flammable" and "Store in a cool place (50° - 80° F.)"

5.3.3 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. Marking shall include the legend:

"STORE IN A COOL PLACE (50° - 80° F.)"

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.2 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army. - MD
Navy. - MS
Air Force. - 03

Preparing activity:
Defense Supply Agency. - DM

Review activities:
Army. - MD
Navy. - MS
Air Force. - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

FORM APPROVED BUDGET BUREAU NO. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use of the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

FUEL, SOLIDIFIED HYDROCARBON MIL-F-36297(DH), dated 7 October 1964

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (ATTACH ANY PERTINENT DATA WHICH MAY BE OF USE IN IMPROVING THIS SPECIFICATION. IF THERE ARE ADDITIONAL PAPERS, ATTACH TO FORM AND PLACE BOTH IN AN ENVELOPE ADDRESSED TO PREPARING ACTIVITY)

SUBMITTED BY (PRINTED OR TYPED NAME AND ACTIVITY)	DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

CAUTION

NOTICE TO BIDDERS/OFFERORS

DO NOT CONDITION OR BASE YOUR BID/OFFER ON ANY CURRENT PROCUREMENT ON THE INFORMATION SUBMITTED ON THIS FORM SINCE ANY CHANGES OR DELETIONS IN THE SPECIFICATIONS MAY RENDER YOUR BID/OFFER NON-RESPONSIVE IN WHICH CASE IT CANNOT BE CONSIDERED FOR AWARD.

Fold Under

DEFENSE SUPPLY AGENCY
DEFENSE MEDICAL SUPPLY CENTER
3RD AVENUE AND 29TH STREET
BROOKLYN, N.Y., 11232

OFFICIAL BUSINESS

POSTAGE FEES PAID
DEFENSE SUPPLY AGENCY

Defense Supply Agency
Defense Medical Supply Center
ATTN: Directorate of Technical Operations (Code T-M6)
3rd Avenue and 29th Street
Brooklyn, N.Y., 11232

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the current version before use.