MIL-L-36296(DM)
6 October 1964

MILITARY SPECIFICATION

LABEL TAPE, PRESSURE SENSITIVE ADHESIVE, "KEEP OUT OF REACH OF CHILDREN" LEGEND

1. SCOPE

1.1 Scope. This specification covers prescription labels that can be fed through a typewriter and positioned for typing without clips or repetitious adjustments.

1.2 Classification. Prescription labels shall be of the following sizes, as specified (see 6.1):

Size 1. - 3 inches long by 1-1/2 inches wide.
Size 2. - 2-1/4 inches long by 1-1/4 inches wide.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Boxes, Set-Up, Paperboard.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (for Carton Sealing).

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 20260-21T08:21Z
Check the source to verify that this is the current version before use.

Military

MIL-L-10547 Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

STANDARDS

Federal

Fed. Std. No. 595 Colors.

Military

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 Marking for Shipment and Storage.

DRAWING

Defense Medical Supply Center

20572 LABEL TAPE, PRESSURE SENSITIVE ADHESIVE, "KEEP OUT OF REACH OF CHILDREN" LEGEND, 1000 LABELS

(Copies of specifications, standards and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

TECHNICAL ASSOCIATION OF THE PULP AND PAPER INDUSTRY

T 402 m-49 Conditioning Paper and Paperboard for Testing.
T 403 m-53 Bursting Strength of Paper.
T 410 os-61 Basis Weight of Paper and Paperboard.
T 411 m-44 Thickness and Density of Paper.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, New York, 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.

3.1.1 Label stock. The label stock shall be paper coated on two sides with a clay coating, using polyvinyl acetate as a binder. When tested as specified in 4.4.1, the coated paper shall have the following minimum physical requirements:

Basis weight	60 pounds (25 by 38 inches - 500 sheets).
Bursting strength (Mullen)	29 units.
Thickness	0.003 inch minimum.

3.1.2 Backing paper. The backing paper shall be coated with a silicone material or wax suitable for the purpose intended. When tested as specified in 4.4.1, the paper shall have the following minimum physical requirements:

Basis weight	44 pounds (24 by 36 inches - 500 sheets).
Thickness	0.002 inch minimum.

3.1.3 Adhesive. Adhesive shall be formulated from a synthetic rubber base containing fillers and tacifying resins and shall create a "permanent bond" (i.e., face paper will tear when attempting to remove).

3.2 Dimensions, style, and design. Labels shall be rectangular in shape and shall be in strict accordance with Drawing 20572. One side shall be coated with adhesive as specified in 3.1.3.

3.3 Writing quality. Labels shall be suitable for writing on with ink, pencil, and typewriter.

3.4 Adhesion. When tested as specified in 4.4.2, labels shall adhere instantly and remain so firmly affixed that they cannot be removed without pulling fibres from the paper.

3.5 Color. The labels shall be white. The printed matter on the labels shall conform to color 35109 (lusterless blue) of No. 595 (see 6.2).

3.6 Assembly. Labels shall be assembled in rolls containing 1000 labels. Labels shall be pre-cut and assembled onto backing paper (adhesive side to the backing paper). Labels shall be flush with backing paper; backing paper shall have a slit (or split) for easy removal. As an alternate, the backing paper shall extend a minimum of 1/8 inch beyond one or more edges of the label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

Label shall be removed from the backing paper by a moderate pull. The backing paper shall be scored or perforated between labels so as to easily remove single labels. No labels shall be in contact with each other. The thickness of the assembled label (label plus backing paper) shall be not less than 0.006 inch, when tested as specified in 4.4.1.

3.7 Printed matter. Labels shall be printed with all the information as shown on the drawing.

3.8 Workmanship. Workmanship shall be first class throughout. Labels shall be free from defects which detract from their appearance or may impair their serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, auditory, etc., investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105.

4.2.2 For tests. Sufficient samples of the components shall be selected to perform tests as required by the applicable subsidiary specifications or by tests specified herein. When sample size is not specified, the sample size for each test shall be as indicated for inspection level S-1 in MIL-STD-105, except that the acceptance number shall be zero (0) for all sample sizes. The unit of product for adhesion test shall be one individual label (end item).

4.2.3 Where possible, the same sample unit shall be used for the determination of two or more test characteristics.

4.3 Examination. The labels shall be examined to determine compliance with all requirements contained in this specification.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.4.1 Backing paper and label stock. The backing paper and label stock shall be tested in accordance with the following standards of the Technical Association of the Pulp and Paper Industry (TAPPI):

TAPPI Standard No.
T 402 m-49
T 403 m-53
T 410 os-61
T 411 m-44

4.4.2 Adhesion test. Remove label from the backing paper and apply to a clean glass surface. The label shall be evenly and firmly placed on the glass surface.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One thousand (1000) labels, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table I shall be packaged in each intermediate and exterior container, as applicable, for the required level of protection specified in procurement document.

Table I. Packaging quantities

Unit package	Intermediate package	Exterior container
Not required	12	48

5.1.2.1 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which will insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Intermediate package. Intermediate package shall be a carton of appropriate size constructed in accordance with PPP-B-566, PPP-B-636, or PPP-B-676. Commercial colors shall be acceptable on paperboard cartons. Closure shall be adequate to prevent spillage of contents under normal handling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class Weather-resistant.

5.2.1.2 Case liner. Each level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes.

5.2.1.3 Closure. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix of PPP-B-636. In addition, waterproofing shall be in accordance with 30.4 of appendix to box specification.

5.2.1.4 Strapping. Strapping, when required, shall be in accordance with appendix of applicable box specification.

NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table I, using type III, class 1 plywood; or shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class Domestic. Closure of fiberboard box shall be in accordance with method I of appendix to box specification.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

Note: The quantity and unit shall be designated on interior packages and exterior container, as follows:

Intermediate package: "12 Roll (of 1000 labels each)".

Exterior container: "48 Roll".

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) Selection of applicable levels of packing (see 5.2).

6.2 Availability of color chips. The individual 3- by 5-inch chips of the color referenced in 3.5 are available from the General Services Administration, Business Service Center, Region 3, Seventh and D Streets, S.W., Washington 25, D.C. Price 5 cents.

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army. - MD
Navy. - MS
Air Force. - 03

Preparing activity:
Defense Supply Agency. - DM

Review activities:
Army. - MD
Navy. - MS
Air Force. - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

FORM APPROVED BUDGET BUREAU NO. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use of the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION LABEL TAPE, PRESSURE SENSITIVE ADHESIVE, "KEEP OUT OF REACH OF CHILDREN" LEGEND, MIL-L-36296(DM), Dated 6 October 1964.

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (ATTACH any PERTINENT DATA WHICH MAY BE OF USE IN IMPROVING THIS SPECIFICATION. IF THERE ARE ADDITIONAL PAPERS, ATTACH TO FORM AND PLACE BOTH IN AN ENVELOPE ADDRESSED TO PREPARING ACTIVITY)

SUBMITTED BY (PRINTED OR TYPED NAME AND ACTIVITY)	DATE

DD FORM 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

CAUTION

NOTICE TO BIDDERS/OFFERORS

DO NOT CONDITION OR BASE YOUR BID/OFFER ON ANY CURRENT PROCUREMENT ON THE INFORMATION SUBMITTED ON THIS FORM SINCE ANY CHANGES OR DELETIONS IN THE SPECIFICATIONS MAY RENDER YOUR BID/OFFER NON-RESPONSIVE IN WHICH CASE IT CANNOT BE CONSIDERED FOR AWARD.

Fold Under

DEFENSE SUPPLY AGENCY
DEFENSE MEDICAL SUPPLY CENTER
3RD AVENUE AND 29TH STREET
BROOKLYN, N.Y., 11232

OFFICIAL BUSINESS

POSTAGE FEES PAID
DEFENSE SUPPLY AGENCY

Defense Supply Agency
Defense Medical Supply Center
ATTN: Directorate of Technical Operations (Code T-HS)
3rd Avenue and 29th Street
Brooklyn, N.Y., 11232

Source: https://assist.dla.mil -- Downloaded: 20261O-21T08:21Z
Check the source to verify that this is the current version before use.