MIL-S-36293A
12 November 1969
SUPERSEDING
MIL-S-36293(DM)
30 September 1964

MILITARY SPECIFICATION

SLIPPERS, CONVALESCENT PATIENTS

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for washable canvas hospital slippers, of the pullman type, suitable to be worn on either foot (see 6.1).

1.2 Classification. The slippers shall be of the following sizes, as specified (see 6.2):

Size 1. - Small (5 to 7)
Size 2. - Medium (7-1/2 to 9)
Size 3. - Large (9-1/2 to 10-1/2)
Size 4. - Extra Large (11 to 13)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

V-T-276	Thread, Cotton.
CCC-C-419	Cloth, Cotton, Duck, Unbleached, Plied-Yarns. (Army and Numbered).
DDD-L-20	Label, for Clothing, Equipage, and Tentage, (General Use).
DDD-T-86	Tape, Textile, Cotton, General Purpose, (Unbleached, Bleached or Dyed).
MMM-A-250	Adhesive, Water-Resistant, (for Sealing Fiberboard Boxes).
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (for Carton Sealing).

Source: https://assist.dla.mil -- Downloaded: 20260-21T08:21Z
Check the source to verify that this is the current version before use.

Military

MIL-T-43566 Tape, Textile, Cotton, General Purpose, Natural or in Colors.

STANDARDS

Federal

Fed. Test Method Std. 191 Textile Test Methods.
Fed. Std. No. 751 Stitches, Seams, and Stitchings.

Military

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 Marking for Shipment and Storage.

DRAWING

MS16686 Medical Services Symbol.

(Copies of specifications, standards and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Guide samples. Guide samples are furnished solely for the guidance and information to the contractor (see 6.2). Variation from the specification may appear in the sample, in which case, the specification shall govern.

3.2 Materials.

3.2.1 Cloth, cotton, duck.

3.2.1.1 Outsole. The cotton duck cloth used for the outsole shall be unbleached and shall conform to type I, No. 1, hard texture, as shown in table I of CCC-C-419. The duck shall be preshrunk and shall not shrink more than 4.0 percent in either the warp or filling direction as tested when specified in 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

3.2.1.2 Coversole and vamp. The cotton duck cloth used for the coversole and vamp shall be unbleached and shall conform to type III of CCC-C-419. The duck shall have a minimum weight of 12.29 ounces per square yard. The duck shall be preshrunk and shall not shrink more than 4.0 percent in either the warp or filling direction as tested when specified in 4.4.

3.2.2 Insole, wool cloth. The wool cloth used for the insole shall be natural or undyed, preshrunk, 21 ounces per square yard (minimum) napped cloth and shall conform to the requirements listed in table I. The wool cloth shall be tested as specified in 4.4.

Table I. Requirements

Yarns per inch (min.)		Breaking strength lbs. (min.)		Wool grade (approx.)	Shrinkage (percent) (max.)		Weave	Color
Warp	Filling	Warp	Filling		Warp	Filling		
27	19	60	40	54s	5.0	5.0	$\frac{2}{2}$ Broken twill	Natural or Undyed

3.2.3 Tape, Cotton.

3.2.3.1 Tying tapes. The cotton textile tape used as the tying tapes and binding of the vamp shall conform to Type I, class 1, 1/2-inch wide tape of DDD-T-86.

3.2.3.2 Binding tape. The cotton tape used as the binding of the slippers shall be a 1 inch wide lightweight tape conforming to Type I class 1 of MIL-T-43566. The tape shall be preshrunk and shall not shrink more than 4.0 percent in the direction of the length, when tested as specified in paragraph 4.4.1.

3.2.4 Threads, cotton. The cotton thread used to assemble the slippers shall conform to Type IA1, 3-ply, ticket No. 24 and Type IA1, 4-ply, ticket No. 12 of V-T-276.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

3.2.5 Identification markings. Each slipper shall have an identification marking conforming to type III or IV of DDD-L-20, on the heel end of the coversole, with the medical services symbol conforming to type I of MS16686. The letters "U" and "S" shall be 1/4 ± 1/16 inch high, and the caduceus of appropriate size. The letters "U" and "S" and the caduceus shall be centered in an ink circle. The letters "S", "M", "L" and "XL" shall be used to indicate the size of the slippers and shall be located directly below the medical services symbol.

3.3 Design. The canvas hospital slippers shall be of a pullman type, consisting of an outsole, insole, a coversole, and vamp. The slippers for any given size shall be interchangeable, using either slipper on either foot.

3.4 Patterns. Standard patterns will be furnished by the Government to the contractor for use in cutting working patterns (see 6.2). The working patterns shall be identical to the Government patterns. Neither the Government patterns or the working patterns shall be altered in any way.

3.5 Stitches, seams, and stitchings. Stitch, seam and stitching types specified herein shall conform to the requirements of Fed. Std. No. 751.

3.5.1 Stitches per inch. The range of stitches per inch as specified shall be interpreted to mean the minimum and maximum number permitted.

3.5.2 Tacking and backstitching. All ends of seams and stitchings, if not caught in other seams or stitching, shall be securely tacked or backstitched. Thread breaks (all stitch types) shall be secured by stitching back of break 1/2 inch to 1 inch.

3.6 Construction. The slippers shall be constructed in accordance with the operations listed below. The contractor is not required to follow the exact sequence of operations provided that the finished slippers are identical to those produced by following the sequence as listed below.

3.6.1 Outsole. The outsole shall be made of one ply of the cotton duck specified in 3.2.1.1.

3.6.2 Insole. The insole shall be made of one ply of the wool cloth which covers the entire outsole, and a second ply of wool cloth which extends from the heel to the middle of the instep. Insole fabric shall be as specified in 3.2.2.

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the currentversion before use.

3.6.3 Coversole. The coversole shall be made of one ply of cotton duck, as specified in 3.2.1.2, and shall cover the entire insole. The coversole shall be marked with the markings specified in 3.2.5.

3.6.4 Vamp. The vamp shall be made of two pieces of the cotton duck specified in 3.2.1.2 and shall be joined together at the midline with the 1/2-inch tape specified in 3.2.3.1. The vamp shall be joined using stitch type 301, seam type SSf-3, using the 12/4-ply thread with from 8 to 10 stitches per inch. The front and rear edges of the vamp shall be bound with the 1/2-inch cotton tape using stitch type 304, seam type BSa-1, using the 24/3-ply thread with 8 to 10 stitches per inch. The vamps shall be open toed, and shall be seamed 3/16 ± 1/16 inch from the toe to the vamp throat, which shall be crescent shaped, 3/4 ± 1/16 inch high and 2 ± 1/16 inches wide. The vamp measurements shall conform to the measurements listed in table II. All measurements and tolerances are expressed in inches.

Table II. Vamp measurements

Size	Top edge line	Bottom edge line	Tolerances
1	3-13/16	6-11/16	± 1/8
2	4-9/16	7-5/16	± 1/8
3	5-5/16	8-1/8	± 1/8
4	5-15/16	9	± 1/8

3.6.5 Tying tapes. Each slipper shall be provided with two tying tapes of 1/2-inch-width cotton tape, securely attached for not less than 5/8 inch of their length to the outside bound rear edge of the vamp, centered 1-1/4 ± 1/8 inches from the bound edge of the sole. Each tying tape shall have a free length of not less than 16 inches. The ends of the tying tapes shall be hemmed or turned over and bartacked, to prevent raveling. The tying tapes shall be secured to the rear edge of the vamp by placing one end (length as specified) under the binding tape, and sewing the binding tape and the tying tapes to the vamp at the same time, using stitch type 304. The tying tapes shall then be laid across the bound edge and stitched down to it, using stitch type 301, or bar tack stitching the entire width of the tying tape. As an alternate method of stitching down the tie tapes to the bound edge of the vamp, a complete row of stitch type 301 may be sewn around the instep binding in lieu of just stitching the tie tapes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

3.6.6 Assembly. The insole and coversole shall first be assembled and stitched diagonally in both directions at intervals of 2 ± 1/4 inches, with the 12/4-ply thread, with from 8 to 10 stitches per inch. The vamp shall extend approximately 3/4 of the distance from the toe to the heel, with the rear edge to fit comfortably over the instep. The sole and the vamp shall then be attached in their proper position, and the complete assembly joined by sewing around the edge using stitch type 301, seam type SSa-1, 12/4-ply thread with 8 to 10 stitches per inch. The entire edge of the assembly shall then be bound with the 1-inch tape, specified in 3.2.3.2, using stitch type 301, seam type BSa-1, 12/4-ply thread with 8 to 10 stitches per inch.

3.7 Size and measurements. Unless otherwise specified, the sizes and measurements of the finished slippers shall be in accordance with table III. All measurements and tolerances are expressed in inches.

Table III. Sizes and measurements

Size	Length	Tolerances	Ball	Tolerances
1	10-1/2	± 5/16-1/8	4	± 3/16 - 1/8
2	11-1/8	± 5/16-1/8	4-1/8	± 3/16 - 1/8
3	11-3/4	± 5/16-1/8	4-1/4	± 3/16 - 1/8
4	12-5/8	± 5/16-1/8	4-1/2	± 3/16 - 1/8

3.8 Workmanship. The finished slippers shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the limits set by the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties).

4.2 Sampling.

4.2.1 Sampling for examination and tests shall be conducted in accordance with MIL-STD-105 and as specified in the following paragraphs.

4.3 Inspection for acceptance. Inspection shall be conducted in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 In-process inspection. An inspection shall be performed during the manufacture of the slippers to see that the proper materials are being used and to determine compliance with all required operations and processes which cannot be determined in the completed end product, and to assure that good workmanship has been employed. Any deviation from requirements or poor workmanship found during in-process inspection shall be cause for rejection of the end item or items.

4.3.2 Inspection of components. An inspection (examination and testing) of components shall be made in accordance with the quality assurance provisions contained in the applicable subsidiary specifications referenced herein to the extent applicable, except that this specification shall govern in the event of conflict. In addition, testing shall be performed on the components listed in table IV for the characteristics noted.

4.3.3 Inspection of the end item. An examination shall be made of the finished slippers for visual and dimensional defects.

4.3.3.1 Examination for visual defects. The defects found during this examination shall be classified in accordance with the defects listed below. The sample unit for this examination shall be one slipper (and the selection shall be by pairs). The lot size shall be expressed in units of one slipper. The sample unit for defects of pairing shall be one pair. Defects of pairing shall be classified as a single defect. The sample size shall be selected in accordance with inspection level II. The acceptance quality levels shall be as specified below:

Major	2.5 defects per 100 units
Total (majors plus minors)	6.5 defects per 100 units

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the current version before use.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties).

4.2 Sampling.

4.2.1 Sampling for examination and tests shall be conducted in accordance with MIL-STD-105 and as specified in the following paragraphs.

4.3 Inspection for acceptance. Inspection shall be conducted in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 In-process inspection. An inspection shall be performed during the manufacture of the slippers to see that the proper materials are being used and to determine compliance with all required operations and processes which cannot be determined in the completed end product, and to assure that good workmanship has been employed. Any deviation from requirements or poor workmanship found during in-process inspection shall be cause for rejection of the end item or items.

4.3.2 Inspection of components. An inspection (examination and testing) of components shall be made in accordance with the quality assurance provisions contained in the applicable subsidiary specifications referenced herein to the extent applicable, except that this specification shall govern in the event of conflict. In addition, testing shall be performed on the components listed in table IV for the characteristics noted.

4.3.3 Inspection of the end item. An examination shall be made of the finished slippers for visual and dimensional defects.

4.3.3.1 Examination for visual defects. The defects found during this examination shall be classified in accordance with the defects listed below. The sample unit for this examination shall be one slipper (and the selection shall be by pairs). The lot size shall be expressed in units of one slipper. The sample unit for defects of pairing shall be one pair. Defects of pairing shall be classified as a single defect. The sample size shall be selected in accordance with inspection level II. The acceptance quality levels shall be as specified below:

Major	2.5 defects per 100 units
Total (majors plus minors)	6.5 defects per 100 units

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties).

4.2 Sampling.

4.2.1 Sampling for examination and tests shall be conducted in accordance with MIL-STD-105 and as specified in the following paragraphs.

4.3 Inspection for acceptance. Inspection shall be conducted in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 In-process inspection. An inspection shall be performed during the manufacture of the slippers to see that the proper materials are being used and to determine compliance with all required operations and processes which cannot be determined in the completed end product, and to assure that good workmanship has been employed. Any deviation from requirements or poor workmanship found during in-process inspection shall be cause for rejection of the end item or items.

4.3.2 Inspection of components. An inspection (examination and testing) of components shall be made in accordance with the quality assurance provisions contained in the applicable subsidiary specifications referenced herein to the extent applicable, except that this specification shall govern in the event of conflict. In addition, testing shall be performed on the components listed in table IV for the characteristics noted.

4.3.3 Inspection of the end item. An examination shall be made of the finished slippers for visual and dimensional defects.

4.3.3.1 Examination for visual defects. The defects found during this examination shall be classified in accordance with the defects listed below. The sample unit for this examination shall be one slipper (and the selection shall be by pairs). The lot size shall be expressed in units of one slipper. The sample unit for defects of pairing shall be one pair. Defects of pairing shall be classified as a single defect. The sample size shall be selected in accordance with inspection level II. The acceptance quality levels shall be as specified below:

Major	2.5 defects per 100 units
Total (majors plus minors)	6.5 defects per 100 units

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECTS	MAJOR	MINOR
Pairing	Both slippers in pair not the same size	X	
Cleanliness	Any spot, stain, or foreign matter clearly noticeable.		X
Design	Any characteristic not in accordance with specified requirements (unless otherwise indicated herein)	X	
Material	Any component not fabricated of the specified material (unless otherwise indicated herein)	X	
	Cuts, holes, tears, heavy slubs, floats broken ends, or any other defect seriously affecting serviceability.	X	
	Streaks, small slubs, floats, coarse filling, or other defect affecting serviceability or appearance but not seriously.		X
	Any mend.	X	
Construction and Workmanship General (applicable to all components unless otherwise indicated herein)	Any component misplaced, operation omitted or not properly performed seriously affecting serviceability or appearance.	X	
	Any component misplaced or operation not properly performed affecting serviceability but not seriously.		X
	Any component missing.	X	
	Any factory damage seriously affecting serviceability.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	MAJOR	MINOR
Construction and Workmanship General (applicable to all components unless otherwise indicated herein) (con.)	Any factory damage affecting serviceability but not seriously.		X
	Any repair (not applicable to restitching)	X	
	Not assembled as specified.	X	
Seams and stitching	Any open seam except in the diagonal stitching of the coversole and insole	X	
NOTE:	A seam shall be considered "open" when one or more stitches are broken or two or more consecutive skipped stitches or runoffs occur.		
	Open seam in diagonal stitches of coversole and insole.		X
	Not specified seam type.	X	
	Not specified stitch type except in the diagonal stitching of the coversole and insole.	X	
	Not specified stitch type in the diagonal stitching of the coversole and insole		X
	Loose stitch tension resulting in a loosely secured seam.	X	
	Tight stitch tension resulting in puckering of fabric or in breakage thread when normal strain is applied.	X	
	Any row of stitching omitted.	X	
	One or two stitches per inch less than specified.		X
	Three or more stitches per inch less than specified except in the diagonal stitching of the coversole and insole.	X	

Source: https://assist.dla.mil -- Downloaded: 202640-21T08:21Z
Check the source to verify that this is the currenversion before use.

EXAMINE	DEFECT	MAJOR	MINOR
	Three or more stitches per inch less than specified in the diagonal stitching of the coversole and insole		X
Seams and stitching (con.)	More than the specified number of stitches per inch		X
	Gauge of stitching irregular		X
	End of seam not backstitched (not applicable to end of a seam that is caught in another row of stitching)		X
Fit of parts	Any part or assembly malformed or not properly affixed causing discomfort to wearer; e.g., coversole seriously wrinkled.	X	
Sole binding	Sole edges not completely caught in by binding.	X	
Vamp length	Does not extend approximately 3/4 of distance from heel to toe.		X
Tie tapes	Any not securely attached.	X	
	Free ends of tie tapes not hemmed or not bartacked.		X
Coversole and outsole.	Soles reversed; i.e., coversole on tread surface.	X	
	Diagonal stitching omitted.	X	
	Diagonal stitching not uniform irregularly accomplished, or deviates from specified pattern.		X
Finishing	Loose thread not trimmed throughout slipper		X
	Slipper is wrinkled or does not otherwise present a neat appearance		X
Marking	Missing, incomplete, incorrect, not legible, not specified type or size, not in proper location, or not accomplished in the specified manner.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.3.3.2 Examination of dimensional defects. Any measurement deviating from the nominal dimensions and tolerances included in tables II and III shall be scored as a measurement defect. The sample unit for this examination shall be one slipper and the selection shall be by pairs. The lot size shall be expressed in terms of one slipper. The sample size shall be selected in accordance with inspection level S-3 of MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

4.3.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packed, selected just prior to the closing operation. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of containers in the end item inspection lot. The sample size shall be selected in accordance with inspection level S-2 of MIL-STD-105. The acceptable quality level shall be 4.0 (one class) defects per 100 units.

Examination	Defect
Markings (Exterior and interior)	Incorrect, illegible, of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective affecting serviceability.
Workmanship	Inadequate application of components such as incomplete closure of case liners, container flaps, loose strapping, etc. Bulging or distortion of containers.
Weight and content (Exterior and interior)	Number per container is more or less than required; gross/net weight exceeds requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

4.4 Tests. The methods for testing specified in Fed-Std-191, wherever applicable, and as listed in table IV, shall be followed. The physical and chemical values specified in section 3 apply to the average of determinations made on a sample unit for test purposes as specified in the applicable test methods. The lot shall be unacceptable if one or more sample units fail to meet any of the test requirements specified. The unit of product for lot formatinn and the unit of product for testing shall be as shown below:

Component	Lot size expressed as	Sample unit for testing
Insole cloth	Yard	3 yards full width
Cotton duck (outsole)-	Yard	3 yards each full width
Cotton duck (coversole and vamp)	Yard	3 yards each full width
Cotton webbing (binding)	Linear yard	4-1/2 linear yards

The selection of the sample size shall be as follows:

Lot size	Sample size
800 or less	2
801 to 22,000	3
22,001 and over	5

Table IV. Testing instructions

Component	Characteristics	Specification reference		No. det. per sample unit
		Rqmt. para.	test method Fed-Std-191	
Insole cloth	Material	3.2.2	1100	1
	Weight	3.2.2	5041	5
	Thread count	3.2.2	5050	
	Warp			5
	Filling			5
	Tensile strength	3.2.2	5100	
	Warp			5
	Filling			5
	Weave	3.2.2	Std. Com'l	1
	Shrinkage	3.2.2	5552	
	Warp			3
	Filling			3
Cotton duck (outsole)	Shrinkage			
	Warp	3.2.1.1	5550	3
	Filling	3.2.1.1	5550	3

Source: https://assist.dla.mil -- Downloaded: 202610-21T08:21Z
Check the source to verify that this is the currenversion before use.

Table IV. Testing instructions (Con't)

Component	Characteristics	Specification reference		No. det. per sample unit
		Rqmt. para.	test method Fed-Std-191	
Cotton duck (coversole and vamp)	Shrinkage			
	Warp	3.2.1.2	5550	3
	Filling	3.2.1.2	5550	3
Cotton tape (binding)	Shrinkage, length	3.2.3.2	4.4.1	5

4.4.1 Shrinkage test.

4.4.1.1 Preparation. Five specimens of tape, each 20 inches in length, shall be used for testing.

4.4.1.2 Procedure. Four liters of water at 100° F. and not over 50 p.p.m. hardness shall be poured into a suitable glass or metal container. The water shall contain 0.2 percent (based on the weight of the tape) of an anionic wetting agent. The tape specimens shall be placed into the container and kept beneath the surface of the water for a period of one-half hour without agitation. At the end of this period, the specimens shall be centrifugally extracted for five minutes in a 17-inch diameter extractor at a speed of 1575 r.p.m. or in any other extractor for a time that will produce an equivalent extraction, and dried in a circulating air oven at a temperature of 200° F. After drying, the specimens shall be pressed with a conventionally heated hand iron; care shall be taken to prevent stretching of tape.

4.4.1.3 Measurement of shrinkage. After reaching equilibrium in the standard atmosphere, the length of the specimens shall be measured, and the shrinkage computed according to the following formula:

$$\text{Shrinkage, Percent} = \frac{\text{Original measurement - measurement after shrinkage}}{\text{Original measurement}} \times 100$$

Measurements shall be taken to the nearest 0.1 inch, and shrinkage shall be reported to the nearest 0.1 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Unit of issue. One (1) pair of slippers, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in table V shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Table V. Packaging quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	96 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Each pair of slippers shall be nested heel to toe with soles turned outward. Each pair shall be further packaged in a plastic bag having an average wall thickness of not less than 0.003 inch. Excess air shall be expelled or evacuated and closure effected by heat sealing.

5.1.3.2 Intermediate package. Intermediate package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class weather-resistant. Boxes shall be closed by taping the top and bottom flaps with two inch wide tape conforming to PPP-T-76. Closing of bottom flap with either adhesive (conforming to MMM-A-250) or metal stitches is permitted. When metal stitches are used, they shall be covered by means of a suitable tape applied over the stitches on the interior surface of the box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for type 2 load, and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table III, using type I, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather-resistant. Closure and strapping shall be in accordance with appendix of applicable box specification.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall conform to PPP-B-601, table II, using type III, class 1 plywood; or shall be designed for type 2 load and constructed in accordance with PPP-B-585, style 3, for class 2 use; PPP-B-621, table I; or PPP-B-636, type CF, class domestic. Closure shall be in accordance with appendix of applicable box specification.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Unit package. Each unit package shall be marked in accordance with MIL-STD-129. The required information shall be printed directly on the bag or on a label inserted withing the bag in such a manner as to permit ready identification. In addition to the markings specified in MIL-STD-129, the name of the contractor shall be shown.

5.3.2 Intermediate package. Intermediate package shall be marked in accordance with MIL-STD-129. Contract or purchase order number and name of contractor shall be shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.

5.3.3 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The slippers are intended to be used by convalescent patients.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) Availability of guide sample (see 3.1).
(d) Availability of patterns (see 3.4).
(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of this specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Military requirements.

Custodians:
Army. - MD
Navy. - MS
Air Force. - 03

Preparing activity:
Defense Supply Agency. - DH

Review activities:
Army. - MD
Navy. - MS
Air Force. - 03

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:21Z
Check the source to verify that this is the current version before use.