INCH-POUND


MIL-PRF-28876/14F(SH)
w/INT. AMENDMENT 1
12 October 2023
USED IN LIEU OF
MIL-PRF-28876/14F
1 March 2021

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, FIBER OPTIC, CIRCULAR, RECEPTACLE STYLE, MULTIPLE REMOVABLE TERMINI, SCREW THREADS, JAMNUT MOUNTING, WITH 90-DEGREE BACKSHELL, ENVIRONMENT RESISTING

This specification is approved for interim use by the Naval Sea Systems Command. Other activities in the Department of Defense may use this interim amendment or may continue using MIL-PRF-28876/14F.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-28876.



Inches	Millimeters
0.006	0.15
0.010	0.25
0.015	0.38
0.020	0.51
0.062	1.57
0.115	2.92
0.125	3.18
0.188	4.78
1.023	25.98

FIGURE 1. Jamnut receptacle connector with 90-degree backshell.

Distribution Statement A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:34Z
Check the source to verify that this is the current version before use.

Shell Size	LL	KK	MM	Z dia max	NN flat	PP dia	TT hex corner max	VV hex nut	M dia max	AE max	AK max
11	0.853 (21.67)	1.368 (34.75)	1.274 (32.36)	0.750 (19.05)	0.841 (21.36)	0.890 (22.61)	1.290 (32.77)	1.079 (27.41)	1.200 (30.48)	4.250 (107.95)	4.250 (107.95)
	0.843 (21.41)	1.348 (34.24)	1.254 (31.85)		0.832 (21.13)	0.880 (22.35)		1.045 (26.54)			
13	0.978 (24.84)	1.508 (38.30)	1.399 (35.53)	0.875 (22.23)	0.966 (24.54)	1.015 (25.78)	1.435 (36.45)	1.205 (30.61)	1.200 (30.48)	4.250 (107.95)	4.250 (107.95)
	0.968 (24.59)	1.488 (37.80)	1.379 (35.03)		0.957 (24.31)	1.005 (25.53)		1.171 (29.74)			
15	1.165 (29.59)	1.681 (42.70)	1.587 (40.31)	1.062 (26.97)	1.153 (29.29)	1.203 (30.56)	1.650 (41.91)	1.392 (35.36)	1.550 (39.37)	4.500 (114.30)	4.700 (119.38)
	1.155 (29.34)	1.661 (42.19)	1.567 (39.80)		1.144 (29.06)	1.193 (30.30)		1.358 (34.49)			
23	1.598 (40.59)	2.108 (53.54)	2.014 (51.66)	1.500 (38.10)	1.587 (40.31)	1.635 (41.53)	2.093 (53.16)	1.812 (46.02)	2.250 (57.15)	5.000 (127.00)	7.500 (190.50)
	1.588 (40.34)	2.088 (53.04)	1.994 (50.65)		1.578 (40.08)	1.625 (41.28)		1.778 (45.16)			

Shell size	Insert figure [1/]	JJ thread class 2A
11	B-1	0.8750-20 UNEF
13	B-2	1.0000-20 UNEF
15	B-3 or B-4	1.1875-18 UNEF
23	B-5 or B-6	1.6250-18 UNEF

FOOTNOTE:

1/ For insert arrangement, see the indicated figure in Appendix B of MIL-PRF-28876.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (mm) are given in parentheses for general information only.
3. Dimensions apply to plated/finished part.
4. Identification marking shall be in accordance with 3.10.3 of MIL-PRF-28876.
5. Optional exposed fasteners are permitted to be 0.25 inch above dimension B.
6. See appendix A of MIL-PRF-28876 for N DIA dimensioning.
7. Hex nut safety wire holes shall be in accordance with MIL-PRF-28876.

FIGURE 1. Jamnut receptacle connector with 90-degree backshell - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and keying configurations. See figure 1 herein and figures A-2, A-3, A-5, A-6, and A-7 of MIL-PRF-28876.

Weight (without termini).

Shell size	Weight, ounces (grams) max
11	10.5 (297.675)
13	11.5 (326.025)
15	14.5 (411.075)
23	28.0 (793.8)

Protective caps. Each connector shall be supplied with protective caps over the front and rear portions of the connector.

Insert arrangement. See Appendix B of MIL-PRF-28876 for desired shell size.

Termini. For style P (pin) terminus or style S (socket) terminus, see MIL-PRF-29504/14 and MIL-PRF-29504/15, respectively. For dummy terminus, see MIL-PRF-29504/3.

Sealing gasket or O-ring. The receptacle shall include a sealing gasket or O-ring to seal between the receptacle flange and the mounting panel.

Shell polarization. For 1 through 6 keyway positions, see figure A-3 of MIL-PRF-28876.

Part or Identification Number (PIN). Marked on the coupling ring of the plug (see table I).

M	**28876**	**/14**	**X**	**X**	**X**	**X**	**X**	**X**
Prefix for military specification	Specification number	Spec sheet no.	Shell size designator (see table I)	Insert arrangement number (see table I)	Backshell dash number (see table I)	Terminus/ insert style (see table I)	Key position number (see table I)	Class designator (see table I)

TABLE I. PIN designators.

Shell size	Shell size designator	Insert arrangement number	Backshell dash number (see table II)	Terminus/ insert style	Key position	Class designator (see table III)
11	A	1	1 or 2	P or S	1, 2, 3, 4, 5, or 6	T or blank
13	B	1	1, 2, or 3	P or S	1, 2, 3, 4, 5, or 6	T or blank
15	C	1 or 2	1, 2, or 3	P or S	1, 2, 3, 4, 5, or 6	T or blank
23	F	1 or 2	1, 2, or 3	P or S	1, 2, 3, 4, 5, or 6	T or blank

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:34Z
Check the source to verify that this is the current version before use.

TABLE II. Backshell dash number.

Shell size	Shell size designator	Maximum cable outer diameter in accordance with backshell dash number inch (mm)		
		1	2	3
11	A	0.250 (6.35)	0.346 (8.79)	--
13	B	0.285 (7.24)	0.346 (8.79)	0.453 (11.50)
15	C	0.515 (13.08)	0.256 (6.50)	0.375 (9.53)
23	F	0.866 (22.00)	1.000 (25.40)	0.600 (15.24)

TABLE III. Class designators.

Class designator	Description
Blank	Aluminum with non-conductive finish
T	Aluminum with conductive plating

Example: M28876/14B12P1

Backshell and insert retention nut attachment. Not applicable.

Fiber optic cable diameter. See table II.

Mating counterpart. Plug connectors are specified in MIL-PRF-28876/6 through MIL-PRF-28876/9. Dust covers are specified in MIL-PRF-28876/15.

Installation and removal tools. As specified in Drawing 499-6872813.

NOTES:

Referenced documents. In addition to MIL-PRF-28876, this specification sheet references the following documents:

MIL-PRF-28876/6	MIL-PRF-28876/7	MIL-PRF-28876/8
MIL-PRF-28876/9	MIL-PRF-28876/15	MIL-PRF-29504/3
MIL-PRF-29504/14	MIL-PRF-29504/15	Drawing 499-6872813

AMENDMENT NOTATIONS. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:34Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Preparing activity:
Navy – SH
(Project 6060-2023-025)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:34Z
Check the source to verify that this is the current version before use.