
INCH-POUND
MIL-PRF-28876/26E
1 March 2021
SUPERSEDING
MIL-PRF-28876/26D
4 October 2004

PERFORMANCE SPECIFICATION SHEET

CONNECTORS, FIBER OPTIC, CIRCULAR, PLUG AND RECEPTACLE STYLE, MULTIPLE REMOVABLE TERMINI, SCREW THREADS, WALL MOUNTING, WITH SHORT BACKSHELL, NON-ENVIRONMENT RESISTING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-28876.



Inches	Millimeters	Inches	Millimeters
0.010	0.25	0.380	9.65
0.016	0.41	0.470	11.94
0.030	0.76	0.878	22.30
0.100	2.54	0.898	22.81
0.130	3.30	0.978	24.81
0.188	4.78	1.263	32.08
0.200	5.08		

FIGURE 1. Wall mounting receptacle connector with short straight backshell.

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:35Z
Check the source to verify that this is the current version before use.

Shell Size	W	X	DD dia max	Z dia max	NN across flats	AH	AL max	A flats max	Y TIR	Insert figure 1/
15	0.130 (3.30)	1.278 (32.46)	1.124 (28.55)	1.062 (26.97)	1.153 (29.29)	4.613 (117.17)	3.60 (91.44)	0.750 (19.05)	0.968 (24.59)	B-3 or B-4
	0.115 (2.92)	1.238 (31.45)			1.144 (29.06)	4.573 (116.15)				

FOOTNOTE:

1/ For insert arrangement, see the indicated figure in Appendix B of MIL-PRF-28876.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (mm) are given in parentheses for general information only.
3. Dimensions apply to plated/finished part.
4. Identification marking shall be in accordance with 3.10.3 of MIL-PRF-28876.
5. For mating key dimensions and configurations, see figure A-3 of MIL-PRF-28876.
6. See appendix A of MIL-PRF-28876 for second location of Z DIA and dimensioning.
7. See appendix A of MIL-PRF-28876 for N DIA dimensioning.

FIGURE 1. Wall mounting receptacle connector with short straight backshell - Continued.

REQUIREMENTS:

Dimensions and keying configurations. See figure 1 herein and figures A-2, A-3, A-5, A-6, and A-7 of MIL-PRF-28876.

Weight (without termini).

Shell size	Weight, ounces (grams) max
15	11.5 (326.025)

Protective caps. Each connector shall be supplied with protective caps over the front and rear portions of the connector.

Insert arrangement. See Appendix B of MIL-PRF-28876 for desired shell size.

Termini. Style P (pin) or S (socket) (see MIL-PRF-29504/14 and MIL-PRF-29504/15). (For dummy terminus, see MIL-PRF-29504/3.)

Shell polarization. 1 through 6 keyway positions (see figure A-3 of MIL-PRF-28876).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:35Z
Check the source to verify that this is the current version before use.

Part or Identification Number (PIN). Marked on coupling ring of plug (see table I).

M	**28876**	**/26**	**X**	**X**	**X**	**X**	**X**	**X**
Prefix for military specification	Specification number	Spec sheet no.	Shell size designator (see table I)	Insert arrangement number (see table I)	Backshell dash number (see table I)	Terminus /insert style (see table I)	Key position number (see table I)	Class designator (see table I)

TABLE I. PIN designators.

Shell size	**Shell size designator**	**Insert arrangement number**	**Backshell dash number (see table II)**	**Terminus/ insert style**	**Key position**	**Class designator (see table III)**
15	C	1 or 2	1, 2, or 3	P or S	1, 2, 3, 4, 5, or 6	T or blank

TABLE II. Backshell dash number.

Shell size	**Shell size designator**	**Maximum cable outer diameter in accordance with backshell dash number inch (mm)**		
		1	2	3
15	C	0.515 (13.08)	0.256 (6.50)	0.375 (9.53)

TABLE III. Class designators.

Class designator	**Description**
Blank	Aluminum with non-conductive finish
T	Aluminum with conductive plating

Example: M28876/26C12P1

Fiber optic cable diameter. See table II.

Mating counterpart. Receptacle connectors are specified in MIL-PRF-28876/1 through MIL-PRF-28876/5 and MIL-PRF-28876/11 through MIL-PRF-28876/14. Dust covers are specified in MIL-PRF-28876/10.

Installation and removal tools. As specified in Drawing 499-6872813.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:35Z
Check the source to verify that this is the current version before use.

NOTES:

Referenced documents. In addition to MIL-PRF-28876, this specification sheet references the following documents:

MIL-PRF-28876/1	MIL-PRF-28876/2	MIL-PRF-28876/3
MIL-PRF-28876/4	MIL-PRF-28876/5	MIL-PRF-28876/10
MIL-PRF-28876/11	MIL-PRF-28876/12	MIL-PRF-28876/13
MIL-PRF-28876/14	MIL-PRF-29504/3	MIL-PRF-29504/14
MIL-PRF-29504/15	Drawing 499-6872813	

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – SH
Air Force – 85
DLA – CC

Preparing activity:
Navy – SH
(Project 6060-2014-039)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:35Z
Check the source to verify that this is the current version before use.