MIL-P-10018F
8 May 1984
SUPERSEDING
MIL-P-10018E
8 September 1978

MILITARY SPECIFICATION

PAIL, COLLAPSIBLE, 10-QUART, CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a collapsible pail fabricated from a rubber coated cotton drill fabric and supported by a metal frame.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
FF-R-556	-	Rivet, Solid, Small; Rivet, Split, Small; Rivet, Tubular, Small; Burr; and Cap, Rivet; General Purpose
QQ-S-700	-	Steel Sheet and Strip, Medium and High Carbon
QQ-W-461	-	Wire, Steel, Carbon (Round, Bare, and Coated)
TT-E 529	-	Enamel, Alkyd, Semi-gloss

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

CCC-C-426 - Cloth, Drill, Cotton
DDD-L-20 - Label: For Clothing, Equipage and Tentage (General Purpose)
PPP-B-636 - Boxes, Shipping, Fiberboard

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods
FED-STD-595 - Colors
FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-2-138 - Pail, Collapsible, 10-Quart Capacity; Illustration, Assembly and Sections
2-2-139 - Pail, Collapsible, 10-Quart Capacity; Details

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitations for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 209 - Aluminum Alloy, Plate and Sheet
B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 1424 - Tear Resistance of Woven Fabrics by Falling-Pendulum (Elmendorf) Apparatus
D 3951 - Standard Practice for Commercial Packaging

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:21Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide samples. Samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.1.2 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials (see 6.5). Materials specified shall conform to the applicable documents and requirements specified herein.

3.2.1 Base fabric. The base fabric used in the manufacture of the coated fabric shall be cotton drill cloth conforming to type III, class 3 of CCC-C-426. The color of the base fabric shall be Olive Green 107 to match the standard sample (see 6.3).

3.2.1.1 Copper and manganese. The dyed base fabric shall contain not more than 0.003 percent copper or 0.0015 percent manganese when tested as specified in 4.4.1.2.

3.2.2 Coating compound. The compound used to coat the base fabric shall be synthetic rubber suitably plasticized and pigmented to produce a shade of Olive Green 207 when tested as specified in 4.4.1.2, except that the use of natural rubber is permissible in the anchor coat. Reclaimed rubber shall not be used.

3.2.3 Coated fabric. The coating compound specified in 3.2.2 shall be applied to one side only of the fabric specified in 3.2.1 and suitably vulcanized. After vulcanization, the coated fabric shall conform to the requirements specified in table I when tested as specified in 4.4.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

TABLE I. Physical requirements of coated fabric

Weight, ounces per square yard	18.0	maximum
Breaking strength, pounds:		
Warp	90	minimu
Filling	55	minimum
Hydrostatic resistance, pounds per square inch	45	minimum
Tearing strength, pounds, scale reading (with NBS augmenting weight):		
Warp	70	minimum
Filling	80	minimum
Stiffness, millimeters (warp only):		
At 70° ± 2°F	60	maximum
At 32° ± 2°F	80	maximum
At 32° ± 2°F after accelerated weathering	80	maximum
Abrasion (50 cycles)	1/	
Adhesion of coating, pounds/2-inch width	8.0	minimum
Accelerated weathering	2/	

1/ No loose fibers of the base fabric shall be exposed in the center 1 inch of the abraded portion. The specimens shall be examined in the warp direction only.

2/ The specimen shall not become stiff and brittle or soft and tacky.

3.2.4 Seam-sealing compound. The seam-sealing compound shall have a synthetic rubber base, shall be self-vulcanizing, and shall not contain any reclaimed rubber. The compound shall be compatible with the coated fabric and have good adhesion.

3.2.5 Thread, polyester. The thread for all stitching shall conform to type I, class 1, sub-class B, size FF of V-T-285. The thread shall be dyed Olive Drab S-1 (CA 66022) and shall show fastness to weathering equal to or better than the standard shade sample (see 6.3). If no standard shade sample is available, the thread shall show good fastness to weathering.

3.2.6 Rings, top and bottom, steel The rings shall be fabricated from hot-rolled, round-edge SAE No. 1025 or 1030 steel conforming to QQ-S-700 and shall be in accordance with the dimensions specified on Drawing 2-2-139.

3.2.7 Stays, hinged, steel. The hinged stays shall be fabricated from SAE No. 1025 or 1030 steel conforming to QQ-S-700 and shall be in accordance with the dimensions specified on Drawing 2-2-139.

3.2.8 Bail, wire, steel. The bail shallbe fabricated from Steel No. 1010 through 1020 steel wire conforming to QQ-W-461 and shall be in accordance with the dimensions specified on Drawing 2-2-139.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:21Z
Check the source to verify that this is the currentversion before use.

3.2.9 Rivets and washers, steel. All rivets except the shouldered rivets shall conform to type VI, grade E of FF-R-556, in the sizes shown on the applicable drawings. The shouldered rivets shall conform to the material and composition of the above rivets and be in accordance with the design and dimensions specified on Drawing 2-2-139. The steel washers specified on the applicable drawing shall conform to current commercial standards.

3.2.10 Stops, aluminum. The aluminum alloy stops shall be fabricated from sheet conforming to 5052-H24 or 5052-H34 temper of ASTM B 209 and shall conform to Drawing 2-2-139.

3.2.11 Handle, bail, wood. The bail handle shall be fabricated from any hardwood commercially used for bail grips. The design and dimensions of the handle shall be in accordance with Drawing 2-2-139.

3.2.12 Enamel. The enamel used for the wood handles shall conform to type 1 of TT-E-529. Enamel used on steel parts shall conform to type II of TT-E-529. The color of all enamel shall be black conforming to No. 27038 of FED-STD-595.

3.3 Construction. The coated side of the fabric shall form the inside of the pail. The construction shall conform in all respects to the drawings listed in section 2 and as specified herein.

3.3.1 Stitching. All stitching shall conform to type 301 of FED-STD-751, with 8 to 10 stitches per inch and 1/8 inch stitching margin.

3.3.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided the requirements for stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying stitches, overlapping stitches, or backstitches are used to secure the ends of stitching.

3.3.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1 inch except where ends are caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose or excessively tight stitching and the lock shall be imbedded in the materials sewn.

3.3.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin runouts occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

b. Thread breaks, or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.3 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.3.1.4 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.3.2 Sealing of seams. All seams shall be made completely waterproof by sealing on the inside of the pail with a minimum of three coats of seam-sealing compound applied by brushing or squeezing onto the seams. The sealed seams shall withstand a hydrostatic pressure of 150 centimeters for 15 minutes without leakage when tested as specified in 4.4.5. All seams shall show no leakage or seepage when tested as specified in 4.4.5.

3.3.3 Setting of rivets. The rivets shall be well headed to insure a secure fastening of components while allowing the components to rotate freely with respect to one another. The rivets shall be free from sharp edges after peening.

3.4 Description of frame. The frame shall consist of two rings, one at the top and one at the bottom, joined at opposite sides by hinged stays. Each ring shall be hinged so that it may be folded on itself to form a semicircle. The stays shall be formed for rigidity with convex surfaces outward. The hinge shall be so designed as to allow the stay to fold completely on itself in one direction and to lock in the extended or straight position. The bail shall be capable of being folded inside the pail proper after it is attached to the pail.

3.5 Finish. All steel parts shall be zinc coated to conform to type IV finish, SC3 of ASTM B 633 followed by enamel conforming to that specified in 3.2.12. The coating shall level out to a uniform film without objectionable orange peel, wrinkles, drops, streaks, or areas of thin film or no film. After fabrication, the wood handle shall be coated with the enamel specified in 3.2.12.

3.6 Marking. The identification marking shall conform to type IV, class 5 of DDD-L-20 and shall be applied in the location shown on Drawing 2-2-139. The "U.S." and special marking shall conform to type IV, class 9 of DDD-L-20 and shall be applied on the outside of the pail in the size and location shown on Drawing 2-2-139. Fastness of class 9 markings shall be as specified for class 5 labels.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:21Z
Check the source to verify that this is the currentversion before use.

3.7 Workmanship. The fabric shall be free of holes, cuts, tears, or other damaged areas. Thread tension shall be maintained so that there will be no loose stitching and seam allowances shall be maintained with seams properly sewn so that no runoffs, twists, pleats, or open seams shall result. Care shall be taken in sewing to see that no needle chews occur. Hardware shall not be malformed or broken. All metal parts shall be free of sharp edges. Fabric shall be free of grease or oil stains. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.4.5. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. A certificate of compliance shall be furnished with each shipment or lot stating the following:

(a) Synthetic rubber was used in the formulation of the sealing and coating compounds and that reclaimed rubber was not used (see 3.2.2 and 3.2.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

(b) The coating compound has been properly vulcanized (see 3.2.3).

(c) Sewing thread was not lubricated (see 3.3.1.4).

4.4.1.2 Component testing. In addition to the quality assurance provisions of the subsidiary documents, tests shall be performed as specified in table II for the characteristics shown. The lot size for coated fabric shall be expressed in units of 1 yard. The sample unit shall be 3 yards full width of the coated fabric and 1/4 yard of the base fabric. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 4.0.

TABLE II. Component tests

Characteristic	Requirement reference	Test method	Determinations per sample unit	Results reported as: Pass or fail	Results reported as: Numerically to nearest
Copper and manganese content 1/	3.2.1.1	2053 2/	1	X	---
Color	3.2.2	4.5.4	1	X	---
Weight	Table I	5041 2/	5	-	0.1 ounce
Breaking strength	Table I	5100 2/	5	-	1 pound
Hydrostatic resistance	Table I	5512 2/ 3/	5	-	1 psi
Tearing strength	Table I	ASTM D 1424	5	-	1 pound
Stiffness:					
At 70° ± 2°F	Table I	5204 2/	5	-	1 mm
At 32° ± 2°F	Table I	5204 2/	5	-	1 mm
At 32° ± 2°F after accelerated weathering	Table I	5204 2/ 4/	5	-	1 mm
Abrasion	Table I	5304 2/ 5/	3	X	---
Adhesion of coating	Table I	5970 2/	5	-	0.1 pound per 2-inch width
Accelerated weathering	Table I	4.5.3	1	X	---

1/ Applicable to testing of base fabric prior to coating.

2/ Test method of FED-STD-191.

3/ The water pressure shall be applied to the coated side of the fabric. The results shall be reported as the average of the highest four specimens of the five tested per sample unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

4/ Test specimens shall be subjected to the accelerated weathering test specified in 4.5.3 before testing for stiffness.

5/ The coated side of the cloth shall be tested using 3 pounds pressure and 6 pounds tension. Breaking strength determinations shall not be made (see table I, footnote 1/).

4.4.2 In-process examination. Inspection shall be made during manufacture, to determine that operations or assemblies are in accordance with requirements of Drawings 2-2-138 and 2-2-139. Whenever nonconformance is noted, corrections shall be made to the items affected and lot in-process. Items which cannot be corrected shall be removed from production.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of pails. The sample units shall be one pail. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total (major and minor combined) defects.

TABLE III. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, thin or weak place due to abrasion, multiple floats or open place, exposed fabric on coated side, tunnels or delaminations of coating, crease or wrinkle, or coating missing.	X	
Hardware	Broken or malformed, finish omitted, corroded area, burrs or sharp edges, any malfunction of hardware.	X	
Rivet(s)	Misplaced.	X	
	Improperly set; i.e., peened tight so that clinched parts will not rotate.		X
Washer(s)	Not placed against fabric.	X	
	Any omitted.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Open seams	1/2 inch or less.		X
	More than 1/2 inch.	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double-stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Run-offs (see open seams)			
Seam and stitch type	Wrong seam or stitch type.	X	
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; excessively tight resulting in puckering of fabric.		X
Stitches per inch	Up to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
	Variation in the number of stitches per inch, caused by the operator's speeding up the machine and pulling the fabric in order to sew over heavy places or in turning corners, shall be classified as follows:		
	a. Within the major defect classification - Minor defect.		
	b. Within the minor defect classification - No defect.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitching margin, stitching gage	Larger than specified by more than 1/8 inch for more than 2 inches.		X
	Stitching margin less than specified for more than 2 inches.	X	
	Stitching gage less than specified for more than 2 inches.		X
Stitching ends	Backstitched less than 1 inch (except where ends are held down by other stitching or turned under in a hem).		X
Thread breaks	Overstitched less than 1 inch.		X
NOTE:	Thread breaks not overstitched shall be classified as an open seam.		
Components and materials	Any component part omitted or not as specified, or any required operation omitted (unless otherwise classified herein).	X	
	Needle chews.	X	
	Seam twisted or pleated.	X	
	One or more required rows of stitching omitted.	X	
	Any mend, darn, or patch.	X	
	Any part of seams or stitching not thoroughly coated with sealing compound.	X	
	Sealing compound applied on outside of pail instead of inside.	X	
Marking	Omitted; incorrect; illegible; misplaced, or size characters not as specified.		X
Cleanness	Grease or oil stains clearly noticeable, thread ends not trimmed to 1/4 inch or less.		X
Finish	Coating not uniform, i.e., contains objectionable orange peel, wrinkles, drops, streaks, or areas of thin film or no film.		X

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:21Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end item shall be examined for conformance to the specified dimensions. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of pails. The sample unit shall be one pail. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

4.4.5 End item testing. The end item shall be tested as specified in 4.5.1 and 4.5.2 for conformance to the hydrostatic and leakage requirements specified in 3.3.2. The lot size shall be expressed in pails. The quantity of items required should be as specified in the contract. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.6 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with table IV. the sample unit shall be one shipping container fully packaged except that it need not be closed. Examination of closure defects listed below shall be made on shipping containers fully packaged. The lot size shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE IV. Packaging defects

Examine	Defect
Marking	Omitted; incorrect; illegible; of imporper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components such as: Incomplete closure of container flap, loose strapping or taping, or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than required.

4.4.7 Palletization inspection. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:21Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limit.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.5 Methods of inspection.

4.5.1 Hydrostatic test. All seams of the pail, shall be tested as specified in Method 5516 of FED-STD-191 with the following exceptions. Water pressure shall be applied to the sealed side of the seam with the seam in the center of the 4-1/2 inch test area. The hydrostatic head shall be raised to 150 centimeters and maintained at this height for 15 minutes. Appearance of water along any portion of the test seam shall be a defect.

4.5.2 Leakage test. A completely fabricated pail shall be filled with tap water, suspended from the bail and allowed to remain at room temperature for 24 hours. Any evidence of leakage or seepage of water on the outer surface of the pail at the end of the test period shall be a defect.

4.5.3 Accelerated weathering test. The test shall be performed with filters for a period of 100 hours on a specimen 6-1/2 by 6-1/2 inches minimum, with the coated side exposed, as specified in Method 5804 of FED-STD-191. After exposure the specimen shall be allowed to dry and then conditioned for 4 hours before evaluating.

4.5.4 Color matching. The color of the coating compound shall match the standard shade sample (see 6.3) under artificial daylight having a color temperature of 7000 $\pm$ 500 kelvins and shall be a good approximation to the standard shade under incandescent lamplight at 2850 $\pm$100 kelvins.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each collapsible pail shall be collapsed down to a circle.

5.1.2 Commercial. The pails shall be preserved in accordance with ASTM 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:21Z
Check the source to verify that this is the currentversion before use.

5.2.1 Level A packing. Thirty collapsible canvas pails, preserved as specifeid in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Pails, preserved level A, shall be packed on edge, alternated top to bottom, 30 in length, 1 in width, and 1 in depth within a shipping container. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.2 Level B packing. Thirty collapsible canvas pails, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Pails, preserved level A, shall be packed on edge, alternated top to bottom, 30 in length, 1 in width, and 1 in depth within a shipping container. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6.

5.2.3 Commercial packing. Pails, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), pails packed as specified in (5.2), shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appeandix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The pail is for general purpose use. It is not intended to be used for the storage of potable water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

6.2 Ordering data,. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1.2, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. When weather-resistant fiberboard is required for level B shipments (see 5.2.2.1).
e. When palletization is required (see 5.3).

6.3 Samples. For access to standard shade samples of base fabric and coating compound and guide samples of the item, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of two completed pails. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for inspection and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8465-0880

Review activities:

Army - MD
Air Force - 82

User activities:

Navy - MC
Air Force - 45

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:21Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-10013F	Pail, Collapsible, 10-Quart, Capacity

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:21Z
Check the source to verify that this is the current version before use.