MIL-S-9964A(USAF)
1 December 1969
SUPERSEDING
MIL-S-9964(USAF)
30 January 1963

MILITARY SPECIFICATION

SAW, HAND, FINGER GRIP, SURVIVAL, TYPE MB-2

1. SCOPE

* 1.1 Scope. This specification covers one type of survival saw which is included in survival kits used by the United States Air Force.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-P-416	Plating, Cadmium (electrodeposited)
QQ-S-766	Steel Plates, Sheets and Strip - Corrosion Resisting
GGG-B-431	Blades, Saw, Round (Machine and Hand)

Military

MIL-H-15424	Hand Tools, Packaging of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables of Inspection by Attributes
MIL-STD-130	Identification Marking of U.S. Military Property

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.

National Bureau of Standards

Handbook H28 Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

National Aerospace Standards

NAS 1300 Thumbscrew

(Copies of National Aerospace Standards' publications may be obtained upon application to the Aerospace Industries Association of America, Inc., 610 Shoreham Building, Washington, D. C. 20005.)

DRAWINGS

U. S. Air Force

Part Number	Description
56B3640	Saw, Hand, Type MB-2
56B3641	Grip, Finger, Survival Saw
56C3800	Bag, Survival Saw
56C3801	Saw, Survival, Assembly of

(The above drawings are an integral part of this specification.)

3. REQUIREMENTS

* 3.1 First article. This specification includes requirements for first article testing. The supplier shall furnish not less than six saw assemblies as a preproduction sample for testing in accordance with section 4. The sample shall be either preproduction items or production items which conform to the requirements of this specification. In either case, the first article shall be manufactured in the same facilities used for manufacture of the production items. Approval of the preproduction sample does not relieve the supplier of responsibility for compliance with all provisions of this specification.

* 3.2 Design. The saw assembly shall conform to the configuration and dimensions shown on the above listed Air Force drawings and shall be capable of performing the tests specified in section 4.

* 3.3 Unit pack. Each unit pack shall include one complete saw assembly and one spare saw blade (see drawing 56C3801).

* 3.4 Threads. All threads shall be in the inch system and shall conform to H-28.

Source: https://assist.dla.mil -- Downloaded: 20260-17T13:17Z
Check the source to verify that this is the current version before use.

* 3.5 Components. The saw assembly shall consist of two grip assemblies, two blade mounting thumb screws and one round saw blade (see drawing 56B3640).

* 3.5.1 Grips. Each grip assembly shall consist of one blade holder and one ring. The configuration, dimensions and type of material shall be as shown on drawing 56B3641. The soldered joint shall blend smoothly to allow 360 degree free rotation of the ring in the blade holder.

* 3.5.2 Thumb-screws. Blade mounting thumb screws shall conform to NAS 1300-3-6 or equal.

* 3.5.3 Saw blade. The blade shall conform to GGG-B-431, Type I, Style C, .040 inch diameter, 13 turns per inch by 20 ± 1/4 inch long. (See drawing 56B3640.)

* 3.6 Surface treatment. All component parts of the saw assembly except the saw blade shall be corrosion preventative treated in accordance with QQ-P-416, Type I, Class 2.

* 3.7 Identification marking. Each unit pack shall be marked for identification in accordance with MIL-STD-130 as shown on drawing 56C3800.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Test report. The supplier shall furnish a certified test report showing that the first article sample conforms to all requirements of this specification and that each saw assembly in the first article sample has successfully passed the tests specified in 4.5.

* 4.2 Classification of examination and tests. The examination and tests required to assure conformance of those items or lots of items offered for acceptance shall be classified as first article test and quality conformance inspection.

* 4.3 Inspection lot. All saw assemblies that have been packaged, marked for identification and offered for delivery at one time shall be considered a lot for purposes of examination and tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.

* 4.3.1 Sampling for quality conformance. Samples shall be taken from the inspection lot in accordance with MIL-STD-105, based on single sampling plan for normal inspection at the level specified. Defects in excess of the acceptance number shall be cause for rejection of the representative lot.

* 4.4 Test method.

* 4.4.1 Visual and dimensional inspection. Each saw assembly in the sample shall be visually and dimensionally inspected for conformance with section 3. Classification of defects shall be as specified in Table I. Sampling shall be at inspection level I with an acceptable quality level (AQL) of 2.5 percent defective for major defects and 6.5 percent defective for total defects.

TABLE I
CLASSIFICATION OF DEFECTS

Category	Defects
Major:	
101	Assembly not complete.
102	Spare blade not included in pack.
103	Blade kinked, broken, or length not as specified.
104	Threads damaged or not complete.
105	Ring bent, will not rotate in blade holder, or ends not securely joined.
106	Configuration and dimensions not as specified.
107	Not treated for corrosion preventative as specified.
108	Preservation, packaging, packing and marking not as specified.
Minor:	
201	Burrs or sharp edges.
202	Pits, modules, or deep scratches.
203	Plating chipped, peeling, or flaked.
204	Marking not legible, incomplete, or missing.

* 4.4.2 First article test. Each saw assembly in the first article sample shall be examined for defects specified in Table I and tested in accordance with 4.5. One or more major defects or failure of any saw assembly to pass all tests in 4.5 shall be cause for rejection.

* 4.4.3 Quality conformance inspection. All samples taken in accordance with 4.3.1 shall be examined for defects specified in Table I and tested in accordance with 4.5. The sample shall be divided into three equal groups and each saw assembly in the separate group shall be subjected to one of the sawing tests in 4.5. One saw assembly, taken at random from each group, shall be tension tested as specified in 4.5.4. Sampling shall be at inspection level II with an acceptable quality level (AQL) of 1.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.

* 4.5 Performance tests.

* 4.5.1 Plastic cutting. Saw at least 6 inches through 1/8 inch thick plexiglass.

* 4.5.2 Wood cutting. Saw through at least two pieces of 2 X 4 inch solid pine lumber.

* 4.5.3 Steel cutting test. Saw 1/8 inch deep through 8 gage stainless steel conforming to QQ-S-766, Class 1, condition A, in not more than 15 sawing strokes.

* 4.5.4 Tension load test. Clamp the grip ring at one end of the saw assembly in a fixed holding device and apply a 50 pound tension load for at least 30 seconds to the ring on the opposite end. Blade separation from either holder, blade breakage, permanent ring deformation, or thread damage, in the blade holder or on the thumb screw, shall be cause for rejection.

* 4.6 Inspection of preparation for delivery. Preservation, packaging, packing and marking shall be inspected to assure compliance with the requirements of section 5.

* 5. PREPARATION FOR DELIVERY

* 5.1 Preservation, packaging and packing. The saws shall be cleaned, preserved, packaged, packed and marked for shipment in accordance with the provisions of MIL-H-15424. Level of preservation, packaging and packing shall be as specified (see 6.2).

* 6. NOTES

* 6.1 Intended use. The saw assembly covered by this specification is for use by aircrew members in an emergency survival situation.

* 6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Selection of applicable levels of preservation, packaging, packing and marking for shipment (see 5.1).

* 6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contents irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 20260-17T13:17Z
Check the source to verify that this is the currenversion before use.

Custodian:

Air Force - 84

Preparing Activity:

Air Force - 84

Project Number:

5110-F237

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.

The digital copy of MIL-S-9964A dated 1-Dec-1969, does not include 4 foldout pages.
Please call the ASSIST SERVICE DESK at 215-737-8000 for copies of these pages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the ecification in procurement of products for ultimate use by the Department of Defense. This sheet is pro- ded for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION
Saw, Hand, Finger Grip, Survival, Type MB-2 MIL-S-9964A(USAF)

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE. AE-WP-O-MAY 64 505

Source: https://assist.dla.mil -- Downloaded: 2026-01-17T13:17Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE

WRAMA (WRNEMI)
Robins AFB Ga 31093
UNITED STATES AIR FORCE
OFFICIAL BUSINESS

WRAMA (WRNEMI/Mr. Normand)

Robins AFB Ga 31093

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:17Z
Check the source to verify that this is the current version before use.