MILITARY SPECIFICATION

COVER, BED FRAME

This specification is approved for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope This specification covers a cotton duck bed-frame cover for use th an adjustable hospital bed

2. APPLICABLE DOCUMENTS

2.1 Issues of documents The following documents, of the issue in effect on te of invitations for bid or requests for proposal, form a part of this specifi-tion to the extent specified herein

SPECIFICATIONS

FEDERAL

V-T-276	- Thread, Cotton
V-T-285	- Thread, Polyester
CCC-C-419	- Cloth, Cotton Duck, Unbleached, Plied-Yarns, Army and Numbered
CCC-D-950	- Dyeing and After Treating Processes for Cotton Cloths
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-C-496	- Clip, End, Strap.
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	- Buckle, Tongueless and Web Strap
MIL-T-5038	- Tape, Textile and Webbing, Textile, Reinforcing, Nylon

STANDARDS

FEDERAL

FED-TEST METHOD-STD-NO 191	- Textiles, Test Methods
FED-STD-NO 751	- Stitches, Seams, and Stitchings

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Defense Personnel Support Center, Directorate of Medical Materiel, DPSC-ATI, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7210

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS

DEFENSE PERSONNEL SUPPORT CENTER (DPSC)

25024 - Bed, Folding, Hospital, Field

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer)

3 REQUIREMENTS

3 1 First article When specified in the procurement document, the contractor shall furnish sample unit(s) for first article inspection (see 4 1 2 1 and 6 2)

3 2 Material Except as hereinafter specified, materials shall conform to the applicable portions of the specifications, standards, and drawing listed herein Materials shall be subjected to the tests and meet the requirements specified in these documents The metals shall conform to the chemical and physical requirements of the applicable specifications Materials, not specifically designated herein, but used in the fabrication of the cover, shall be suitable for the purpose intended

3 2 1 Cotton duck Cotton duck shall be pre-shrunk such that residual shrinkage shall be not more than 2.0 percent in the direction of either the warp or the filling when tested as specified in 4 5.1

3 2 1 1 Government Furnished Material (GFM) When specified (see 6 2) the cotton duck cited in 3 2 1 shall be furnished as GFM The contractor is required to examine the GFM upon receipt, and prior to use, to determine that the GFM is free from defects such as those cited in the Classification of Defects (Table III) The sampling plan used in the examination shall be at least that required herein if the contractor were to purchase the material

3 3 Design and construction The cover shall be constructed in accordance with the applicable portions of DPSC Drawing No 25024 and as specified herein (Sheet No 6 of the drawing, and pages 4 and 5 of the Bill of Materials thereto, contain all references to the cover)

3.4 Stitching All stitching required in the fabrication of the cover shall be Type 301 or 401 of FED-STD 751. There shall be 8 to 10 stitches per inch. When machine stitching is not continuous or is broken, there shall be not less than 1/2 inch overstitching at each break All stitching shall be backtacked not less than 1/4 inch at the ends, to prevent unraveling except where the ends

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

are turned under in a hem or held down by other stitching Thread tension shall be properly maintained so that the lock shall be embedded in approximately the center of the materials sewed All edges which are not selvaged shall be hemmed with stitching, Type EFb-1 or FED-STD 751 All seams shall be straight and evenly spaced

3 5 Treatment The finished cloth shall be type I, olive drab No. 7, class B of CCC-D-950, except that the cloth shall be made mildew resistant by treatment limited to one of the following mildew inhibitors

a 2,2' Metnylene-Bis (4-Chlorophenol)
b Copper -8- Quinolinolate

3.6 Identification marking Each cover shall be marked, on the underside, permanently and legibly, with the contract or purchase order number, the name or registered trademark of the manufacturer and the National Stock Number

3 7 workmanship Workmanship shall be first class throughout Item shall be free from defects which detract from its appearance or impair its service-ability

4 QUALITY ASSURANCE PROVISIONS

4 1 Responsibility for inspection. Unless otherwise specified in the contract. the contractor is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified in the contract. the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified nerein. unless disapproved by the Government The Government reserves the right to perform any of the inspections set forth in the specification wnere such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4 1 1 Records Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time. during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate

4 1.2 Inspection Inspection, as used in this specification, is defined as both examination (such as visual and auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item

4 1 2 1 Classification of inspection The inspection requirements specified nerein are classified as follows

a. First article inspection
b. Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

4 1 2 1 1 First article inspection. First article inspection shall be performed on the cover when a first article sample is required (see 3.1). This inspection shall include examination of 4.4 and tests of 4.5

4 1 2.1.2 Quality conformance inspection Quality conformance inspection shall include the examination of 4 4 and tests of 4 5

4 1 3 Certificates of quality Certificates of quality, supplied by the manufacturer of the materials may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demonstrated to the Government and provided also that the test methods and the results obtained comply with those described in this specification The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the Item Identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

4.2 Inspection lot

4 2 1 Raw materials An inspection lot for raw material inspection shall be all material produced under the same conditions and controlled to the degree that uniformity of product within the designated lot can be assured Lot identification of the raw material by the manufacturer is one method of control, as cited above, which is considered acceptable

4 2 2 End product An inspection lot for inspection of end product shall consist of all covers of the same type produced under essentially the same conditions and offered for inspection at one time

4.3 Sampling

4 3 1 For examination Sampling for examination shall be conducted in accordance with MIL-STD-105, and table I The unit of product for sampling purposes shall be one cover

TABLE I Sampling for examination

	Inspection level	AQL (defects per hundred units)
For visual examination		
Major defects	II	2.5
Total defects (Major and Minor combined)	II	6.5
For dimensional examination	S-1	6.5

4.3.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and table II, for an acceptance level of zero.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling for tests.

Component (Unit of product)	Characteristic	Requirement	Test procedure	Inspection level
Cotton duck	Shrinkage Breaking strength 2/	3.2.1 3.2.1.1	4.5.1 4.5.2	1/ 1/

1/ Sample size for cotton duck shall be as follows

Lot size in yards	Sample size
800 or less	2
801 to 22,000	3
22,000 and over	5

2/ Certificate shall be acceptable for non-Government-furnished material

4.4 Examination. The cover shall be examined to determine compliance with all requirements contained in this specification.

4.4.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects listed in table III. Examination shall not be restricted to the classified possible defects listed below.

TABLE III. Classification of defects.

Categories	Defects
Major	
101	Any component missing or not as specified
102	Any component improperly aligned or assembled
103	Stitched seam incomplete or missing
104	Material has tear, hole, or rip
Minor	
201	Edge loose or unraveled
202	Number of stitches not as specified
203	Thread break not overstitched at least 1/2 inch
204	End of stitching not backstitched at least 1/4 inch (unless hemmed or held down by other stitching)
205	Edge not hemmed or selvaged
206	Color not as specified
207	Identification marking missing, incomplete, or illegible
208	Blemish or imperfection in the weave of the cotton duck greater than 1/8 inch long
209	Seam not straight or evenly spaced

4.4.2 Dimensional examination. The cover shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein shall be classified as a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

4.4 3 Packaging inspection The inspection of the unit package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129

4 5 Tests Tests shall be conducted to determine compliance with specification requirements

4 5 1 Shrinkage Cotton duck shall be tested for shrinkage as specified in Test Method 5550 of FED-TEST METHOD-STD-NO 191

4 5 2 Breaking strength Government-furnished cotton duck shall be tested for breaking strength in accordance with method 5100 of FED-TEST METHOD-STD-NO 191

5 PACKAGING

5 1 Packaging Packaging shall be level A or C, as specified (see 6 2)

5 1 1 Unit of issue Each cover, as specified, constitutes a unit of issue

5 1.2 Level A

5 1 2 1 Unit package Each cover shall be neatly folded to an approximate dimension of not more than 13 by 20 inches in such a manner that all metal buckles are within the interior folds Each folded cover shall be wrapped in kraft paper and the wrap secured with kraft gummed tape As an alternate each folded cover may be packaged in a clear polyethylene bag having a minimum thickness of 0 003 inch thickness Closure of the bag shall be made by heat sealing or by means of a tuck or reverse flap A 1/4 inch diameter hole shall be made at one corner of the bag to allow excess air to escape

5 1 3 Level C. Each cover shall be neatly folded and packaged in a manner that will afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity

5 2 Packing Packing shall be level A, B or C as specified (see 6 2)

5 2 1 Level A Four unit packages shall be packed in a shipping container designed for a type 2 load and conforming to PPP-B-636, class weather-resistant Closure, strapping and waterproofing shall be as specified in the appendix of the box specification.

5 2 2 Level B Four unit packages shall be packed in a shipping container designed for a type 2 load and conforming to PPP-B-636, class domestic Closure shall be as specified in the appendix of the box specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

5 2 3 Level C The packaged covers shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity These packs shall conform to the carrier's rules and regulations.

5 3 Marking Each unit package and shipping container shall be marked as specified in MIL-STD-129

NOTE Polyethylene bags shall have the required information printed directly on the bag across the center face or on a paper label inserted in the bag in such a manner to permit ready identification

6. NOTES

6.1 Intended use. The cover is intended for use with adjustable bed, NSN 6530-01-015-5189 or NSN 6530-00-935-4184.

6 2 Ordering data Purchasers should select the preferred options permitted herein and include the following information in procurement documents

a Title, number and date of this specification
b Selection of applicable levels of packaging and packing (see 5 1 and 5 2)
c When a first article is required (see 3 1, 4 1 2.1 and 6.3)
d Whether Government-furnished Material is to be supplied (see 3 2 1 1 and 6 4)

6 3 First article When a first article is required, it shall be tested under the appropriate provisons of the Defense Acquisition Regulation/ Armed Services Procurement Regulation The contract or purchase order specifies the quantity, procedure for delivery and other specific instructions for inspection and approval of the first article

6 4 Government Furnished Material (GFM) When GFM is specified in the contract or purchase order, the procuring agency will provide a sufficient quantity of 9 85 oz Army Duck The contract or purchase order will include this information along with the procedure and destination of the delivery

6 5 This specification covers the following item appearing in the Federal Supply Catalog

National Stock Number	Item Identification
7210-00-118-0008	COVER, BED FRAME, Cotton Duck, 26-3/4 by 77-5/8 inches

Custodians
Army - MD
Navy - MS
Air Force - 03

Preparing activity
DLA-DM

Project No. 7210-0232

Review activity:
DoD - MB

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter when name and address is provided within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-37827 COVER, BED FRAME

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID



DEFENSE PERSONNEL SUPPORT CENTER
DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:34Z
Check the source to verify that this is the current version before use.