MILITARY SPECIFICATION

TERBUTALINE SULFATE TABLETS

This specification is approved for use by the Defense Personnel Support Center, Defense Logistics Agency, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers Terbutaline Sulfate Tablets, (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-C-186	- Containers, Packaging and Packing for Drugs, Chemicals and Pharmaceuticals.

STANDARDS

FEDERAL

FED-STD-140	- Tablets (for Medicinal Purposes).

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Hq, Defense Personnel Support Center, ATTN: Directorate of Medical Materiel, DPSC-ATT, 2800 South 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6505

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

U. S. DEPARTMENT OF HEALTH, EDUCATION, AND WELFARE,
FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder.

(Application for copies should be addressed to the Food and Drug Administration, Washington, DC 20204.)

U. S. PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia (USP).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

The National Formulary (NF).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

3. REQUIREMENTS

3.1 Material. Shall be Terbutaline Sulfate Tablets, and shall be in accordance with all applicable requirements of FED-STD-140, and as specified herein.

S2. Classification. Shall be Type I.

S5.3 The following is added to this paragraph:

Tablets shall contain 5 mg of terbutaline sulfate per tablet within the designated assay limits for the tablets.

S6.4.9.1 Disintegration. Tablets shall disintegrate in not more than 10 minutes when determined in accordance with the procedure described in the USP for "Uncoated Tablets".

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

3.2 Ingredients.

3.2.1 Active ingredient - terbutaline sulfate.

3.2.1.1 Identification. Shall comply with the identity tests as specified in 4.4.4.1.

3.2.1.2 Loss on drying. Shall lose no more than 0.5 percent when tested in accordance with 4.4.4.2.

3.2.1.3 Residue on ignition. Shall not exceed 0.2 percent when determined by the method as specified in 4.4.4.3.

3.2.1.4 Heavy metals. Shall not exceed 0.0025 percent when determined by the method as specified in 4.4.4.4.

3.2.1.5 Water content. Shall not exceed 0.5 percent when determined as specified in 4.4.4.5.

3.2.1.6 Absorbance of extractable impurities. Shall not exceed an absorbance reading of 0.100 at any wavelength when determined as specified in 4.4.4.6.

3.2.1.7 Absorbance of 3,5-Dihydroxy-w-t-butylaminoacetophenone sulfate. Shall not exceed 0.3 percent (absorbance not greater than 0.470) when determined as specified in 4.4.4.7.

3.2.1.8 Chloride. Shall not exceed 0.0100 percent when determined as specified in 4.4.4.8.

3.2.1.9 Protolytic impurities. Shall contain not more than 0.3 percent calculated as acetic acid, when determined as specified in 4.4.4.9.

3.2.1.10 Assay - titrimetric. Shall contain not less than 98.0 percent and not more than 101.0 percent of $(C_{12}H_{19}NO_3)_2 \cdot H_2SO_4$ - terbutaline sulfate when determined as specified in 4.4.4.10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

3.3 Other ingredients. All other ingredients used in the manufacture of the tablets shall comply with S5.1 of FED-STD-140.

3.4 Expiration dating period. The expiration dating period shall be not less than 36 months.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and, (i) as to any expiration dated item, for the expiration dating period specified by the contractor for such item, or such longer period as may be required by regulation of any federal agency; or (ii) as to non-dated items, for not less than 3 years after delivery of the item to the Government.

4.1.2 No company supplying any ingredient(s) to the contractor will be considered an acceptable facility for the performance of the inspection requirements specified herein.

4.2 Packaging inspection. The inspection of the intermediate package, packing and marking for shipment and storage shall be in accordance with quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

4.3 Labeling inspection. Sampling shall be in accordance with MIL-STD-105 and the unit of product shall be the unit of issue. The inspection lot shall be the number of units of issue of each batch, lot, control number, etc., offered for inspection at one time. The inspection level for labeling shall be S-2 and the acceptance number shall be zero.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

4.4 Tests and examinations. Tests and examinations shall be performed to determine compliance with all requirements of this document and all referenced documents.

4.4.1 Tests.

4.4.1.1 Assay for terbutaline sulfate in the finished tablet.

Reagents and Solutions

Hydrochloric Acid, 0.1N
Dilute 8.5 ml of concentrated hydrochloric acid, reagent grade with purified water to 1000 ml.
4-Aminoantipyrine Solution
Dissolve 2.0 gram of 4-aminoantipyrine, reagent grade in 100 ml of purified water. Prepare this solution fresh.
Potassium Ferricyanide Solution
Dissolve 8.0 gram of potassium ferricyanide, anhydrous, reagent grade in 100 ml of purified water. Prepare this solution fresh.
Tris-buffer, pH 9.5 (0.3M)(THAM)
Dissolve 36.3 gram of tris (hydroxymethyl) aminomethane, reagent grade in 100 ml of purified water and qs to 1000 ml. Adjust the pH to 9.5 with 1N hydrochloric acid.
Terbutaline Sulfate Reference Solution
Accurately weigh approximately 50 mg of terbutaline sulfate reference standard into a 50 ml volumetric flask. Dissolve in and dilute to volume with purified water. Pipet 10.0 ml of the solution into a 100 ml volumetric flask and dilute to volume with purified water. (Note: Retain the solution for Content Uniformity Test.)

Procedure

Accurately weigh a minimum of 20 tablets and determine the average tablet weight. Reduce the tablets to a fine powder. Accurately weigh a portion of powder, equivalent to about 5 mg of terbutaline sulfate, and transfer to a 50 ml volumetric flask. Shake with 5.0 ml of 0.1N hydrochloric acid and 10 ml of purified water for 15 minutes, dilute to volume with purified water, mix and filter through #1 Whatman paper or equivalent. Prepare a blank solution by diluting 5.0 ml of 0.1N hydrochloric acid to 50 ml with purified water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

Pipet 5.0 ml of sample, standard and blank solutions into individual 50 ml volumetric flasks. To each flask add
35 ml of pH 9.5 tris-buffer solution and mix;
1.0 ml of 4-aminoantipyrine solution and mix;
1.0 ml of potassium ferricyanide solution and mix, and dilute to volume with pH 9.5 tris -buffer solution and mix. Determine the absorbance of the sample, standard and blank solutions exactly 75 seconds after the addition of the potassium ferricyanide solution. Measure the absorbance of the solutions against pH 9.5 tris-buffer solution at 550 nm in 1 cm cells with a suitable spectrophotometer.

Calculation:

$$\frac{A - Ao}{As - Ao} \times \frac{Ss}{S} \times \frac{W}{10} = \text{mg terbutaline sulfate/tablet}$$

Where:
A = absorbance of sample solution
As = absorbance of standard solution
Ao = absorbance of blank solution
S = sample weight in mg
Ss = weight of standard in mg
W = average weight/tablet in mg

4.4.2 Identification.

4.4.2.1 Sulfate.

Reduce 5 tablets to a fine powder. Add 25 ml of purified water and shake for 10 minutes. Filter and acidify 2 ml of filtrate with 2-3 drops of 2M hydrochloric acid. A white precipitate is formed on addition of 2-3 drops of 1 M barium chloride.

4.4.2.2 Thin layer chromatography.

Reagents and Solutions

Ethanol, 50 percent
Dilute 5.0 ml of absolute ethanol to 10 ml with purified water.
Developing Solution
Prepare a solution of cyclohexane/isopropanol/formic acid in ratio of 25:65:5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

4-Aminoantipyrine, 2 percent
Dissolve 2.0 gram of 4-aminoantipyrine in 100 ml of methanol.
Potassium Ferricyanide, 8 percent
Dissolve 2.0 gram of potassium ferricyanide in 5 ml of purified water and 20 ml of concentrated ammonium hydroxide.
Terbutaline Sulfate Reference Solution
Accurately weigh 10 mg of reference standard and dissolve in 1.0 ml of 50 percent ethanol.

Equipment
Chromatographic Plate
20 x 20 cm (or 10 x 20 cm) glass plates precoated with silica gel GF254, to a thickness of 0.25 mm. The plates can be used without activation.

Procedure
Transfer 2 tablets, equivalent to 10 mg of terbutaline sulfate to a centrifuge tube. Add 1.0 ml of 50 percent ethanol and shake for 10 minutes and centrifuge. Spot 2 ul of the sample solution and 2 ul of the standard solution on the plate. Place the plate in the saturated development tank and allow the solution to travel 10 cm. Remove the plate from the tank and dry with a stream of air. Spray the plate with 2 percent 4-aminoantipyrine solution. Let the plate air-dry and spray with 8 percent potassium ferricyanide solution. The sample and the standard appear as red-violet spots at approximately the same Rf value.

4.4.3 Content uniformity.

Reagents and Solutions
Same as specified in 4.4.1.1 Assay for terbutaline sulfate in the finished tablet.

Procedure
Assay a minimum of 10 tablets individually. Transfer each tablet to a 50 ml volumetric flask. Add 10 ml of purified water and 5 ml of 0.1N hydrochloric acid and shake the mixture on a mechanical shaker for 20 minutes. Dilute to volume with water, shake and filter through Whatman #1 filter paper. Continue as directed in assay procedure (see 4.4.1.1) beginning "...Prepare a blank solution..."

Calculation:

$$\frac{A - Ao}{As - Ao} \times Ss \times \frac{1}{10} = \text{mg terbutaline sulfate/tablet}$$

Where:
A = absorbance of sample solution
As = absorbance of standard solution
Ao = absorbance of blank solution
Ss = standard weight in mg

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

4.4.4 Active ingredient. The terbutaline sulfate powder shall comply with the following:

4.4.4.1 Identification.

4.4.4.1.1 Infrared absorption.

The infrared absorption spectrum of a potassium bromide dispersion of it (approximately 1 mg in 300 mg of KBr) exhibits maxima only at the same wavelengths as that of a preparation of terbutaline sulfate reference standard similarly prepared and measured.

4.4.4.1.2 Ultraviolet absorption.

The ultraviolet absorption spectrum of a solution with with a final concentration of approximately 75 ug per ml in 0.1N hydrochloric acid exhibits maxima and minima at the same wavelengths as that of a similar solution of terbutaline sulfate reference standard, concomitantly measured in a 1-cm cell, with a suitable spectrophotometer.

4.4.4.1.3 Sulfate.

To one drop of a 2 percent solution of sample, add 2 ml of purified water, acidify with 2M hydrochloric acid, and add a few drops of 1M $BaCl_2$ solution. A white precipitate shall form.

4.4.4.2 Loss on drying. Shall be determined using an accurately weighed sample of 1.0 gram dried to constant weight at 105°C, using the USP method.

4.4.4.3 Residue on ignition. Shall be determined as follows:

Accurately weigh about 1.0 gram of sample in a tared crucible which has been previously heated to 850°C and cooled to room temperature. Ignite the sample in air to a temperature not to exceed 650°C. (The sample may be stirred with a platinum wire if it does not sinter at the bottom of the crucible.) Cool the residue. (If all the carbon has not been consumed, moisten the residue cautiously with a few drops of concentrated hydrogen peroxide solution. Carefully heat to dryness, and ignite until only a small quantity of carbon remains.) Moisten the residue with 3 drops of 1M sulfuric acid and heat gently to dryness. Heat the residue to 800-850°C until all the residue is ignited. Ignite to 800-850°C for 5 minute periods until the weight difference between two successive weighings is no greater than 0.5 mg.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

4.4.4.4 Heavy metals. Shall be determined as follows:

Reagents and Solutions

Standard Lead Solution
Dissolve 0.183 gram of lead acetate trihydrate in 5 ml of 2M acetic acid in a 1-liter volumetric flask. Dilute to volume with purified water. Pipet 1.0 ml of this solution into a 100 ml volumetric flask and dilute to volume with carbon dioxide-free purified water.
Sodium Sulfide Solution 0.25M
Dissolve 6.0 grams of sodium sulfide ($Na_2S.9H_2O$) in 40 gram of glycerol (Fischer Certified reagent or equivalent) and dilute to 100 ml with purified water. Filter the solution, if necessary.

Procedure
Thoroughly mix 0.66-0.67 gram of sample with 0.20 gram of anhydrous sodium sulfate in a quartz crucible. Heat cautiously, until the sample is charred. Ignite at 750-800°C until the residue is white. Cool to room temperature and add 1.0 ml of 2M hydrochloric acid. Heat cautiously to boiling. Add 14.0 ml of warm purified water and allow the mixture to cool to room temperature. Pipet 9.0 ml of this solution and 1.0 ml of 2M sodium acetate solution into a test tube. Pour the solution into a flat bottom test tube (15 mm x 70 mm) containing 1 drop of 0.25M sodium sulfide solution. After one minute, compare the color intensity with 10.0 ml of standard lead solution treated in a similar manner. The color intensity of the sample solution should not be greater than that of the standard solution when observed against a white background, a few centimeters away from the bottom of the tubes.

4.4.4.5 Water. Shall be determined by the USP Karl Fischer electrometric end point method using approximately 1.5 gram of sample.

4.4.4.6 Absorbance of extractable impurities. The absorbance shall be determined as follows:

Accurately weigh about 0.290-0.300 gram of sample into a 100 ml separator and dissolve in 30 ml of purified water. Shake with 30 ml of water-saturated chloroform. Collect the chloroform layer in a centrifuge tube (A).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

Dissolve 1.0 gram of sodium bicarbonate in the water layer. Add 2.0 ml of 1N sodium hydroxide solution. Shake with 30 ml of water-saturated chloroform and collect the chloroform extract in a separate centrifuge tube (B). Centrifuge the chloroform extracts (A and B) for 10 minutes. Determine the absorbance of each chloroform extract in 1 cm cells against water-saturated chloroform from 360 to 250 nm using suitable scanning spectrohotometer.

4.4.4.7 Absorbance of 3,5-dihydroxy-w-t-butylaminoacetophenone sulfate. Shall be determined as follows:

Prepare a 2.00 percent solution of the sample by weighing 2.00 gram accurately and dissolving in 100 ml of 0.01N hydrochloric acid. Determine the absorbance of the solution at 330 nm in a 1 cm cell against 0.01N hydrochloric acid as the blank with a suitable spectrophotometer.

4.4.4.8 Chloride. Shall be determined as follows:

Hydrochloric Acid, 0.100N
Standard Chloride Solution, 0.0001N Hydrochloric Acid (3.5ug/ml Cl)
Dilute 10.0 ml of 0.1N hydrochloric acid with purified water to 100.0 ml. Dilute 10.0 ml of this solution with purified water to 1000 ml. Do not store this solution for more than 1 week.

Accurately weigh 350 mg of sample and transfer quantitatively to a test tube. Dissolve in 10 ml of purified water, add 1.0 ml of 2M nitric acid. Transfer the solution into a comparison tube (15 x 70mm) containing 3 drops of 0.1M silver nitrate. Allow the mixture to stand for 1 minute and compare against exactly 10.0 ml of the standard chloride solution, 1.0 ml of 2M nitric acid and 3 drops of 0.1M silver nitrate. The opalescence of the sample should not be greater than the standard solution when tubes are observed at eye level with the eye at right angles to the tubes, and in penetrating light, against a black background.

4.4.4.9 Protolytic impurities. Shall be determined as follows:

Procedure
Accurately weigh about 0.2 gram of sample and transfer to a suitable vessel containing 10 ml of carbon

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

dioxide-free purified water. Titrate potentiometrically to about pH 6 with 0.02N sodium hydroxide standard volumetric solution using glass/calomel electrodes and a 1 ml buret. An inflection point will occur at about pH 5.5 if acetic acid is present. Perform a blank determination and make the necessary correction. (Adjust the sample weight and the amount of purified water to the buret size, if necessary.)

Calculation:

$$\frac{(V-Vb) \times N \times 60 \times 100}{S} = \text{percent acetic acid}$$

Where:
V = ml of sodium hydroxide cosumed by the sample
Vb = ml of sodium hydroxide consumed by the blank
N = normality of sodium hydroxide
S = sample weight in mg

4.4.4.10 Assay. Shall be determined as follows:

Perchloric Acid, 0.1N in Glacial Acetic Acid
Prepare and standardize as directed in the USP.

Procedure
Accurately weigh approximately:
100 mg (for use with 2.5 ml buret)
400 mg (for use with 10 ml buret)
of sample into a suitable titration vessel and dissolve by warming in
15 ml (for 2.5 ml buret)
60 ml (for 10 ml buret)
of glacial acetic acid. Cool to room temperature and add
15 ml (for 2.5 ml buret)
60 ml (for 10 ml buret)
of Acetonitrile (USP). Titrate potentiometrically with 0.1N perchloric acid in glacial acetic acid using glass/calomel electrodes (lithium chloride in acetic acid). Perform a blank determination.

Calculation:

$$\frac{(V-Vb)N}{S} \times 54.86 = \text{percent terbutaline sulfate}$$

Where:
V = ml of perchloric acid consumed by the sample
Vb = ml of perchloric acid consumed by the blank
N = normality of perchloric acid
S = sample weight in gram

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with all applicable requirements of PPP-C-186, and as specified herein.

5.2 Packaging. Packaging shall be level A or C, as specified (see 6.1

5.2.1 Unit of issue. One bottle containing 100 tablets, as specified, constitutes one unit of issue.

5.2.2 Level A.

5.2.2.1 Immediate container. The immediate container shall be a commercially available bottle considered acceptable by the Food and Drug Administration (FDA) for the product contained therein and shall be of such compatibility that neither the contents nor the container are altered in any way by each other. The closure shall be P (child-proof).

5.2.2.2 Unit package. At the option of the contractor, each unit may be packaged as specified in 5.2.5 of PPP-C-186.

5.2.2.3 Intermediate package. Twelve (12) units of issue shall be packaged as specified in 5.2.7.1 of PPP-C-186.

5.2.3 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.3 Packing. Packing shall be level A, B or C, as specified (see 6.1)

5.3.1 Level A. One hundred forty-four (144) units of issue shall be packed as specified in 5.4.4. of PPP-C-186.

5.3.2 Level B. One hundred forty-four (144) units of issue shall be packed as specified in 5.4.3.1.1 of PPP-C-186.

5.3.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.4 Marking.

5.4.1 Labeling. Labeling shall be in accordance with the requirements of the Federal Food, Drug, and Cosmetic Act and shall include the information required below:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

5.4.1.1 Immediate container. Each immediate container label shall bear the following information:

(a) label information in accordance with commercial practice.
(b) the expiration date.

5.4.1.2 Unit package. Each unit package label shall bear the following information:

(a) label information in accordance with commercial practice.
(b) the National Stock Number.

NOTES: (1) The National Stock Number shall not be preceded by any prefix.
(2) Strip labeling may be used.
(3) Label adhesion test shall not apply.
(4) If a unit package is not supplied, the National Stock Number shall appear on the immediate container label.

5.4.2 Intermediate package. Intermediate package shall be marked as specified in 5.5.3 of PPP-C-186. Type I shelf life markings as specified in MIL-STD-129 shall be shown. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE 15° - 30°C (59° - 86°F)".

5.4.3 Exterior container. Exterior container shall be marked as specified in 5.5.4 of PPP-C-186. Type I shelf life marking as specified in MIL-STD-129 shall be shown. Marking shall include the legend: "STORE AT CONTROLLED ROOM TEMPERATURE 15° - 30°C (59° - 86°F)".

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) National Stock Number.
(c) Selection of applicable levels of packaging and packing (see 5.2 and 5.3).

6.2 This specification covers the following item:

National Stock Number	Item Identification
6505-01-039-2808	TERBUTALINE SULFATE TABLETS, 5 mg, 100s

Preparing activity:
DLA - DM

Project No. 6505-1984

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-T-37836(DLA-DM) TERBUTALINE SULFATE TABLETS

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T11:35Z
Check the source to verify that this is the current version before use.