TIER II ADOPTION NOTICE

SAE-AMS5701 “Nickel Alloy, Corrosion- and Heat-Resistant, Bars, Forgings, Flash Welded Rings and Forging Stock 41.5Ni - 16Cr - 37Fe - 2.9Cb (Nb) - 1.8Ti Consumable Electrode Remelted or Vacuum Induction Melted 1800 °F (982 °C) Solution Heat Treated” was adopted on 17MAR1989 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity at engineering.standards@us.af.mil or AFLCMC/EN Engineering Standards, Bldg 28 Rm 118, 2145 Monahan Way, WPAFB, OH 45433-7017.

This specification covers a corrosion- and heat-resistant nickel alloy in the form of bars, forgings, flash welded rings up to 4.00 inches (101.6 mm), inclusive, and stock for forging or flash welded rings of any size. This document may be obtained from www.sae.org, CustomerService@sae.org, or SAE International, 400 Commonwealth Drive, Warrendale PA 15096.

Custodians:
Army – MR
Air Force – 20
DLA – CQ

Adopting Activity:
Air Force – 20
(Project 9535-2023-001

Review Activities:
Air Force – 11

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

FSC 9535

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T16:20Z
Check the source to verify that this is the current version before use.