INCH-POUND

MIL-C-48683A (AR)
AMENDMENT 4
5 September 2000
SUPERSEDING
AMENDMENT 3
9 June 1993

MILITARY SPECIFICATION

CARTRIDGE, 40MM, M918 TP; PROJECTILE ASSEMBLY

MIL-C-48683A was inactivated on 8 February 1996 for new design.

This amendment forms a part of Military Specification MIL-C-48683A (AR), dated 26 October 1987, and is approved for use by the U.S. Army Armament, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1.1, Specifications, Military, Delete:

"MIL-P-116 – Preservation, Method of"

PAGE 2

* 2.1.1, Standards, Military:

Add: "MIL-STD-2073 – Standard Practice for Military Packaging"

Delete: "MIL-STD-1235 – Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes" and substitute "MIL-STD-1916 – DOD Preferred Methods for Acceptance of Product."

PAGE 3

* 2.2, Under American Society for Testing and Materials, Add:

"ASTM C208 – Cellulose Fiber Insulating Board"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Add to 3.4:

"For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

PAGE 5

* 4.3.1, Delete "Spring, Anti-Creep 9399395 50" and substitute "Spring, Anti-Creep 9399408 50"

4.3.1, Change:

From: "Body Assembly 9399402 50"
To: "Body Assembly (prior to Painting) 9399402 25
Body Assembly (after Painting) 9399402 25"

PAGE 7

* Table I, Delete "Dwg. 9399395" and substitute "Dwg. 9399408"

PAGE 8

Add to Projectile Assembly (Dwg. 9399374) under functioning:

"Petalling (missing petals), 200 5/, 1-2 6/, 3.4, 4.5.6, 4.5.6.2, 4.5.6.3

Petalling (blown base), 200 5/, 0-1, 3.4, 4.5.6, 4.5.6.2, 4.5.6.3".

Add Note 5:

"5/ Projectiles fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases."

Add Note 6:

"6/ One defect consists of one or more missing petals per projectile."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

Table I Change,

From: “Body Assembly (Dwg. 9399402)

Examination for defects	50	3.2	4.4.2.12/4.4.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9”

To: “Body Assembly (prior to painting) (Dwg. 9399402)

Examination for defects	25	3.2	4.4.2.12
Body Assembly (after painting) (Dwg. 9399402)	25	3.2	4.4.2.13
Salt Spray	4	3.2	4.5.2.2
Push test of rotating band	50	3.2	4.5.9”

Add to Note 1:

“For 1,000 meter test, sound and smoke or sound and flash are also acceptable.”

Add Major 110:

“110. Missing or improperly placed groove,.40,3.2,Visual”

Minor 206, Delete in its entirety and substitute the following:

“206. Poor workmanship .65 2/ 3.5 Visual”

Add Note 2 as follows under Notes:

“2 Total surface imperfections for nicks, dents, scratches and voids in color shall not exceed 2.5% of the total surface of the part with any individual indentation not to exceed 0.010 in. in depth provided the items pass the salt spray requirements per paragraph 4.5.2.1.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 15

* 4.4.2.6, Delete in its entirety.

Add new paragraph 4.4.2.6.1 as included page 15a:

* 4.4.2.6.1, Delete paragraph number “4.4.2.6.1” and substitute “4.4.2.6 and delete “(alternate)” in title block.

PAGE 17

4.4.2.8:

Delete Major 101: “101. Wall Thickness, Min, .40 1/, 3.2, Gage”

Add Minor 205: “205. Wall Thickness, Min, .65 1/, 3.2, Gage”

Change from “201 to 201
202 202
202 203
201 204”

PAGE 18

4.4.2.9:

Delete Major 101: “101. Wall Thickness, Min, .40 1/, 3.2, Gage”

Add Minor 205: “205. Wall Thickness, Min, .65 1/, 3.2, Gage”

PAGE 20

* 4.4.2.11, Delete Major 102 and 103 in their entirety.

4.4.2.11, Delete Major 104 and Major 106 in their entirety.

4.4.2.11, Minor 205, Delete in its entirety.

4.4.2.11, Delete Major 107 in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-C-48683A (AR)
AMENDMENT 4

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6.1	Spring, Anti-Creep (alternate)				9399408
					NEXT HIGHER ASSEMBLY 9399390
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL or 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE/INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Load Test	125	Acc-1 Rej-2		4.5.3
102.	Length		.40		Gage
103.	Outer diameter		.40		Gage
MINOR					
201.	Poor workmanship		.65		Visual

NOTES:

Source (15th): https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.4.2.11, Major 108, Delete “Total”

4.4.2.11, Change From: “Thickness of groove (6) in base”
To: “Thickness below groove (6) in base”

PAGE 21

* 4.4.2.12, Add the following new Major characteristics:

“107. Pitch diameter of thread .40 3.2 Gage
108. Minor diameter of thread .40 3.2 Gage”

Add to 4.4.2.12:

“105. Runout of indicated point of taper with outside large diameter .40 3.2 Gage/9399396

106. Location, large diameter on taper .40 3.2 Gage/9399396”

PAGE 22

Add Major 104:

“104. Missing or improperly placed markings .40 3.2 Visual”

PAGE 23

4.4.2.14, Delete Major 106:

“106. “135-200 Feet test 50 0-1”

Add Major 106:

“106. 135-200 Feet test 50 0-2
100 1-2”

Delete Major 102:

“102. Gap between body and ogive, min, .40 3.2 Gage”

Renumber Majors as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

"102. True position, rotating band to ogive diameter .40 3.2 Gage

103. Assembly torque, prior to sealant cure 3/ 3.2 4.5.4

104. Pressure test 125 3-4 3.2 4.5.5

105. Functioning, 1000 meter, min, test 144 6-7 4/ 3.4 4.5.6, 4.5.6.1 135 to 200 feet, test, 50 0-1 4/ 3.4 4.5.6, 4.5.6.1

106. Airburst, 194 2/ 0-1 3.4 4.5.6 4.5.6.1 4.5.6.2

107. Petalling (Missing petals), 50 5/ 1-2 6/ 3.4 4.5.6, 4.5.6.2

108. Petalling (Blown base) 50 5/ 0-1 3.4 4.5.6, 4.5.6.2"

Add Note 5:

"5/ Projectile fired in 135 to 200 feet and rapid fire tests shall be recovered and inspected for missing petals and blown bases."

Add Note 6:

"6/ One defect consists of one or more missing petals per projectile."

4.4.2.14, Major 106, delete "Rapid fire test, 150 to 656.2 feet (200 meters) 50 0-1 4/ 3.4 . . . 4.5.6.3"

Critical 6, Change from "244" to "194"

Critical 6, Delete "4.5.6.3"

Major 107, Change from "244" to "194"

Major 107, Delete "4.5.6.3"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

PAGE 24

* 4.4.2.14, Delete Note 3 in its entirety and substitute the following:

"3. Table I (with verification level (VL) II and Table IV (Continuous sampling plans) of MIL-STD-1916 are applicable."

4.4.2.14:

Note 2/ Delete "and rapid fire tests."

Add:

"202. Marking missing, improper or illegible .65 3.2 Visual"

4.4.2.14:

Add to Note 4: "For 1,000 meter test, sound and smoke or sound and flash are also acceptable."

In Note 5, delete: "and rapid fire test"

PAGE 31

4.4.3.2, Delete in its entirety.

PAGE 32

* 4.5.3, Delete ". . .Dwg. 9399395 . . ." and substitute ". . . 9399408. . ."

4.5.3, Delete: "Dwg 9399390" and substitute "Dwg. 9399395"

* 4.5.4, Delete "WARNING: This test is conducted on assemblies containing an explosive element. Test barricades (where used), procedures and equipment shall have prior approval."

4.5.6, Change from "Mk 19 MOD III Grenade Machine Gun" to "weapon"

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

4.5.6.1:

Delete “linked” from paragraph. (3 times)

Add to end of paragraph: “All tests performed shall be observed from the gun position.”

4.5.6.1:

Delete “linked” from paragraph.

Change from “Machine Gun” to “weapon”

PAGE 33

* 4.5.6.2, Delete “. . . ½ inch thick celotex target . . .” and substitute “. . . ½ inch cellulosic fiber insulating board per ASTM C208 or approved equal target material.”

4.5.6.2:

Delete “linked” from paragraph.

Change from “Machine Gun” to “weapon”

4.5.6.3:

Change from “Machine Gun” to “MK 19 MOD III Grenade Machine Gun”

Add to end of paragraph: This test shall be performed at an approved Government installation.”

* 4.5.8, Delete “MIL-P-116” and substitute “MIL-STD-2073”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisks or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractor are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-0601)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:36Z
Check the source to verify that this is the current version before use.