MILITARY SPECIFICATION

EXTRACTOR FOR 155MM GUIDED PROJECTILE, M712
AND TRAINING PROJECTILE M823

This amendment forms a part of Military Specification MIL-E-48622A (AR), dated 17 April 1980, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 12

4.4.2.7, add the following Minor defects:

"208 Paint Mark; AQL - .65%; Reg. Para. - 3.2; Insp. Method - Gage."

"209 Paint Mark Location; AQL - .65%; Para. - 3.2; Insp. Method - Gage."

PAGE 13

4.4.2.8, add the following Major defects:

"109 Diameter of Large Holes (3 locations); AQL - .40%; Reg. Para. - 3.2; Insp. Method - Gage."

"110 Location of Large Holes (3 locations); AQL - .40%; Reg. Para. - 3.2; Insp. Method - Gage."

Delete Minor defects 203 and 204 in their entirety.

PAGE 17

4.4.2.12, add the following Minor defects:

"206 Washer missing; AQL - 100%; Reg. Para. - 3.2; Insp. Method - Visual."

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.

4.5.1, delete the last two sentences entirely and substitute:

"The system shall be tested at each of its three extended lengths at two locations. Failure to meet the specified requirements shall be cause for rejection of the unit."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320 - A676)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:34Z
Check the source to verify that this is the current version before use.