MILITARY SPECIFICATION

INTEGRATED CIRCUIT, DIGITAL, CMOS CONTROL AND TIMING BASE, MONOLITHIC, SILICON

This Amendment forms a part of Military Specification MIL-I-48632 (AR), dated 31 July 1986, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1: Change: "M718E1/M741E1" to "M718A1/M741A1".

PAGE 3

3.2.2, Second line down: Delete "18 pin" and substitute "16 pin".

PAGE 4

3.4.1:

Delete "-55 to +125°C" under rating and substitute "-55 to +125°F".

Delete "-65 to +150°C" under rating and substitute "-65 to +150°F".

3.4.2: Delete "-32°C $\leq$ T_A $\leq$ +63°C V_B=7.5v" under conditions and substitute "-32°C $\leq$ T_A $\leq$ +63°C V_B=7.5v".

PAGE 5

3.4.2:

Under conditions: Delete "(Greater of LVD or 2.5 volts - V_B - 7.5 volts)" and substitute "(Greater of LVD or 2.5 volts $\leq$ T_A $\leq$ 7.5 volts)"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

Delete "$-32^{o} - T_A - +63^{o}C$" and substitute "$-32^{o} \leq T_A \leq +63^{o}C$".

Delete "$-32^{o}C - T_A - +63^{o}C$" and substitute "$-32^{o}C \leq T_A \leq +63^{o}C$".

PAGE 11

3.4.9.2:

First paragraph: Delete "Para. 3.3.9.3" and substitute "Para. 3.4.9.3".

Paragraph designated by *: Delete "3.3.9.4" and substitute "3.4.9.4" in 2 places.

PAGE 14

4.3.2: Delete "TABLE V" and substitute "TABLE III".

4.3.3: Delete in its entirety and substitute the following:

"4.3.3 Inspection conditions. Unless otherwise specified, all examinations and tests shall be made under the following conditions:

a.	Temperature	25 ± 5 Degrees C
b.	Humidity	10 to 75% RH
c.	Pressure	29 ± 3 inches of Hg
d.	Voltage an current measure	±2%"

4.4: Delete "TABLE VI" and substitute "TABLE IV".

PAGE 25

TABLE III, In-process screening: Delete "3.5.18" and substitute "3.5.17".

PAGE 27

TABLE III Qualification Test, under method paragraph:

Delete "4.5.4.2" and substitute "4.5.9" under "1" Output Voltage Terminal 11.

Delete "4.5.9" and substitute "4.5.10" under "0" Output Voltage Terminal 11.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

PAGE 28

TABLE III: Delete "4.5.9" and substitute "4.5.10" under "0" Voltage Terminal 11.

PAGE 29

TABLE IV, In-process screening: Delete "3.5.18" and substitute "3.5.17".

PAGE 44

4.6: Under Method for Past Burn-In: Delete "125°C" and substitute "25°C".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A386)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.