INCH-POUND

MIL-R-48595A(AR)
AMENDMENT 2
12 October 1993
SUPERSEDING
AMENDMENT 1
9 NOVEMBER 1987

MILITARY SPECIFICATION

RANGEFINDER, FIRE CONTROL, LASER: 11743101

This amendment forms a part of MIL-R-48595A(AR), dated 30 June 1981, and is approved for use by the U.S. Army Armament, Munitions, and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add the following paragraph:

"3.1.4 Interchangeability. The rangefinder shall meet all the requirements of this specification without the need for selective assembly of the units and cables. The units shall be interchangeable, such that replacement of any single unit or random combination of units of the rangefinder permits the system to operate and perform to the requirements of this specification.

NOTE: The PFN current adjustment may be reset after substitution of a different Electronic Unit or Receiver-Transmitter unit to meet the system performance requirements but shall not be further adjusted from the initial setting before, during, or after the environmental tests."

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

PAGE 11

* 3.4.1 Shock., delete and substitute the following:

"3.4.1 Shock. The Rangefinder shall be capable of operating as specified herein after exposure, under the conditions of 3.1.3, to three shock pulses, shown in Figure 1 and with intensity as shown below, applied in each direction along three mutually perpendicular axes placed upon the assembly as shown in Figure 2 (see 4.6.3.1).

Part Number	Nomenclature	Basic Design	High Intensity		
			x Axis	y Axis	z Axis
11743121	Receiver-Transmitter	20 ± 3 g 18 ± 3 ms	40 ± 4 g* 9 ± 1 ms	40 ± 4 g* 9 ± 1 ms	40 ± 4 g* 9 ± 1 ms
11743131	Electronic Unit	40 ± 4 g 18 ± 3 ms	120 ± 12 g 1.7 ± 0.2 ms	120 ± 12 g 1.7 ± 0.2 ms	120 ± 12 g 1.7 ± 0.2 ms

* Note indicates saw tooth shock pulse, all others 1/2 sine wave shock pulses. Tolerances shall be in accordance with MIL-STD-810, Method 516.2, Figure 516.2-1 except the limit of + 0.2/-0.3 on post pulse oscillation peak amplitude shall not apply."

PAGE 18

TABLE IX, Test Equipment, Item 5, Delete "23-inch minimum diameter circle, " and substitute "23-inch minimum diameter circle or 23 inch minimum square,".

PAGE 19

* TABLE IX, Test equipment. Delete part number and nomenclature of items 6,7,8,and 9 and substitute:

Item	Part Number	Nomenclature
6	Target 3	4 ft² minimum, 15 % minimum diffuse reflectivity. 1/
7	Target 4	4 ft² minimum, 80 % minimum diffuse reflectivity. 1/

1/ The exact location of the target from the window of the Receiver-Transmitter shall be known within ± 1 meter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.

PAGE 20

* 4.6.3.1.1 Basic design (shock), delete and substitute the following:

"4.6.3.1.1 Basic design. Use item 2 of Table IX and subject the rangefinder to the shock test specified in MIL-STD-810, Method 516.2, Procedure I, Figure 516.2-1. At the conclusion of the test, subject the rangefinder to the performance tests of Table VI."

PAGE 21

* 4.6.3.1.2 High intensity (shock), delete and substitute the following:

"4.6.3.1.2 High intensity. Use item 2 of Table IX and subject the rangefinder to the shock test specified in MIL-STD-810, Method 516.2, Procedure IV, Figure 516.2-2. At the conclusion of this test, subject the rangefinder to the performance tests of Table VI."

PAGE 22

Add the following paragraph:

"4.6.5 Interchangeability. The interchangeability requirements specified in 3.1.4 shall be satisfied when the rangefinder is selected as specified in 4.4.1 for First Article samples and the environmental samples."

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1240-A968)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:33Z
Check the source to verify that this is the current version before use.