
MILITARY SPECIFICATION SHEET


TRANSFORMER, POWER, STEP-DOWN, TF4S03AJ

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for procuring the transformer described herein shall consist of this document and the latest issue of Specification MIL-T-27.



INCHES	MM
016	41
.063	1 60
125	3 18
138	3 51
156	3 96
250	6 35
312	7 92
375	9 52
1 188	30 18
1 625	41 28
2 375	60 32



PRI (2-4) 115 V → NOM OUTPUT
(1-4) 115 V → -6% NOM OUTPUT
(1-3) 115 V → +6% NOM OUTPUT
(2-3) 115 V → +12% NOM OUTPUT
WORKING VOLTAGE (PEAK) = 535 V Ⓐ

CIRCUIT DIAGRAM AND MARKING

NOTES
1 Dimensions are in inches
2 Metric equivalents are given for general information only and are based upon 1 00 inch = 25 4 mm
3 Tolerance on terminal position dimensions is ± 016 inch
4 Unless otherwise specified, tolerance on overall case dimensions is + 000, - 063 inch
5 Marking shall be on the side of the case

U S GOVERNMENT PRINTING OFFICE 19H 011 158 4

FIGURE 1 Dimensions and configuration

Ⓐ denotes changes

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i e , (1-2) are used, they indicate the winding and the extreme terminals of the winding)

Electrical ratings

TABLE I. Electrical ratings

Dash no.	Primary voltage		Secondary voltage (5-6)	Secondary voltage (6-7)	Secondary voltage (8-9)	Secondary voltage (9-10)
01	(2-4)	115 V, 50/60 Hz	8 25 V	12.0 V	12 0 V	8.25 V
	(1-4)	115 V, 50/60 Hz	7.76 V	11.28 V	11 28 V	7 76 V
	(1-3)	115 V, 50/60 Hz	8 74 V	12 72 V	12 72 V	8 74 V
	(2-3)	115 V, 50/60 Hz	9 24 V	13 44 V	13 44 V	9.24 V

Ⓐ Primary current 120 mArms maximum
Ⓐ Secondary current 105 mArms maximum (5-7), (8-10)
Ⓐ VA 4 8
Working voltage (peak) 535 volts

Design and construction
Dimensions and configuration See figure 1
Duty cycle Continuous
Case Metal encased
Terminals Solder terminal, NC-2 or equivalent
Terminal height 0.312 inch ±0 016
Ⓐ Weight 397 grams, maximum
Altitude 10,000 feet maximum
Operating temperature range -55°C to +130°C

Terminal strength MIL-STD-202, method 211, test condition A, 5 0 pounds and test condition E, 8 0 ounce-inches

Vibration (high frequency) MIL-STD-202, method 204

Dielectric withstanding voltage
At sea level 1,500 Vrms

Electrical characteristics
No load With 115 volts, 60 Hz across (2-4), current in (2-4) shall not exceed 120 mA and the power in (2-4) shall not exceed 1 2 watts
Ⓐ Voltage across
(5-7) 24 86 volts ±5 percent
(8-10) 24 86 volts ±5 percent
Ⓐ Rated load With 115 volts, 60 Hz across (2-4), the voltage across (5-7) and (8-10) shall be 20 25 volts ±5 percent @ 105 mArms
DC resistance
(1-4) 200 ohms, maximum
(8-10) 27 ohms, maximum
(5-7) 24 ohms, maximum
Polarity Additive, with 1 and 5, and 7 and 8 connected

Ⓐ Temperature rise 40°C with 115 volts rms, 60 Hz across (2-4) at an ambient temperature of 90°C

Marking location See figure 1

Part number M27/156-01

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI, SC
Navy - SH, OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR, ME
Navy - MC, AS
Air Force - 19

Preparing activity
Army - ER

Agent
DLA - ES

(Project 5950-0581-12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Cdr, US Army ERADCOM
ATTN: DELET-R-S
Fort Monmouth NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-T-27/156A TRANSFORMERS, POWER, STEP-DOWN TF4S03AJ

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.