INCH POUND

MIL-T-27/158C
12 July 2013
SUPERSEDING
MIL-T-27/158B
8 June 2012

MILITARY SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS (AUDIO, POWER, AND HIGH-POWER PULSE) TRANSFORMER, POWER, STEP-DOWN

This document is inactive for new design

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the product described herein shall consist of this document and the latest issue of specification MIL-PRF-27.




FIGURE 1. Dimensions and configurations.

AMSC N/A

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.



WORKING VOLTAGE (PEAK):

(1 - 3) = 535 V
(4 - 6) = 1070 V

CIRCUIT DIAGRAM AND MARKING

Inches	mm
.005	0.13
.030	0.76
.125	3.18
.157	3.99
.186	4.72
.375	9.52
.653	16.59
.850	21.59
1.406	35.71
1.690	42.93
1.781	45.24
2.125	53.98
2.187	55.55
2.312	58.72

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance on case dimensions is ±.016 inch (.41 mm).
4. Marking shall be on the side of the case.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the windings.)

Electrical ratings:

Primary voltage (1-2-3): 105/115 volts, 380 Hz to 1,000 Hz.

Primary current (1-3): 0.6 ampere rms, maximum.

Voltamperes: 63.

Secondary voltage (4-6): 6.3 volts ct.

Secondary current (4-6): 10 amperes rms, maximum.

Working voltage (peak):

(1-3): 535 volts.
(4-6): 1,070 volts.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Encapsulated.

Material: Epoxy.

Terminals: Solder terminal, Zierick #70 or equivalent for terminals 1, 2, and 3. Zierick #105 or equivalent for terminals 4, 5, and 6.

Terminal height: .312 Max.

Weight: 454 grams, maximum.

Operating temperature range: -55°C to +130°C.

Terminal strength: MIL-STD-202, method 211, test condition A, 5 pounds and test condition D, 40 ounce-inches.

Dielectric withstanding voltage (at sea level):

(1-3): 1,500 volts rms.
(4-6): 2,500 volts rms.

Electrical characteristics:

No load: With 115 volts, 400 Hz across (1-3), current in (1-3) shall not exceed 300 mA and the power in (1-3) shall not exceed 6 watts. Voltage across (4-6): 6.51 volts ct, ±3 percent.

Rated load: With 115 volts, 400 Hz across (1-3), the voltage across (4-6) shall be 6.3 volts ct, ±3 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.

DC resistance:

(1-3): 3.0 ohms, maximum.
(4-6): 0.085 ohm, maximum.

Polarity: Additive, with terminals 3 and 6 connected.

Temperature rise: 55°C with 115 volts rms, 400 Hz across (1-3) at an ambient temperature of 75°C.

VERIFICATION:

Qualification inspection: Not applicable for this specification sheet.

Quality conformance inspection: Groups A and B tests of MIL-PRF-27 shall be applicable.

Marking location: See figure 1.

Part or Identifying Number (PIN): M27/158-01.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA – CC

Review activities:
Army – CR4, MI
Navy – AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5950-2013-027)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at https://assist.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:40Z
Check the source to verify that this is the current version before use.