FED. SUP CLASS
6640



PART NUMBER	MALE JOINT SIZE	FEMALE JOINT SIZE
MS36254-1	10/30	24/40
MS36254-2	19/38	24/40
MS36254-3	24/40	29/42

MATERIAL: Adapter shall be made of borosilicate glass, in accordance with ASTM E 438, Type I, Class A.

DESIGN: Adapter shall be reducing, bushing type, and shall have standard taper joints. Adapter shall have an overall length of 55 mm nominal.

TOLERANCE: Female joint tolerance shall be -0.15 mm, and male joint tolerance shall be +0.15 mm at gaging point.

NOTES:

1. Items which vary in design but otherwise conform to size requirements shall be considered as one interchangeable Military Standard item.
2. In the event of a conflict between the text of this standard and the references cited herein, the text of this standard shall take precedence.
3. Referenced Government documents of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this standard to the extent specified herein.
4. FSCMs: 07736, 14674 and 18575, and 22527.

Ⓐ ENTIRE STANDARD REVISED

APPROVED 15 DEC 1961 REVISED Ⓐ 10 APR 1987

USER ACTIVITIES:

REVIEWER ACTIVITIES:

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P. A. EA Other Cust MS, ME 99	INTERNATIONAL INTEREST	TITLE ADAPTER, LABORATORY GLASSWARE bushing type	MILITARY STANDARD MS36254
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. PROJECT NUMBER 6640-1417-1

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:37Z
Check the source to verify that this is the current version before use.