FED. SUP CLASS
6640



PART NUMBER	DIAMETER OF CYLINDERS ACCOMMODATED CM	SUPPORT SURFACE THICKNESS ACCOMMODATED CM
MS36560	10 to 35	2.5 to 6.25

MATERIAL: Clamp shall be malleable or cast iron or cast aluminum with a corrosion-resisting finish.

Buckle shall be nickel-plated steel. Web strap shall be either nylon or cotton tape and shall be fire resistant. Thumbscrew shall be corrosion-resisting steel.

DESIGN: Clamp shall be capable of being firmly attached to a bench top or other surface with a minimum of 2.5 cm overhang.

Adjustable strap and buckle shall hold cylinder of compressed gases in an upright position.

NOTES:
1. Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements specified herein.
2. FSCM: 22527 and 59728.

(A) ENTIRE STANDARD REVISED

USER ACTIVITIES: ARMY - MD, DM, MI
NAVY - MS

REVIEWER ACTIVITIES: ARMY - ME
AIR FORCE - 82

APPROVED 15 Dec 1967 REVISED (A) 12 OCT 1983

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. EA	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust MS 99		CLAMP, CYLINDER SUPPORT	MS36560
Procurement Specifications NONE	SUPERSEDES:		SHEET 1 OF 1

DD FORM 1 MAY 73 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NUMBER 6640-1212

U.S. GOVERNMENT PRINTING OFFICE: 1983 — 705-040/5604

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:43Z
Check the source to verify that this is the current version before use.