FED SUP CLASS
6630

USER ACTIVITIES ARMY - CE
NAVY - YD

REVIEWER ACTIVITIES ARMY - MD

PART NUMBER	DESCRIPTION	ELECTRODE LENGTH (CM)	TEMP RANGE °C	pH RANGE
MS36586-1	Calomez Internal With Quartz Junction	12 7	-5 to 100	0 - 14
MS36586-2	Calomez Internal With Ceramic Junction	12.7	-5 to 100	0 - 14
MS36586-3	Silver-Silver Chloride Internal With Ceramic Junction	12 7	-5 to 110	0 - 14
MS36586-4	Silver-Silver Chloride Internal With Quartz Junction	12 7	-5 to 110	0 - 14

MATERIAL Electrodes shall be made with internal elements as specified and of the specific type of glass necessary to meet the requirements for temperature, pH range and resistance to chemical attack

DESIGN Electrodes shall be glass with either a side arm or side filling hole They may also have a sleeve junction or reverse-sleeve The lead may be detachable or permanently attached and shall be a minimum of 76 cm in length The electrode plugs shall be designed so that they are readily adaptable for use with most pH meters

PURPOSE For use in conjunction with an indicator elector to determine hydrogen ion or other ion concentration or oxidation reduction potential measurement of a sample solution

NOTE Items differing from this Military Standard by minor variations in design or dimensions are considered standard under this document, provided such variations do not affect performance and are not in conflict with the material requirements as specified herein

APPROVED 28 JAN 1982 REVISED

This military standard is approved for use by all Departments and Agencies of the Department of Defense Selection for all new engineering and design applications and for repetitive use shall be made from this document

P A	EA	INTERNATIONAL INTEREST	TITLE ELECTRODE, HYDROGEN ION (REFERENCE TYPE)	MILITARY STANDARD
Other Cust	MS 99			MS 36586
Procurement Specifications		SUPERSEDES: MS36465		SHEET OF

DD FORM 672 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE PROJECT NUMBER 6630-0 DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:44Z
Check the source to verify that this is the current version before use.