MIL-D-23224A(OS)
9 July 1982
Superseding
MIL-D-23224(SHIPS)
5 April 1962 and
WS 19308
29 September 1977

MILITARY SPECIFICATION

DOLLY, HANDLING, MK 24 MOD 1

This specification is approved for use by Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the Dolly, Handling, MK 24 MOD 1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-104	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116	Preservation, Methods of
MIL-P-15024/10	Nameplates, ORDALT Plates and Information Plates

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization/Documentation Division (524), Indian Head, MD 20640 using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1398

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

NAVAL SEA SYSTEMS COMMAND (Code Ident 53711)

DL 5166020	Dolly, Handling, MK 24 MOD 1

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between this specification and the references cited herein, this specification shall take precedence.

3. REQUIREMENTS

3.1 Item definition. The manually propelled handling dolly will be used to transport uncovered torpedoes weighing up to 1000 pounds total weight aboard ships or at shore stations. The Dolly, Handling, MK 24 MOD 1 shall be referred to in this specification as "dolly".

3.2 Materials. Unless otherwise specified in the contract, all materials, purchased parts and processes thereto entering into the final assembly of the dolly shall conform to the detailed requirements indicated on the drawings and specifications listed in DL 5166020.

3.2.1 Interchangeability. All parts having the same part number shall be directly and completely interchangeable with respect to installation and performance.

3.3 Performance requirements.

3.3.1 General. The purpose of these performance requirements is to provide assurance that MK 24 MOD 1 dollies are manufactured in accordance with DL 5166020 and the drawings and specifications listed thereon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

3.3.2 Brake operation. The brake system is a normally locked (dead man) mechanical system which operates through hand grip levers on the dolly handles. The brakes are activated from either end of the dolly dependent upon handle installation.

3.3.3 Braking response. When loaded with 1000 pounds as specified in 4.3 and tested in accordance with 4.6.2 and moving at a speed of four feet per second between two parallel lines 32 inches apart, on a dry, smooth level concrete surface or a surface upon which the dolly wheel treads will have a coefficient of sliding friction of 0.6, the dolly shall stop not more than 18 inches from the point on the surface where the brakes were applied. The wheels must remain within the parallel lines.

3.4 Marking. Markings on the dolly shall include a nameplate identifying the dolly in accordance with MIL-P-15024/10. The capacity will be stencilled, in 1" characters, in accordance with Drawing 5166020.

3.5 Workmanship. The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance will all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of marking of parts and assemblies, surface treatment, and freedom from burrs and sharp edges. The standards of workmanship exhibited in any approved sample, subject to any qualifications stated in the Government's notice of approval, shall establish the requirements of workmanship insofar as not specifically covered by the applicable specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as:

a. Quality conformance inspection (see 4.4).

4.3 Dummy load. A dummy load of 1000 pounds + 50 pounds, cylindrical in shape having a diameter of 12.75" to 21" shall be rested on the two aft dolly roller supports and the two forward roller supports such that the dummy load center of gravity (CG) falls between the forward and aft sets of roller supports.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Each dolly shall be inspected for compliance with 4.5 and tested in accordance with 4.6.1 and 4.6.2.

4.5 Examinations. Each dolly shall be examined for compliance with material and dimensional requirements of DL 5166020 and the workmanship of 3.5. Major characteristics shall be sampled in accordance with Level II plans of MIL-STD-105 at an AQL of 1%. Minor characteristics shall be examined at an AQL of 4%.

4.6 Test mehtods.

4.6.1 Test conditions. Unless otherwise specified, the following tests shall be performed in an area having a dry, uncoated brush finish, level concrete surface or a surface condition on which the dolly wheel treads will have a coefficient of sliding friction of 0.6. For the purposes of this specification, the loaded condition is defined in 4.3.

4.6.2 Braking response. The dolly shall be laoded as described in 4.3 and propelled manually at a speed of 4 feet per second between two parallel lines 32 inches apart. The dolly brakes shall be applied once with the handles installed in each end of the dolly. The final stopping position of the dolly shall meet the requirements of 3.3.3.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 The dolly shall be packed in accordance with Method III of MIL-P-116.

5.1.2 Level B. Not applicable.

5.1.3 Level C. Not applicable.

5.2 Packaging.

5.2.1 Level A.

5.2.1.1 Exterior container. The dolly shall be packaged in a wooden crate designed to accomodate the dolly with handles removed and stowed within the crate conforming to MIL-C-104.

5.3 Marking.

5.3.1 Special markings. None, unless other specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

5.3.2 Normal markings. In addition to the markings required by the contract or purchase order, shipping containers shall be marked in accordance with the requirements of MIL-STD-129 including serial numbers.

6. NOTES

6.1 Intended use of dolly. The manually propelled dolly is for use aboard ship or at shore stations to transport uncovered torpedoes weighint a maximum of 1000 pounds in confined areas which preclude the use of mechanized transporters.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Number of dollies to be furnished.

c. Applicable detailed drawings.

d. Quality assurance procedures to be followed.

e. Date for delivery.

6.3 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing Activity:
Navy - OS

Project No. 1398-N111

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-D-23224A(OS) DOLLY, Handling, MK 24 MOD 1

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-LF-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.