MIL-L-23225C
22 April 1985
SUPERSEDING
MIL-L-23225B
23 June 1977

MILITARY SPECIFICATION

LATHE, PRECISION, INSTRUMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE .

1.1 Scope. This specification covers small precision instrument lathes for use in the repair and manufacture of small parts to precise tolerances with equipment and accessories specified herein.

1.2 Classification. This specification covers lathes of the following types. The type furnished shall be as specified (see 6.2.1).

Type I - Instrument lathe, single pedestal bed (see 3.4.1).
Type II - Instrument lathe (see 3.4.2).

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2,1,1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5297, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3416

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910)

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/NEMA MG 1 - Motors and Generators.
ANSI/NEMA ICS 1 - Industrial Control and Systems.

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th St., New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIAL

ASTM-D-3951 - Commercial Packaging, Standard Practice for.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:57Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence, In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), a sample shall be subjected to first article inspection (see 4.2 and 6.3).

3.2 Design. The lathe shall be one of the manufacturer's current models capable of conforming to the accuracy requirements for instrument lathe, in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and Indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the machine shall be graduated in the same system.

3.2.1.2 Dual calibrations. When specified (see 6.2.1), measuring and indicating devices shall be graduated in both the US and the SI system of measurements. When a dual US and SI system is furnished, both feed dials shall have independent zero adjustments and both dials shall be calibrated In such a manner that the last dial graduation progresses into and is continuous with the first dial graduation as the dial is rotated through the zero position.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials provided such materials will not jeopardize the machine's intended use and performance. the reclaimed materials shall have been reprocessed, remanufactured or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the machine.

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:57Z
Check the source to verify that this is the current version before use.

3.2.3 Energy efficiency. The lathe and all its applicable components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

3.2.4 Controls. All operating controls shall be located convenient to the operator at his normal work station.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the lathe that present safety hazards. The safety devices shall not interfere with the operation of the machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance and repair of the parts. All machine parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA 2206 that are applicable to the machine itself. Additional safety and health requirements shall be as specified (see 6.2.1 and 6.4).

3.2.6 Mercury restriction. The machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the machine.

3.2.8 Environmental protection. The machine shall be designed and constructed such that, under the operating, service, transportation and storage conditions described herein, the machine shall not emit materials hazardous to the ecological system as prescribed by Federal, state or local statutes in effect at the point of the installation.

3.2.9 Lubrication. Means shall be provided to insure adequate lubrication for all moving parts. All oil holes, grease fittings and filler caps shall be accessible.

3.3 Construction. The lathe shall be constructed of parts which are without defects and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects such as scale and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. fastening devices subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. All surfaces to be painted shall be cleaned of all foreign matter. Unless otherwise specified (see 6.2,1), the machine shall be finished in accordance with manufacturer's standard commercial practice which shall include cleaning, priming and painting.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Dials. All dials that indicate stock removal or tool movement shall be graduated in increments not larger than .001 inch. Dial diameters shall be such that graduations may be read from the normal operating position. Dials shall be permanently and legibly engraved or etched on a non-glare background.

3.3.8 Gears. All gears shall be constructed from a material suitable for the intended purpose. All metal gears shall be machined and heat treated by a process that will impart the hardness, surface finish and toughness that will enable the gear train to transmit full rated torque of the drive motor without gear damage, failure or premature deterioration and wear.

3.3.9 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-STD-461.

3.4 Components. The lathe shall conform to the following requirements for the type required under 1.2.

3.4.1 Type I, instrument lathe, single pedestal bed. Unless otherwise specified (see 6.2.1), the instrument lathe shall consist of a bed supported on a single pedestal with an open or an enclosed type headstock and a tailstock and the following features. The bed shall have precision finished ways running its full length to permit positioning the components mounted thereon and to facilitate changing accessory equipment. The single pedestal shall have means for attaching the lathe to a bench or cabinet top. The headstock shall consist essentially of the spindle, spindle support and spindle drive pulley. The spindle drive shall consist of a drive motor and controls, belting, and means for selecting or varying spindle speeds. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

spindle shall be mounted in sealed and lubricated-for-life type precision bearings or precision cone type bearings with means for lubrication. The spindle shall accept draw-in collets, chucks and centers as specified. The tailstock shall be the plain or lever actuated push type and shall be suitable for centering and drilling to precision tolerances.

3.4.2 Type II, instrument lathe. Unless otherwise specified (see 6.2.1), the instrument lathe shall consist essentially of a bed supported at each end, an open or an enclosed type headstock, or the type specified, and tailstock and the following features. The bed shall have precision finished ways extending from the headstock through the tailstock end designed to facilitate changing accessory equipment. The bed supports shall have means for attaching the lathe to a bench or cabinet top. The headstock shall consist of the spindle, spindle supports and spindle drive pulley. The spindle shall accept the draw-in collets, chucks and centers specified in 3.8 and 3.9. The spindle drive shall consist of a drive motor and controls, belting, and means for selecting or varying spindle speeds. The spindle shall be mounted in sealed and lubricated-for-life type precision bearings or precision cone type bearings with means for lubricating. The tailstock shall be the plain or lever actuated push type suitable for centering and drilling to precise tolerances.

3.5 Type and capacities. Unless otherwise specified (see 6.2.1), the size and characteristics of the machine shall be not less than those specified in table I for the machine size specified.

TABLE I. Types and capacities.

REQUIREMENTS	instrument	
	Type I	Type II
Swing over bed	3.94 inch	3.94 inch
Optional swing over bed	4.72 inch	4.72 or 5.90 inch
Bed length	12 inch	15 inch
Optional bed length	15 inch	18 inch
Distance between centers	3-1/4 inch	5-1/2 inch
Distance between centers with optional bed lengths	5-1/4 inch	8-1/2 or 9-1/2 inch
Maximum collet capacity	3/16-WW	3/16-WW
Optional collet capacity	5/16-D	5/16-D
Optional, metric size	5MM or 8MM	5MM or 8MM

NOTE : The machine size and capacity shall not be less than the stated requirements of the size ordered nor greater than the requirement to the next larger size shown in the above table. The largest size and capacity offered shall not exceed the stated requirement more than 10 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

3.6 Alignment tolerances. Each lathe shall meet the alignment accuracies of table II.

TABLE II. Alignment accuracies.

REQUIREMENTS	INCHES
Bed ways parallel	0.0003 per foot
Spindle collet seat runout	0.0005 TIR
Optional spindle accuracy	0.0001 TIR or 0.000025
Spindle parallel with bed ways, vertically and horizontally	0.0005 overall
Center alignment, test bar between centers, vertically and horizontally	0.0002 in 4“

3.7 Performance. The lathe and components, operator’s controls and safety devices shall function properly when tested in accordance with 4.6.1 and 4.6.2.

3.8 Optional equipment. When specified (see 6.2.1), the following attachments and accessories shall be supplied for the type lathe required.

3.8.1 Centers, two, headstock and tailstock, male, taper, with holding collet.

3.8.2 Handrest, tip-over with clamping device.

3.8.3 Tailstock, combination, collet holding, rack and pinion feed lever.

3.8.4 Collet closer, lever type, for the style collets required.

3.8.5 Chuck, bezel for external and internal holding, scroll operated, at least 2“ capacity.

3.8.6 Chuck, 3-jaw, reversible jaws, scroll operated, at least 2“ maximum capacity.

3.8.7 Chuck, 4-jaw, reversible jaws, Independent, at least 2“ maximum capacity。

3.8.8 Chuck, drill, mounted for use in headstock or tailstock.

3.8.9 Collets, inch sizes or metric sizes, Type 3C, Type D, or Type WW, as specified.

3.8.9.1 Spindle adapter, for use with the collet types and styles specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

3.8.10 Cross slide, double tool, lever action with tool posts for 3/16″ square tool bit.

3.8.11 Slide rest, two slide, screw feed in inch or metric graduations as specified, one tool post for 3/16″ square tool bit.

3.8.12 Slide rest, two slide, screw feed in inch or metric graduations as specified, one tool post for 3/16″ square tool bit.

3.8.13 Slide rest, compound, three slides, screw feed and compound settings graduated in inch or metric settings as specified, 3/16″ tool post.

3.8.14 Screw cutting attachment, with change gears for cutting right hand and left hand threads in the inch or metric system as specified.

3.8.15 Pivot polisher, swivel head graduated in degrees, on slide with cross feed screw, graduations in inch or metric units as specified.

3.8.16 Face plate, for clamping and supporting parts to be machined.

3.8.17 Drive plate and adjustable drive dog for between center work.

3.8.18 Turret , six position, indexing, hand lever operated with adjustable stop screw for each tool position (for lathe bed 18″ or longer).

3.8.19 Chip and coolant tray, for use with a coolant system, either separate, or as part of cabinet top when the lathe is cabinet mounted.

3.8.20 Coolant system, consisting of a pump, coolant tank and necessary tubing to direct the coolant to the cut.

3.8.21 Bench , plain top, plain top with drawers, or top cut out for mounting motor under bench, as specified.

3.8.22 Cabinet, steel, space for enclosing a coolant system, drive motor and motor controls and accessory items, with chip tray top.

3.8.23 Drive motor, supplier’s standard for open headstock or enclosed headstock lathe, complete with necessary mounting equipment, wiring, controls, foot switch, counter shaft, pulleys for four or eight speeds, and drive belts, ready for use when connected to a power supply. The motor shall be suitable for maximum spindle speeds to 2500 RPM, 3000 RPM, or 4000 RPM, as specified. It shall be for under bench or bench top mounting as specified (see 6.2.1).

3.8.24 Drive motor, variable speed, for a cabinet mounted or bench mounted lathe, complete with variable speed selector controls, necessary mounting equipment, wiring and drive belts, ready for use when connected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

a power supply. The motor shall be suitable for maximum spindle speeds of zero to 4000 RPM, reversible with dynamic braking. When the lathe is for cabinet mounting, the motor shall be for mounting within and shall have cabinet mounted motor controls. When for bench mounting, the motor shall be for under or bench top mounting with foot switch or bench top control as specified (see 6.2.1).

3.9 Additional requirements. Lathe features or tooling required in addition to, or in lieu of equipment specified herein, shall be supplied as required (see 6.2.1).

3.10 Electrical equipment. Unless otherwise specified (see 6.2.1), the electrical controls and drive motor shall conform to the applicable requirements of NEMA Standards ICS1 and MG1. The motor and electrical shall be for operation on 110 or 115 volts, single phase, 60 Hz power supply.

3.11 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-STD-461.

3.12 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate shall be securely attached to each machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each such caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Type Size Horsepower
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.13 Technical data. When technical data is required it shall be furnished in accordance with the requirements of the contract.

3,14 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure of the item to pass the first article tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract , Unless otherwise specified (see 6.2.1) quality conformance inspection shall consist of at least the examination in 4.5 and the tests in 4.6. Failure of the item to pass the examination or tests shall be cause for rejection.

4.5 Examination. The machine and equipment shall be examined to determine compliance with the requirements in 3.2 through 3.14.

4.6 Tests.

4.6.1 Operational and accuracy tests. The lathe shall be checked in accordance with the supplier's standard test procedures to determine proper operation of electrically and mechanically operated equipment. The lathe shall be checked to determine that its accuracies are within the tolerances of table II, using instruments of the supplier's choice.

4.6.2 Electromagnetic interference control tests. When required, (see 6.2.1), equipment requiring electromagnetic interference control testing shall be tested for compliance with 3.11.

4.7 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Packaging, packing and marking. Unless otherwise specified, packaging, packing, and marking shall be in accordance with ASTM-D-3951 l When

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T15:57Z
Check the source to verify that this is the current version before use.

specified (see 6.2.1), level A packaging, level A or level B packing and special marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. The lathes covered by this specification are intended for use in any shop, toolroom or laboratory where precision tolerances are required in the repair or manufacture of small parts. The instrument lathe is intended for use in manufacturing operations or second operation use, when equipped with accessory items, to produce small parts to precise tolerances in maintenance or production operations.

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Type lathe required (see 1.2).
c. First article approval, if required (see 3.1).
d. If machine is required to be configured in a specific measurement system (US or SI), state required system (see 3.2.1).
e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).
f. Dual calibrations (US and SI), if required (see 3.2.1.2).
g. Additional safety and health requirements, if required (see 3.2.5).
h. Painting, if different (see 3.3.5).
i. Requirements for the type I lathe, if different (see 3.4.1).
j. Requirements for the type II lathe, if different (see 3.4.2).
k. Optional lathe capacities as required (see table I).
l. Accuracy tolerances requirements, if different (see table II).
m. Optional equipment, underneath or bench top motor drive and control as required (see 3.8).
n. Requirements or accessories, if different (see 3.9).
o. Electrical equipment, if different (see 3.10).
p. Electromagnetic interference control requirements, if different (see 3.11).
q. Nameplate, if different (see 3.12).
r. First article inspection, if different (see 4.3).
s. Quality conformance inspection, if different (see 4.4).
t. Electromagnetic interference control, test requirements if different (see 4.6.2).
u. Level of preservation, packing and marking requirements (see 5.1).
v. Drive motor, if different (see 3.8.23).
w. Drive motor, variable speed, If different (see 3.8.24).

6.2.2 Contract data requirements. All data requirements such as parts lists, wiring diagrams, operating manuals, maintenance manuals, alignment

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:57Z
Check the source to verify that this is the current version before use.

and test results shall be required on a DD Form 1423, Contract Data Requirements List and shall be furnished in accordance with each specified DD Form 1664, Data Item Description as shown on the DD Form 1423.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test and approval of the first article.

6.4 Safety and health requirements. Paragraph 3.2.5 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, heat, etc. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring activity is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional machine requirements that will integrate the new machine into its future operating environment. The machine shall be equipped with all points-of-operation guarding normally furnished as standard on the manufacturer's commercial machines supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity should specify the exact configuration of the guard required, as in most cases, the guard configuration is dependent on the size and configuration of the workplaces. The above, and any other additional safety and health requirements should be specified in detail under 6.2.1.

6.5 Supersession data. This specification includes the requirements of precision instrument lathe, type I and type II, which were formerly included under type I - jewelers lathe, single pedestal bed and type 11 - instrument lathe of MIL-L-23225B dated 23 June 1977.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review Activities:
Navy - SH
DLA - GS
Air Force - 84

Preparing Activity:
DLA - IP

Project Number:
3416-0182

Source: https://assist.dla.mil -- Downloaded: 202640-19T15:57Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY
Headquarters
Defense Industrial Plant Equipment Center
Memphis, Tennessee 38114-5297

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSM
Memphis, Tennessee 38114-5297

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-L-23225C	Lathe, Precision, Instrument

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-19T15:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:57Z
Check the source to verify that this is the current version before use.