MIL-E-1/432B
26 September 1968
SUPERSEDING
MIL-E-1/432A
18 June 1957

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6Y6GT 1/

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Pentode, beam power amplifier

Outline --- 9-11 (EIA) Ⓑ

Base --- B7-7 or B6-81

Envelope --- T9

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	7	8
Element	---	nc	h	p	g2	g1	h	k, g3

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ik	Pp	Pg2	Ⓑ Ehk	Alt
Unit:	V	Vdc	Vdc	Vdc	mAdc	W	W	v	ft
Maximum:	6.9	220	---	150	125	14	2.0	200	10,000
Minimum:	5.7	---	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	200	-14	135	---	---	---	---	---

GENERAL:

Qualification - Required

1/ Formerly JAN-6Y6G, 6Y6GT
(See note 2)

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:20Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						MIN	MAX	
	Quality conformance inspection, part 1							
1266	Total grid current		0.65	II	Ic1	0	-3.0	µAdc
(B) 1246	Audio frequency noise	Esig = 600 mVac; Rp = 2,000 ohms (see note 1)	0.65	II	---	---	---	---
1231	Emission	Eb = Ec1 = Ec2 = 30 Vdc	0.65	II	Is	180	---	mAdc
1256	Electrode current (anode)		0.65	II	Ib	43	79	mAdc
1256	Electrode current (screen)		0.65	II	Ic2	0	4.4	mAdc
1341	Power output	Esig = 9.9 Vac; Rp = 2,600 ohms	0.65	II	Po	4.8	---	W
(B) 1201	Short and discontinuity detection		0.4	II	---	---	---	---
(B) ---	Visual and mechanical inspection criteria		---	---	---	---	---	---
(B) ---	Dimensions	Outline 9-11; dimensions A thru D	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
(B) 1031	Low-frequency vibration	Ec1 = -22 Vdc; Rp = 2,000 ohms	6.5	S3	Ep	---	1,000	mVac
1301	Heater current		6.5	S3	If	1.13	1.37	A
(B) 1336	Heater-cathode leakage		6.5	S3	Ihk	---	75	µAdc
1306	Transconductance		6.5	S3	Sm	5,800	8,400	µmhos
(B) 1101	Secureness of base, cap, or insert		6.5	S3	---	---	---	---
(B) 1111	Base pin solder depth	See note 3	6.5	S3	---	---	---	---
(B) 1211	Insulation of electrodes		4.0	S3	R	10	---	Meg
(B) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Life-test provisions (intermittent) (500 hours)	Group A: Ehk = 300 V	---	---	---	---	---	---
---	Life-test end point (intermittent) (500 hours)	Power output	---	---	Po	3.0	---	W

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:20Z
Check the source to verify that this is the current version before use.

NOTES:

1. The rejection level shall be set at the VU meter reading obtained during calibration.
2. Tube type 6Y6G has been deleted from this tube specification sheet. Tubes for replacement purposes shall be procured to this specification sheet.
3. This test applies for flexible leads as well as for rigid leads.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - ME, AV
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2289-81)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:20Z
Check the source to verify that this is the current version before use.