MIL-E-1/439B
18 April 1968
SUPERSEDING
MIL-E-1/439A
21 January 1959

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 26A6

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Pentode, miniature, RF remote cutoff

Outline --- 5-2(EIA) (B)

Base --- E7-1

Envelope --- T5-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7
Element	---	g1	g3 (int sd)	h	h	p	g2	k

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ec3	Ik	Pp	Pg2	Rg1	Ehk	Alt
Unit:	Vdc	Vdc	Vdc	Vdc	Vdc	mAdc	W	W	Meg	v	ft
Maximum:	29.1	55	---	55	0	45	0.3	0.15	---	100	(see note 1) (B)
Minimum:	23.8	---	---	---	---	---	---	---	---	---	
TEST CONDITIONS:	26.5	26.5	0	26.5	0	---	---	---	2	---	---

REQUIREMENT OR TEST:

GENERAL

3.2 Qualification - Required

E-50.2 Holding period

E-50.3 Preheating

5. Preparation for delivery

(B) denotes [illegible]

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:20Z
Check the source to verify that this is the currentversion before use.

METHOD OR PARAGRAPH	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1266	Total grid current	Eb = Ec2 = 50 Vdc, Ec1 = -1.5 Vdc (see note 2)	0.65	II	Ic1	0	-1.0	μAdc
1256	Electrode current (anode)		0.65	II	Ib	1.0	2.2	mAdc
1306	Transconductance	Esig = 50 mVac (max), bypass Rg1 with 1-μf capacitor	0.65	II	Sm	1,200	2,700	μmhos
1231	Emission	Eb = Ec1 = Ec2 = Ec3 = 15 Vdc (see note 2)	0.65	II	Is	50	---	mAdc
1201	Short and discontinuity detection		0.4	II	---	---	---	---
Appendix D, 20(a), 30	Visual and mechanical inspection criteria		---	---	---	---	---	---
Appendix D, 20(b)	Dimensions	Outline 5-2; dimensions A, C, D, and E	1.0	I	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes	E (p-all) = -100 Vdc	4.0	L6	R	10	---	Meg
1031	Low-frequency vibration	Eb = Ec2 = 50 Vdc; Rp = 10,000 ohms; Ec1 = -1.5 Vdc	6.5	L6	Ep	---	150	mVac
1301	Heater current		6.5	L6	If	64	76	mA
(D) 1336	Heater-cathode leakage		6.5	L6	Ihk	---	20	μAdc
1256	Electrode current (screen)		6.5	L6	Ic2	0.4	0.9	mAdc
1331	Direct-interelectrode capacitance	Shield No. 316	6.5	Code F	Cgp Cin Cout	--- 4.0 3.5	0.004 7.0 6.5	pf pf pf
1121 and 4.3.2	Base strain		---	---	---	---	---	---
2126	Glass strain		4.0	I	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
4.7 and 1501	Life-test provisions (intermittent)	Group A: Eb = Ec2 = 50 Vdc, Rg1 = 0.25 Meg Ehk = 100 V	---	---	---	---	---	---
4.7.3	Life-test end point (intermittent) (500 hours)	Transconductance	---	---	Sm	1,100	---	μmhos

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:20Z
Check the source to verify that this is the current version before use.

NOTES:

1. See 6.5.2.3 for reduced pressure (altitude) rating, and for altitude, maximum peak voltage. (B)

2. This test to be performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL
Navy - SH
Air Force - 11, 85
DSA - ES

User activities:
Army - None
Navy - AS, OS, MC, CG
Air Force - 19

Preparing activity:
Navy - EC

(Project 5960-2211-7)

Code C

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:20Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:20Z
Check the source to verify that this is the current version before use.