INCH-POUND
MIL-DTL-24643/35D
1 October 2009
SUPERSEDING
MIL-DTL-24643/35C
22 August 2002

DETAIL SPECIFICATION SHEET

CABLE, ELECTRICAL, -20 °C TO + 90 °C, TYPE LS3SU (INCLUDING VARIATION LS3SUS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-24643.

This cable can be manufactured in two variations: LS3SU and LS3SUS (double overall shield).

Construction, Non-Watertight

First	-	Copper conductor, coated or uncoated, 18 AWG (7 by 0.0152 inches).
Second	-	Separator may be used at manufacturer's option where required to provide free-stripping insulation.
Third	-	Thermoset insulation. Nominal wall thickness of 0.013 inch; wall thickness may vary from nominal as necessary, in order for the completed cable to meet the specified electrical requirements. Colored insulation, one white, one black, and one red conductor to form each triad.
Fourth	-	Three conductors (one black, one white, and one red) cabled together with a nominal lay of 3.5 inches to form each triad.
Fifth	-	An optional binder.
Sixth	-	Braided shield of 34 or 36 AWG, coated or uncoated copper. Braid angle of 30 to 35 degrees; minimum coverage of 85 percent.
Seventh	-	Shield insulation of two polyester tapes, outer tape sealed. An alternate shield insulation may consist of one polyester tape, plus an extruded jacket of a suitable transparent material, minimum average thickness of the transparent material 0.003 inch. The standard identification code shall be applied by Method 2.
Eighth	-	The specified number of triads (see table I) shall be cabled together in accordance with 3.4.4 of MIL-DTL-24643. Cabling sequence shall be consecutive starting with no. 1 from the center outward. Fillers may be used as necessary to form a firm well-rounded assembly.
Ninth	-	An optional binder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:07Z
Check the source to verify that this is the current version before use.

Construction, Variant Type LS3SU

Tenth - Cross-linked polyolefin jacket (see table I for thickness).

Construction, Variant Type LS3SUS

Tenth - Braided shield of tin-coated copper with minimum coverage of 85 percent.

Eleventh - Spirally-wrapped polyethylene terephthalate (polyester film) separator tape with a 25 percent minimum overlap.

Twelfth - Braided shield of tin-coated copper with minimum coverage of 85 percent.

Thirteenth - An optional binder.

Fourteenth - Cross-linked polyolefin jacket (see table II for thickness).

TABLE I. Details (unshielded).

Military part no. M24643/36	Type and size	Number of triads	Cable jacket thickness min. avg. (inch)	Overall diameter	
				min. (inch)	max. (inch)
-01UN	LS3SU-3	3	0.040	0.650	0.700
-02UN	LS3SU-7	7	0.050	0.840	0.910
-03UN	LS3SU-10	10	0.050	1.100	1.190
-04UN	LS3SU-14	14	0.050	1.200	1.290
-05UN	LS3SU-19	19	0.050	1.340	1.430
-06UN	LS3SU-24	24	0.060	1.580	1.670
-07UN	LS3SU-30	30	0.060	1.680	1.770
-08UN	LS3SU-37	37	0.060	1.840	1.930
-09UN	LS3SU-44	44	0.060	2.060	2.150

TABLE II. Details (shielded).

Military part no. M24643/36	Type and size	Number of triads	Cable jacket thickness min. avg. (inch)	Overall diameter	
				min (inch)	max (inch)
-01UD	LS3SUS-3	3	0.040	0.710	0.760
-02UD	LS3SUS-7	7	0.050	0.900	0.970
-03UD	LS3SUS-10	10	0.050	1.160	1.250
-04UD	LS3SUS-14	14	0.050	1.260	1.350
-05UD	LS3SUS-19	19	0.050	1.400	1.490
-06UD	LS3SUS-24	24	0.060	1.640	1.730
-07UD	LS3SUS-30	30	0.060	1.740	1.830
-08UD	LS3SUS-37	37	0.060	1.900	1.990
-09UD	LS3SUS-44	44	0.060	2.120	2.210

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:07Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Qualification required.

INSPECTION:

Basic Electricals:	
Conductor resistance (ohms/1000 feet at 25 °C, max.)	7.06
Voltage withstand (volts, root mean square, min.)	
Conductor to conductor	2000
Conductor to shield	1000
Component shield to all other shields	500
Overall shield to overall shield (Type LS3SUS only)	200
Insulation resistance (megohms/1000 feet, min.)	
Conductor to conductor	500
Conductor to shield	500
Component shield to all other shields	100
Overall shield to overall shield (Type LS3SUS only)	100
Conductor continuity	No failure
Shield continuity	No failure
Jacket flaws (Type LS3SUS only)	No failure
Group A:	
Visual and dimensional	No failure
Capacitance	
Mutual capacitance, at 1 kilohertz (KHz) (pF/ft, max.)	30
Capacitance unbalance (percent max.)	10
Group B:	
Thermoset proof test (percent, max.)	
Insulation	50
Jacket (when tested at 200 °C)	50
Physicals (unaged)	
Insulation (extruded)	
Tensile strength (lb/in^2, min.)	700
Elongation (percent, min.)	150
Jacket (cable)	
Tensile strength (lb/in^2, min.)	1300

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:07Z
Check the source to verify that this is the current version before use.

Elongation (percent, min.)	160
Tear (lb/in thickness, min.)	35
Group C:	
Physicals (aged) air oven	
Insulation (extruded)	
Tensile strength (percent of unaged, min.)	75
Elongation (percent of unaged, min.)	75
Jacket (cable)	
Tensile strength (percent of unaged, min.)	60
Elongation (percent of unaged, min.)	60
Permanence of printing (jacket) (cycles, min.)	125
Heat distortion (percent of unaged, max.)	30
Shrinkage	No failure
Shield (conformance to material, construction and coverage)	No failure
Surface transfer impedance (Type LS3SUS only)	
Milliohms per meter (max.)	700
EMP response (dB, min.)	60
Group D:	
Flame propagation (cable)	No failure
Qualification Inspection:	
Qualification inspection shall include basic electricals; groups A, B, C, and D; plus the following:	
Aging and compatibility (cable) (125±5 °C)	No failure
Abrasion resistance (jacket) (scrapes, min.)	75
Acid gas equivalent (percent, max.)	
Jacket	2
Fillers	2
Insulation	18
Shield insulation	2
Halogen content (percent, max.)	
Jacket	0.2
Fillers	0.2
Insulation	0.2
Immersion (jacket)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:07Z
Check the source to verify that this is the current version before use.

Tensile strength (percent of unaged, min.)	50
Elongation (percent of unaged, min.)	50
Smoke index (max.)	
Jacket	25
Fillers	45
Insulation	45
Toxicity index (max.)	
Jacket	5
Fillers	5
Insulation	1.5
Durometer (jacket) - Type A (hardness, min.)	80
Weathering (jacket)	No failure
Electrical moisture absorption	No failure

UNIT ORDERING LENGTHS:

Types	Sizes	Feet (nominal)
LS3SU and LS3SUS	3 through 19	1000
LS3SU and LS3SUS	24 through 44	500

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army – MI
Navy – SH

Preparing Activity:
Navy – SH
(Project 6145-2008-039)

Review Activities:
Army – AR, AV, CR
Navy – CG, EC
DLA – CC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T00:07Z
Check the source to verify that this is the current version before use.