MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, TYPE IV, 100 PIN, STRAIGHT THROUGH, CONTACT TAILS ON .100 CENTERS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-28754.





FIGURE 1. Dimensions and configurations.

(B) Denotes changes

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:43Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.001	.03	.015	.38	.120	3.05	.217	5.51	4.960	125.98
.002	.05	.020	.51	.125	3.18	.220	5.59	5.005	127.13
.003	.08	.040	1.02	.134	3.40	.270	6.86	5.200	132.08
.004	.10	.050	1.27	.145	3.68	.280	7.11	5.440	138.18
.005	.13	.100	2.54	.150	3.81	.360	9.14		
.007	.18	.106	2.69	.17	4.3	4.900	124.46		
.010	.25	.114	2.90	.190	4.83				

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified, tolerances are ±.005 (.13 mm) for three place decimals, ±.01 (.3 mm) for two place decimals and ±2° for angles.
4. Flash around blade contacts not to exceed .010 inch from the surface of the insulator and shall be firmly attached.
5. The line referred to as - B - designates a plane passing through the axis of two (2) .114 $^{+.000}_{-.005}$ inch diameter keying pin holes.
6. Pin shield shall be marked with contact numbers 1, 50, 51 and 100 in white ink .06 (1.5 mm) inch high.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:43Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Material:

Body: Green diallyl phthalate glass filled type SDG-F in accordance with MIL-M-14.

Ⓑ Pin shields: Aluminum alloy 5052, H34 in accordance with QQ-A-250/8; anodized black in accordance with type III, class 2 of MIL-A-8625. Alternate material unclad epoxy glass in accordance with MIL-P-13949, type GF.

Contact leads: Tinned and covered to a thickness of 0.0005 inch to 0.0030 inch with solder in accordance with QQ-S-571, type Sn60, form B, type Sn60. A noncorrosive flux may be used in accordance with MIL-F-14256, type RMA.

Contact resistance: Voltage drop shall not exceed 20 millivolts.

Solderability: In accordance with MIL-C-28754.

Current rating: 3 amperes.

Temperature range: -55°C to +105°C.

Voltage rating: 300 volts, AC (rms) at sea level.

Durability: Voltage drop shall not exceed 20 millivolts.

Pin shield retention: In accordance with MIL-C-28754.

Military part number: M28754/44- (dash number from table I).

TABLE I. Dimensions and supersession data.

Dash no.	D	Supersession (code 28687)
-01	.062 (1.57) .058 (1.47)	0102-694-1
-02	.035 (.89) .031 (.79)	0102-694-2

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - MC
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AR, MI
Navy - YD, AS

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5935-3266-39)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE

MIL-C-28754/44B

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

Naval Electronic Systems Command
Washington, D. C. 20363

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12903 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20363

ATTN: ELEX 8111

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:43Z
Check the source to verify that this is the current version before use.