GGG-B-00325C(ME)
July 17 1987
USED IN LIEU OF
GGG-B-325B
July 18, 1980

FEDERAL SPECIFICATION

BINDER, LOAD

This interim Federal Specification was developed by the General Services Administration, Office of Federal Supply and Services, Washington, DC, 20406, based on currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to GGG-B-325B, dated July 18, 1980.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers lever-operated, eccentric load binders.

1.2 Classification.

1.2.1 Types, classes, and styles. Load binders covered by this specification shall be of the following types, classes, and styles as specified (see 6.2).

Type I - Plain.
Type II - With slack take-up hook arrangement.

Class 1 - Without compression spring.

Style A - Light duty.
Style C - Heavy duty.

Class 2 - With compression spring.

Type III - With continuous slack take-up double claw-hook arrangement.

Class 1 - Without compression spring.

Style A - Light duty.
Style B - Medium duty.
Style C - Heavy duty.

Class 2 - With compression spring.

AMSC N/A FSC 3990
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

Type IV - Latching type load binder with low energy release feature.

Class 1 - Without compression spring.

Style A - Light duty.
Style C - Heavy duty.

Class 3 - With compression unit.

Style A - Light duty.
Style C - Heavy duty.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The issues of the following documents, in effect on date of invitation for bids or solicitation for offers, form a part of this specification to the extent specified herein.

Federal Specfication:

PPP-P-40 - Packaging and Packing of Hand Tools.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions, as outlined under General Information in the Index of Federal Specifications, Standards, and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection for Attributes.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM A 413 - Carbon Steel Chain.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT CLASSIFICATION

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

3. REQUIREMENTS

3.1 Material. Materials of component parts of the binders shall be as specified in 3.1.1 through 3.1.7. The manufacturer shall utilize recovered materials to the maximum extent practicable.

3.1.1 Operating lever. The operating levers shall be of malleable iron, forged steel, or cast steel.

3.1.2 Swivels. The swivels shall be either malleable alloy or drop forged steel.

3.1.3 Hooks. The hooks shall be of high strength drop forged steel.

3.1.4 Clevis and tongue. The clevis and tongue shall be of forged steel or alloy steel.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:39Z
Check the source to verify that this is the currentversion before use.

3.1.5 Links. The links shall be of either alloy or forged steel.

3.1.6 Pins. The pins shall be of hardened steel.

3.1.7 Compression spring. The compression spring shall be of spring steel.

3.1.8 Compression unit. The compression unit shall be of a molded rubber elastomer enclosed by threaded U-bolts, end caps and nuts.

3.2 Illustrations. The illustrations shown herein are for the convenience of identification only and are not intended to preclude the purchase of load binders which are otherwise in accordance with the requirements of this specification.

3.3 Design. Types I and II load binders shall consist essentially of an operating lever, clevis, tongue, two swivels, two links, two pins, two grab hooks, and for type II, class 2, a compression spring. Type III load binders shall consist essentially of an operating lever, two clevises, a tongue, a swivel, three links, two claw hooks, a grab hook, and, for class 2, a compression spring. Type IV latching load binders shall consist essentially of an operating lever, front clevis, back clevis, with stabilizing flat base to prevent binder from digging into and damaging load, two swivels, two links, two grab hooks, a handle pin, and a greased front clevis pin. The load binders shall be designed for eccentric take-up and latching type take-up. The load binders shall operate in accordance with the following:

a. Provide a minimum take-up of 4 inches for load binders with compression spring or compression unit, take-up is to be calculated with compression element not compressed.
b. Allow free movement of the assembled parts of the load binder.
c. Preclude the possibility of the parts binding or spreading under normal service conditions.
d. Withstand the minimum pulling load specified in 3.5, 3.6, and 3.7, as applicable, without breakage and permanent deformation.
e. Provide suitable means for a positive and permanent lock whereby the lever will be held in a fixed position when the take-up operation is completed.
f. Acceptable means for a positive and permanent lock (which may be provided, includes, but is not restricted to the following:

(1) A pin fastened to the load binder by a chain and appropriate holes in parts of the binder.
(2) A hook on a chain attached near the free end of the lever.
(3) Construction utilizing the slack end of the chain. (An over center pivot arrangement, by itself, is not considered a positive and permanent locking means. Also the chain slack end wrapped around the handle is not acceptable as a permanent locking means.)
(4) An acceptable means for a positive and permanent lock for type IV latching-type load binder is a tiedown hole in end of handle to tie down handle.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

3.3.1 Operating lever. The operating lever shall be of such design as to have a tie bar or solid back construction.

3.4 Interchangeability of parts. All parts of a particular model load binder shall be interchangeable with the similar parts of any other load binder of their same model made by the same manufacturer.

3.5 Type I, plain load binder. Type I load binders shall be capable of binding any load that requires the use of 1/4-inch, up to and including 1/2-inch chain. The length of the operating lever shall be not more than 18-1/2 inches. The load binder shall be capable of withstanding a tensile proof load of 16,000 pounds (see 4.3.1.1). The load binders shall weigh not less than 8 pounds nor more than 14 pounds and shall be similar to figure 1.

FIGURE 1 - Type 1, plain.

3.6 Type II, load binders with slack take-up hook. Type II load binders shall be provided with a slack take-up hook arrangement and shall be constructed in such a manner that tension will be maintained on the chain at all times during the take-up operation. Class 1, style A load binders shall have an operating lever not more than 18 inches in length and shall be capable of withstanding a tensile proof load of 12,000 pounds (see 4.3.1.2.1). Class 1, style C and class 2 load binders shall have operating levers not more than 20 inches in length and shall be capable of withstanding a tensile proof load of 15,000 pounds (see 4.3.1.2.2).

3.6.1 Slack take-up hook arrangement. The slack take-up hook arrangement of type II load binders shall be simple and easy to operate and shall have a leverage of not more than a 10-inch movement at the end of the operating lever to 1-inch movement of the slack take-up hook. The slack take-up hook of class 1, style A load binders shall be capable of withstanding a proof load of 6,000 pounds (see 4.3.2.1.1). The slack take-up hook of class 1, style C, and class 2 load binders shall be capable of withstanding a proof load of 8,000 pounds (see 4.3.2.1.2 and 4.3.2.2).

3.6.2 Class 1, load binders without compression spring. Type II, class 1, styles A and C load binders shall be similar to figure 2.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

FIGURE 2 - Type II, class 1, styles A and C, with slack take-up hook arrangement, without compression spring.

3.6.2.1 Style A, light duty. Type II, class 1, style A load binders shall be provided with grab hooks and a slack take-up hook. The load binders shall be designed for use with 1/4- and 3/8-inch chains. The chain shall meet ASTM A 413, table 3, link dimensions of Proof Coil (PC) and High Test (HT) lid and chain for both 0.281 (1/4-inch) and 0.406 (3/8-inch) link diameter.

3.6.2.2 Style C, heavy duty. Type II, class 1, style C load binders shall be provided with grab hooks and a slack take-up hook. The load binders shall be designed for use with 3/8- and 1/2-inch chains.

3.6.3 Class 2, load binders with compression spring. Type II, class 2 load binders shall be similar to figure 3. The load binders shall be provided with grab hooks and a slack take-up hook designed for the use with 3/8- and 1/2-inch chains. The load binder shall be provided with a compression spring assembly which shall function as a link.

FIGURE 3 - Type II, class 2, with slack take-up hook arrangement, with compression spring.

3.6.3.1 Compression spring. The compression spring shall be capable of exerting a force of 5,000 pounds ±200 pounds immediately prior to becoming solid without taking a permanent set. The spring shall have a mean free diameter of not more than 3-1/2 inches and shall have a rate not greater than 4,000 pounds per inch deflection. Hook or hairpin loops external to the spring will not be acceptable.

3.7 Type III, load binders with continuous slack take-up double claw hook. Type III load binders shall be provided with continuous slack take-up double claw hook arrangement and be constructed in such a manner that tension will be maintained on the chain at all times during the take-up operation. Type III load binders shall have an operating lever not more than 22 inches in length. Class 1,



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

style A, and class 2 load binders shall be capable of withstanding a tensile proof load of 7,000 pounds (see 4.3.1.4.1). Class 1, style B load binders shall be capable of withstanding a tensile proof load of 19,000 pounds (see 4.3.1.4.2). Class 1, style C load binders shall be capable of withstanding a tensile proof load of 28,000 pounds (see 4.3.1.4.3).

3.7.1 Continuous slack take-up double claw hook arrangement. The continuous slack take-up double claw hook arrangement of type III load binders shall be easy to engage and lock onto the chain and shall have a leverage of not more than 10-inch movement at the end of the operating lever to 1-inch movement of the claw hook engaged on the chain.

3.7.2 Class 1, load binders without compression spring. Type III, class 1, styles A, B, and C load binders shall be similar to figure 4.

3.7.2.1 Style A, light duty. Type III, class 1, style A load binders shall be designed for use with 3/16- and 1/4-inch chains.

3.7.2.2 Style B, medium duty. Type III, class 1, style B load binders shall be designed for use with 5/16- and 3/8-inch chains.

3.7.2.3 Style C, heavy duty. Type III, class 1, style C load binders shall be designed for use with 7/16- and 1/2-inch chains.

FIGURE 4 - Type III, class 1, styles A, B, and C, with continuous slack takeup double claw hook arrangement, without compression spring.

3.7.3 Class 2, load binders with compression spring. Type III, class 2 load binders shall be similar to figure 4 except that the grab hook assembly shall be provided with a compression spring assembly which shall function as a link (see figure 3). The load binders shall be designed for use with 3/8- and 1/2-inch chains. The compression spring shall conform to the requirements of 3.6.3.1.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

FIGURE 5 - Type IV, latching load binder.

3.7.4 Type IV, latching binder without compression unit. Type IV latching load binders shall be provided with a handle and sliding front clevis pin so that energy can be transferred to a back clevis for low energy release feature. Type IV load binders shall have an operating lever of not more than 19 inches in length. Class 1, style A load binders shall be capable of withstanding a tensile proof load of 12,000 pounds (see 4.3.2.3.1) and class 1, style C, a load of 15,000 pounds (see 4.3.2.3.2). The load binders shall weigh not less than 8 pounds nor more than 14 pounds and shall be similar to figure 5.

3.7.4.1 Style A, light duty. Type IV, class 1, style A load binders shall be designed for use with 1/4- through 3/8-inch chain sizes.

3.7.4.2 Style C, heavy duty. Type IV, class 1, style C load binders shall be designed for use with 3/8- through 1/2-inch chain sizes.

3.7.5 Type IV, latching load binder with compression unit. Type IV, class 3, latching load binders shall be similar to figure 5 except that the grab hook assembly shall be provided with a compression unit assembly which shall function as a link.

3.7.5.1 Compression unit. The molded rubber elastomer shall be capable of exerting a force of 5000 pounds ±200 pounds prior to becoming solid without a permanent set.

3.7.5.2 Style A, light duty. Type IV, class 3, style A shall be designed for use with 1/4- through 3/8-inch chain. The compression unit shall conform to the requirements of 3.7.5.1.

3.7.5.3 Style C, heavy duty. Type IV, class 3, style C shall be designed for use with 3/8- through 1/2-inch chain. The compression unit shall conform to the requirements of 3.7.5.1.

3.8 Finish. The load binders shall be free from fins, burrs, and excessive roughness and shall have a suitable protective coating or be painted. When painted, the color shall be in accordance with the manufacturer's standard practice.

3.9 Identification marking. Each load binder shall be plainly marked with the manufacturer's designation for the item and with his name or trademark of such known character that the source of manufacture may be readily determined.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

3.10 Workmanship. The load binders shall be free from defects which may detract from their appearance or affect their serviceability.

4. QUALTIY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection for acceptance. Inspection shall be made in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 Inspection of components and materials. In accordance with 4.1, the contractor is responsible for insuring that all components and naterials used were manufactured, tested and inspected in accordance with the requirements or referrenced subsidiary specifications and standards to the extent specified herein or, if none, in accordance with this specification.

4.2.2 End product inspection.

4.2.2.1 Visual examination. Representative samples of the completely assembled end item shall be examined for defects in finish, material, construction, workmanship, and marking. Defects shall be classified as outlined in table I. The inspection level shall be II with an acceptable quality level (AQL) of 1.0 for major defects and 6.5 for total defects expressed in defects per hundred units.

TABLE I. Examination.

| Defects | |
|---|---|
| Major | |
| 101. | Any area of rust or corrosion on protective finish. |
| 102. | Component not fabricated of the specified material. |
| 103. | Any characteristics not in accordance with the specified design requirements. |
| 104. | Any component cracked, fractured, or otherwise damaged affecting serviceability. |
| 105. | Any component missing. |
| 106. | Any operation omitted or not performed as specified. |
| 107. | Any sharp edges, butts, or metal slivers. |
| 108. | Any part not assembled or joined as specified. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE I. Examination. (Cont'd)

| Minor | |
|---|---|
| 201. | Any breaks in protective finish through coating to metal. |
| 202. | Dirt, oil, grease, or other foreign matter in finish. |
| 203. | Defective or other damaged component, but not affecting servicability. |
| 204. | Functioning component that requires abnormal force to operate. |
| 205. | Identification marking missing, incomplete, illegible, or incorrect. |

4.2.2.2 Dimensional examination. Examination shall be made of the end item to determine compliance with dimensional requirements. The inspection level shall be S-2 with an AQL of 6.5 defects per hundred units.

4.2.2.3 Sampling for tests. A random sample of load binders shall be taken from each inspection lot in accordance with MIL-STD-105 at inspection level S-3 for tests of 4.3. If any load binder fails any of the tests, the lot shall be rejected.

4.3 Test procedures.

4.3.1 Tensile load test of load binders. Sample load binders shall tested in any suitable tensile testing device. The binder shall be secured in the testing device by its grab hooks. The operating handle of the binder shall be in the closed or load binding position during the test. The binders shall be loaded as specified in 4.3.1.1, 4.3.1.2.2, 4.3.1.3, 4.3.1.4.2, and 4.3.1.4.3. Following each loading test, the binder shall be examined for failure of any component and permanent deformation of the total binder. Any evidence of failure or permanent deformation shall be cause for rejection.

4.3.1.1 Type I, load binders. Type I load binders shall be tension loaded to 16,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.1.2 Type II, class 1, load binder.

4.3.1.2.1 Style A. Type II, class 1, style A load binders shall be tension loaded to 12,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.1.2.2 Style C. Type II, class 1, style C load binders shall be tension loaded to 15,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.1.3 Type II, class 2, load binders. The test procedure and loading shall be identical with that for type II, class 1, style C, as specified in 4.3.1.2.2.

4.3.1.4 Type III, class 1, load binders.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

4.3.1.4.1 Style A. Type III, class 1, style A, and class 2 load binders shall be tension loaded to 7,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.1.4.2 Style B. Type III, class 1, style B load binders shall be tension loaded to 19,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.1.4.3 Style C. Type III, class 1, style C load binders shall be tension loaded to 28,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.2 Slack take-up hook load test. Sample load binders shall be tested in any suitable tensile testing device to determine conformance to the slack take-up hook loading requirements of 3.6.1. The binder shall be secured in the testing device by the trailing grab hook and the slack take-up hook. The shank of the slack take-up hook shall be vertical to a longitudinal line through the grab hooks during the test. The take-up hook and components of the binder that were subjected to loading shall be examined for any failure and permanent deformation.

4.3.2.1 Type II, class 1, load binders.

4.3.2.1.1 Style A. Type II, class 1, style A load binders shall be loaded as specified in 4.3.2 to 6,000 pounds, this load being applied for not less than 1/2 minute. The load shall then be removed and the load binder examined.

4.3.2.1.2 Style C. Type II, class 1, style C load binders shall be loaded as specified in 4.3.2 to 8,000 pounds, this load being applied for not less than 1/2 minute. This load shall then be removed and the load binder examined.

4.3.2.2 Type II, class 2, load binders. The test procedure and loading shall be identical with that for type II, class 1, style C load binders as specified in 4.3.2.1.2.

4.3.2.3 Type IV, class 1, load binders.

4.3.2.3.1 Style A. Class 1 load binders shall be tension loaded to 12,000 pounds with load applied for not less than 1/2 minute. The load shall be removed and the load binder examined for any cracks or other damage that will cause the binder to fail.

4.3.2.3.2 Style C. Class 1 load binders shall be tension loaded to 15,000 pounds with load applied for not less than 1/2 minute. The load shall be removed and the load binder examined for any cracks or other damage that will cause the binder to fail.

4.3.2.4 Type IV, class 3, load binders.

4.3.2.4.1 Style A. The test procedure and loading shall be identical with that for type IV, class 1, style A load binder as specified in 4.3.2.3.1.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

4.3.2.4.2 Style C. The test procedure and loading shall be identical with that for type IV, class 1, style C, load binder specified in 4.3.2.3.2.

4.3.2.5 Compression unit test. Sample compression units for class 3 load binders shall be tested in any suitable testing device to determine conformance to the requirements of 3.7.5 or 3.7.5.1 as applicable. The unit shall be compressed to 5000 ±200 pounds and shall be held in this position for not less than 1/2 minute. The load shall then be removed and the unit examined for any failure and permanent deformation.

4.3.3 Compression spring test. Sample compression springs for class 2 load binders shall be tested in any suitable testing device to determine conformance to the requirements of 3.6.3.1 or 3.7.3 as applicable. The spring shall be compressed to a length immediately prior to its becoming solid and shall be held in this position for not less than 1/2 minute. The load shall then be removed and the spring examined for any failure and permanent deformation.

4.4 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery and selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 1.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; or improper size, location, sequence, or method or application. |
| Materials | Any component missing or damaged. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping, and inadequate strapping, and inadequate stapling. |
| | Bulging or distortion of container. |

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. The packaging, packing, and any additional marking shall be level A or commercial as specified in 6.2.

5.1.1 Level A. The load binder shall be packaged, packed, and marked in accordance with PPP-P-40.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. The binders shall be packaged in accordance with normal commercial practice and packed in a manner that will assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification.

5.1.2.1 Marking. Marking shall be in accordance with the contract or purchase order.

6. NOTES

6.1 Intended use. The load binders covered by this specification are intended for use as a tiedown tensioning device for binding such lading as logs, lumber, pipes, beams, hay, and other materials on open trucks, flat cars, and ships.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Type, class, and style required (see 1.2.1).
c. Level of packaging required (see 5.1).
d. Level of packing required (see 5.1).
e. Additional marking, when required (see 5.1).

6.3 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

MILITARY INTEREST:

Custodians

Army - ME
Navy - SA

User activity

Navy - SH

CIVIL AGENCY COORDINATING ACTIVITES:

AGR
COM
FSS

PREPARING ACTIVITY:

Army - ME

Project 3990-A199

---

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.



Source: https://assist.dla.mil -- Downloaded: 202640-26T12:39Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
Belvoir Research, Development,
and Engineering Center
ATTN: STRBE-TSE
Fort Belvoir, VA 22060-5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| GGG-B-00325C(ME) | Binders, Load |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

*(TO DETACH THIS FORM, CUT ALONG THIS LINE.)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.