AMENDMENT

TO

FEDERAL SPECIFICATION

DIE, THREADCUTTING AND RETHREADING, COLLET, THREADING DIE: AND DIESTOCK (BOLT AND SCREW THREADING, UNIFIED, AMERICAN NATIONAL AND METRIC FORM THREADS)

This amendment, which forms a part of Federal Specification GGG-D-296B, dated February 23, 1968, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 2

Paragraph 2.1, add:

Federal Specification:

PPP-P-40 - Packaging and Packing of Hand Tools.

Paragraph 2.1, under Military Standards: Delete "MIL-STD-129 - Marking for Shipment and Storage." and "MIL-STD-130 - Identification Marking of U.S. Military Property.".

Paragraph 3.3: Delete and substitute:

"3.3 Material of dies. Unless otherwise specified (see 6.2), the steel used for dies shall be carbon tool steel or high speed steel."

Paragraph 3.4: Delete and substitute:

"3.4 Hardness of dies. Carbon tool steel dies shall be hardened to Rockwell C 57 to 63, and high speed steel dies to Rockwell C 61 to 65. The cutting lands of the die threads shall show no evidence of partial or total decarbonization."

PAGE 3

Paragraph 3.5.1: Delete and substitute:

"3.5.1 Marking of dies, collets, and diestocks: All dies, collets, and diestocks shall be marked in a plain and permanent manner with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined."

Paragraph 3.5.1.1: Delete and substitute:

"3.5.1.1 Die marking. American Standard threads will be marked with the nominal size designation and the number of threads per inch, separated by a dash. Metric threads will be marked with a capital M followed by the nominal size and pitch in millimeters, separated by a capital X. Marking shall be by etching or other equally permanent method."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

PAGE 3 (CON.)

Paragraph 3.5.1.1.2: Add new subparagraph as follows:

"3.5.1.1.2 High speed steel dies. Dies made of high speed steel shall be clearly marked "HS" or "HIGH SPEED".

Paragraph 3.7: Delete and substitute:

"3.7 Die adjustment. Types I and II dies shall be capable of adjustment which will produce threads with pitch diameters within a range of basic pitch diameter to the minimum pitch diameter for a class 2A thread as listed in NBS H28.

Paragraph 3.10: Immediately preceding the last sentence, insert "The threads at the front face shall be chamfered approximately 2 to 3 threads, and 1 to 1-1/2 threads at the rear face."

PAGE 7

Paragraph 3.12: Delete and substitute:

"3.12 Type III, hexagon rethreading dies, solid. Type III hexagon rethreading dies shall be of solid construction, be similar to figure 3, and conform to the dimensions and tolerances shown in table IV. The clearance between lands shall be of sufficient depth to provide room for the disposal of chips and foreign matter. Both faces shall be parallel and square to the axis of the threads within a total indicator variation of 1/64th inch. The cutting edge shall have a positive angle and the chamfered thread crests shall be relieved. Threads shall be within the limits of the maximum for a class 3A thread and the minimum for a class 2A thread, as listed in NBS H28.

PAGE 10

Paragraph 3.15: Delete and substitute:

"3.15 Workmanship. There shall be no defects which may affect serviceability, durability, or appearance. In addition, dies shall contain no defects which may affect serviceability or appearance of threads which are cut by the die."

PAGE 12

Paragraphs 4.4.2, 4.4.3 and 4.4.4: Delete and substitute:

"4.4.2 Thread cutting test. Two test dies shall be drawn from the sample that was selected in accordance with 4.2.1 to be used for thread cutting tests as follows:

4.4.2.1 Types I and II dies. Each of the two test dies shall cut a thread 2 inches long on 10 sample lengths of medium carbon (1035-1050) steel rod of the applicable size. During the course of the test, the dies shall be adjusted after each cut until the high and low extremes of the adjustment as required in 3.7 are met. Failure of the dies to produce clean smooth threads at the end of test, or the inability of the dies to adjust to the high and low limits shall be cause for rejection.

4.4.2.2 Type III dies. Each of the two test dies shall be tested on previously threaded medium carbon (1035-1050) steel rods of the same nominal size and pitch of the test dies. One rod shall be within class 2A thread limits, and the other, within class 3A thread limits. A steel weight of at least one pound shall be allowed to drop freely from a height of two feet onto the external threads of the test specimen in order to cause damage to the threads. The rethreading die being tested

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

shall then be threaded over the damaged class 2A threads. If the test die recuts the thread to more than 0.002 inch below the minimum pitch diamter for a class 2A thread, the die shall be considered defective and rejected. If the die being tested does not completely remove the deformed portion of the threads, the same die shall be threaded onto the class 3A threaded rod. Failure of the die to remove the deformed portion of the class 3A threads shall be cause for rejection of the sample unit."

Delete Section 5 and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with PPP-P-40. Preservation and packaging shall be level A, B, or C as specified (see 6.2), packing shall be level A, B, or C as specified (see 6.2), and marking shall be for civil agencies or military activities as specified (see 6.2)."

Paragraph 6.1.2: Delete last part of first sentence beginning with the word "but".

Paragraph 6.2: Insert the following options and redesignate the existing options in proper alphabetical sequence:

"c. Material requirement, when different (see 3.3).

h. Type of marking required (see 5.1)."

MILITARY INTERESTS:

DOD has waived coordination on revisions and amendments to this Federal Specification until further notice.

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.