GGG-F-325B
AMENDMENT-3
August 30, 1973
SUPERSEDING 1/
Amendment-2
April 22, 1968

FEDERAL SPECIFICATION

FILE, HAND (AMERICAN PATTERN) AND RASP, HAND

This amendment, which forms part of Federal Specification GGG-F-325B, dated October 31, 1966, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 2

3.1: Delete and substitute:

3.1 Qualification. The files and rasps furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time set for opening of bids (see 4.2 and 6.3).

Pages 3 and 4

3.12: Delete the last sentence and substitute:

"The tang shall be tempered to a hardness not greater than 30 Rockwell C at a point approximately midway of its length and width (see 4.5.1)."

Page 12

3.28.1: Delete and substitute:

3.28.1 Class 1 regular, styles A, B, and C. Bastard-cut, second-cut, and smooth-cut. The files shall taper at least 1/3 of the length to the point. Bastard-cut files in lengths 4 inch through 10 inch shall be single cut or double cut. Bastard-cut files in lengths 12, 14, and 16 inch shall be double cut. Second-cut files shall be single cut except the 12 and 14 inch lengths which shall be double cut. Smooth cut files shall be single cut. The files shall conform to table XVIII and shall be similar to figure 17.

Page 21

3.39 Delete and substitute:

"3.39 Workmanship: The teeth of the files shall be well-defined, sharp, and uniform in height and form. There shall be no evidence of rust or other defects which may impair durability, serviceability, or appearance.

4.1: Delete and substitute:

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2, line 3: Delete "Bureau of Ships" and substitute "Naval Ship Engineering Center".

1/ THE MARGINS OF THIS SPECIFICATION ARE MARKED "0" TO INDICATE WHERE CHANGES (ADDITIONS, MODIFICATIONS, CORRECTIONS, DELETIONS) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS WAS DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

Page 21 (continued)

Footnote 1/: Delete and substitute:

1/Application for Qualification tests shall be made in accordance with Provisions Governing Qualification SD-6 (see 6.3 and 6.3.1).

Add new 4.2.1.1.1 as follows:

"4.2.1.1.1 Samples for qualification of individual types. When all types are not manufactured by a manufacturer, two each of the class, cut, and length as listed in table XXXV for the applicable type for which qualification is requested shall be furnished.

Page 23

4.5.1: Delete and substitute:

4.5.1 Tang hardness. The inspector shall satisfy himself that all files and rasps having tangs meet the applicable requirements of 3.12.

Page 25

4.5.7: Add the following: "The sum of the average amounts of bar length removed by file types VII, IX, and XIII shall be a minimum of 3.50 inches. An individual file side or the average of an individual file type, however, shall be considered acceptable at the applicable minimum level stipulated in table XXXIX, providing the total of the 3 averages meets the 3.50 inch requirement."

Table XXXIX: Delete footnote "1/".

Add the following as 4.6:

4.6 Inspection of preparation for delivery. The packaging, packing, and marking sh. be inspected for compliance with section 5 of this document.

Page 27

6.3 and 6.3.1: Delete and substitute:

6.3 With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in applicable Qualified Products List QPL-GGG-F-325 whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Naval Ship Engineering Center, Prince George's Center, Center Building, Hyattsville, Maryland 20782, and information pertaining to qualification of products may be obtained from that activity. Application for Qualification tests shall be made in accordance with "Provisions Governing Qualification SD-6" (see 6.3.1).

6.3.1 Copies of "Provisions Governing Qualification SD-6" may be obtained upon application to Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120.

Custodians:
Army - GL
Navy - SH
Air Force - 84
Review activities:
Army - GL
Navy - SH
Air Force - 84
User activities:
Navy - YD, MC

Preparing activity:
Navy - SH
(Project 5110-0249)

U. S. GOVERNMENT PRINTING OFFICE : 1973 O - 546-576/2368

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.