GGG-L-350
AMENDMENT-3
February 20, 1965

SUPERSEDING
Int. Amendment-2,
April 17, 1964

FEDERAL SPECIFICATION

LIFTER, VALVE SPRING; COMPRESSOR, VALVE SPRING

This amendment, which forms a part of Federal Specification GGG-L-350, dated March 30, 1956, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 2.1: Under Military Specifications delete: "MIL-P-15424 — Packaging of Hand Tools for Domestic and Overseas Shipment and Storage" and substitute: "MIL-H-15424 — Hand Tools, Packaging of".

Page 3: Add the following size and dimensions to table I:

Size number	Capacity (valve spring outside diameter)	A		B (full open position)		Weight (approx.)	Test load (min.)
		Min.	Max.	Min.	Max.		
	Inches	*Inches*	*Inches*	*Inches*	*Inches*	*Pounds*	*Pounds*
4	7/8 to 2-3/4	10-1/2	12	13	14-3/8	9	450

Page 7: Delete 4.1 through 4.3 and substitute:

4.1 Responsibility for inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling and inspection for quality conformance.

4.2.1 *Inspection lot.* All lifters and compressors of the same type, class, and style

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

shall be considered a lot for purposes of quality conformance inspection. The sample unit shall be one valve spring lifter and one valve spring compressor. The inspection level shall be level II with an acceptable quality level of 1.5 defects per hundred units.

4.2.2 *Inspection of end item.* Inspection of the lifters and compressors shall be performed as specified in 4.2.2.1 and 4.2.2.2. The sample unit shall be one completely fabricated and assembled tool.

4.2.2.1 *Visual examination.* The sample unit shall be examined for the defects specified below. The inspection level shall be level II with an acceptable quality level of 4.0 defects per hundred.

Examine	Defect
Material	Not as specified for each type, class, and style.
Operation	Tool does not operate freely; bends or binds.
Finish	Not coated; evidence of rust, corrosion, or pitting.
Marking	Missing, illegible, or not permanent.
Construction and workmanship	Components poorly fitted; sharp edges or burrs.

4.2.2.2 *Dimensional examination.* Each sample unit shall be examined for compliance with dimensions specified in applicable paragraphs and tables. Any deviation therefrom shall constitute a defect. The inspection level shall be level S-3 with an acceptable AQL of 4.0 defects per hundred units.

4.3 **Inspection of preparation for delivery.** Inspection to determine compliance with preparation for delivery shall be made in accordance with MIL-H-15424.

Page 8, paragraph 4.4.3: Delete in its entirety.

Page 8, paragraph 5.2.1, fourth line: Delete "MIL-P-15424" and substitute "MIL-H-15424".

DOD coordination has been waived.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.