GGG-N-350a
Interim Amendment-4
December 9, 1963
SUPERSEDING
Interim Amendment-3 (DOD)
September 26, 1963

INTERIM AMENDMENT

FEDERAL SPECIFICATION

NIPPERS AND PINCERS

This Interim Amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20407, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above. The General Services Administration has authorized Federal agencies to use this Interim Amendment as a valid exception to Federal Specification GGG-N-350a, dated June 8, 1959.

Pages 1 and 2, paragraph 2.1 - Add the following in proper sequence:

"Fed. Test Method Std. No. 151 - Metals; Test Methods"

Page 2, paragraph 2.1 - Delete "MIL-P-15424" in its entirety and substitute the following:

"MIL-H-15424 - Hand Tools, Packaging of"

Page 4, paragraph 3.9.1.3 - Delete the fifth sentence and substitute: "Each jaw shall be secured to the frame by one screw for the 5-1/2 inch size and by two screws for the 7 inch size. The screws shall extend through the jaws and engage a sliding threaded member in a groove in the frame."

Page 4, add after the eighth sentence: "An adjustable stop shall be provided so that excessive pressure will not be placed on the jaws.

Page 4, add the following paragraph:

"3.9.1.3.1 Style C, 5-1/2 inch size, when specified can be supplied with mauling jaws or type cutting jaws."

Page 5, paragraph 3.10.2 - Delete and substitute:

"3.10.2 Class 2, carpenters',- The pincers shall be suitable for use in carpentry work and shall be of high grade, oil-tempered tool steel. The handles shall have plain tips, except that when specified (see 6.1), one handle shall have a screwdriver end for use on screws and for prying, and the other handle shall have an integrally forged "Vee"-shaped opening at the end for extracting tacks or small nails. The pincers shall be capable of withstanding the tests in 4.4.4.2.1 and 4.4.4.2.2, respectively. Class 2 pincers shall conform to table VII for the size specified (see 6.1), and shall be similar to figure 7, except that the handles may have plain ends unless the procurement documents require a screwdriver end and a nailpulling end as illustrated.

Page 6: Delete table III and substitute new table as follows:

TABLE III.---Type I, class 1, style C nippers, end cutting, adjustable jaws, flat

Nominal size	Overall length A		Center of rivet to end of jaw B ± 1/8	Thickness of jaw C ± 1/8	Span of handles in closed position D ± 3/16	Jaw opening minimum	Weight maximum
	Minimum	Maximum					
Inches	Inches	Inches	Inch	Inch	Inches	Inch	Ounces
5-1/2	5-3/8	5-5/8	11/16	5/8	2-1/16	3/32	18
7	6-7/8	7-1/8	13/16	13/16	2-1/16	3/32	20

Page 6, figure 4 - Delete the arrow heads and lines on the "B" dimension and substitute arrow heads and lines showing the "B" dimension from the end of the nippers to the centerline of the rivet.

FSC 5110, 5120

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

Pages 11 thru 15, paragraphs 4 thru 4.3.2 and 4.5 - Delete and substitute:

"4 SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance.- Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL-STD-105, except where otherwise indicated herein.

4.2.1 Inspection of materials and components.- In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2.2 Inspection of the end item.- Inspection of the nippers or pincers shall be performed as specified in the following paragraphs. A lot shall consist of nippers or pincers of the same type, class or style. The sample unit shall be one completely fabricated and assembled nipper or pincer.

4.2.2.1 Visual examination.- Each sample unit shall be visually examined for the defects set forth below. The inspection level shall be level II, with an acceptable quality level (AQL) of 4.0 defects, expressed in terms of defects per hundred units.

Examine	Defect
Finish	Not finished as specified.
	Area of no film where required.
	Scratches, peeling or blistering.
	Sags, runs, or wrinkles.
	Dirt, grit or foreign material imbedded in finish.
	Cracks or other defects.
	Evidence of rust or scale.
Design	Characteristics not in accordance with specified requirements.
Construction and Workmanship	Operation omitted or not properly performed.
	Stop screw missing (when applicable).
	Cutters not removable (when applicable).
	Jaws not adjustable (when applicable).
	Component missing or improperly assembled.
	Compressing spring missing (when applicable).
	Ends of handles touch when jaws are in closed position.
	Handles bind or excessively loose when opened or closed.
Marking	Missing, incorrect, not legible.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

4.2.2.2 Dimensional examination.- Each sample unit shall be examined for dimensions specified in applicable paragraphs and tables. Any nonconformance to requirements shall constitute a defect. The inspection level shall be level II, with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.2.2.3 Testing.- Each sample unit shall be tested as specified in paragraphs 4.4.2 thru 4.4.4.2.2 as applicable. Any determination not within specified requirements shall constitute a defect. The inspection level shall be level II, with an AQL level of 2.5 defects, expressed in terms of defects per hundred units. For the hardness test a lot shall consist of parts heat treated as a batch or under the same process and temperature control. Testing may be performed prior to finish. The inspection level shall be level II, with an AQL level of 1.5 defects, expressed in terms of defects per hundred units.

4.3 Inspection of preparation for delivery.- Unless otherwise specified, inspection to determine compliance with requirements for preparation for delivery shall be performed in accordance with Specification MIL-H-15424."

Page 11, paragraph 4.4.1 - Add the following as the first sentence: "The hardness test shall be in accordance with the applicable requirements of Method 243.1 of Federal Test Method Standard No. 151 and the values thus obtained shall comply with the requirements of 3.6.2."

Page 15, paragraphs 5.1.1, 5.2.1 and 5.2.2 - Delete "MIL-P-15424" and substitute "MIL-H-15424."

Page 15, paragraph 5.2.3 - In the first sentence, between the words "at" and "destination", insert "lowest transportation cost to".

Page 15, paragraph 6.1 - Add the following subparagraph:

"(g) If type II, class 2, carpenters' pincers require a screwdriver end on one handle and a nail-extracting notch on the end of the other handle, so state (see 3.10.2)."

Page 16 - Insert paragraph 6.4 as follows:

"6.4 Transportation description.- Transportation descriptions and minimum weights applicable to this commodity are:

Rail:
Nippers and pincers. Carload minimum weight 30,000 pounds.

Motor:
Nippers and pincers. Truckload minimum weight (W) 30.2 (W), subject to Rule 115, National Motor Freight Classification".

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.