GGG-P-00340a (GSA-FSS)
October 18, 1967
SUPERSEDING
Int. Fed. Spec. GGG-P-00340 (GSA-FSS)
April 27, 1964

INTERIM FEDERAL SPECIFICATION

PIN STRAIGHTENER, ELECTRON TUBE

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D.C., 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers the requirements for one type of pin straightener used for straightening pins on 7-pin and 9-pin miniature electron tubes.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Ft.Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-H-15424 - Hand Tools, Packaging of.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The metal inserts used for straightening the pins shall be made either of corrosion resisting steel or steel plated to resist corrosion. The base shall be made either of metal or plastic.

3.2 Identification marking. Each pin straightener shall be stamped or otherwise permanently marked in a plain and permanent manner with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

3.3 Design and construction. The electron tube pin straightener shall have two metal inserts; one insert shall straighten pins on 9-pin miniature tubes and the other insert shall straighten pins on 7-pin miniature tubes. The tool shall consist essentially of two metal inserts and a base with fasteners.

3.3.1 Metal inserts. One metal insert shall have eight equally spaced holes suitable for straightening pins on 7-pin miniature tubes and the other insert shall have ten equally spaced holes suitable for straightening pins on 9-pin miniature tubes. The holes shall be equally spaced on a 0.375 (± 0.002) inch diameter pin circle for the 7-pin straightening insert; and on a 0.468 (± 0.002) inch diameter pin circle for the 9-inch straightening insert. The chordal dimensions between holes for the 7-pin straightening insert shall be 0.1435 (± 0.005) inch and for the 9-inch straightening insert 0.1446 (± 0.005 inch. (The tolerance on chordal distances are not cumulative.) Each hole shall be 0.0445 (± 0.0025) inch in diameter. The top of each hole shall be countersunk to a top diameter of not less than 0.109 nor more than 0.130 inch and to a depth of not less than 0.070 nor more than 0.160 inch. The thickness of each pin straightening insert shall be not less than 1/4 inch and the pin straightening holes shall extend through the inserts.

3.3.2 Base. The base or other components of the tool shall provide a firm mounting for the pin straightening inserts, and suitable guides shall be provided for guiding the 7 and 9-pin tubes into the holes. The base shall be provided with two holes not less than 9/64 nor more than 3/16 inch in diameter suitable for mounting the tool on a work bench or tube tester. Two brass machine screws No. 6-32 by 2 inches long shall be furnished with each pin straightener. Two brass nuts No. 6-32 shall be furnished with each pin straightener. The fasteners shall be designed, or incorporate means, to prevent easy loosening of the nut from the screw.

3.4 Workmanship. Workmanship shall be first class in every respect.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

4.1.1 Inspection of materials and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2 Sampling procedures. Sampling procedures shall be in accordance with MIL-STD-105. Data for sampling shall be as stated in table I.

4.3 Examination.

4.3.1 Visual examination. Each sample shall be examined for any nonconformance in design, material, coating, workmanship, and marking. Defects are listed in table II.

4.3.2 Dimensional examination. Each sample unit shall be examined for any nonconformance with dimensional requirements.

4.4 Inspection of preparation for delivery. An examination shall be made to determine that requirements of section 5 are complied with. Defects are listed in table III.

TABLE I. Sampling data

Category	Sample unit	Inspection level	Acceptable quality level	AQL expressed in terms of	Reference
Visual examination	1	II	2.5 Major 4.0 Minor	Defects per 100 units	4.3.1
Dimensional examination	1	II	2.5	Defects per 100 units	4.3.2
Preparation for delivery examination	One container	S-2	4.0	Defects per 100 units	4.4

TABLE II. Visual examination defects list

Examine	Defect	Major	Minor
Design	Not as specified (see 3.3 to 3.3.2)	x	
Material	Not as specified (see 3.1)	x	
Coating	When applicable, not as specified (see 3.1)	x	
Workmanship	Not as specified (see 3.4)		x
Marking	Not as specified (see 3.2)		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of preparation for delivery, defects list

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible; or improper size, location, sequence, or method of application.
Materials	Nonconforming, missing or damaged.
Content	Not as specified.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping or tape banding, bulging or distortion of containers.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Unless otherwise specified (see 6.1), the pin straighteners shall be preserved, packaged, and packed in accordance with MIL-H-15424. The level of packaging shall be A or C and the level of packing A, B, or C as specified (see 6.1).

5.1.1 As part of the requirements of section 5 of this specification, the following is considered as part of table I of MIL-H-15424:

Column 1	Column 2	Column 3	Column 4	Column 5	Column 6	Column 7
Pin straightener	None	III	10	------	24	240

5.2 Marking.

5.2.1 Military agencies. In addition to any special marking required by the contract or order, or herein, interior and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.2.2 Civil agencies. In addition to any special marking specified in the contract or order (see 6.1), each unit and intermediate package and shipping container shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of packaging and packing required (see 5.1).
(c) State additional marking requirements, if required (see 5.2).

GSA DC 68-6889

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.