GGG-P-323c
February 26, 1968
SUPERSEDING
Fed. Spec. GGG-P-323b
September 5, 1962

FEDERAL SPECIFICATION

PICK, ICE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers one type of ice pick.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-397	-	Plastic Molding Material, Cellulose Acetate.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Box, Fiberboard.
PPP-B-676	-	Boxes, Setup.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 151 - Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards, and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample ice pick shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.2 Standard product. The ice pick delivered under this specification shall be the manufacturer's standard product, except for any design modifications and additional requirements specified herein.

3.3 Materials. Materials specified shall conform to the applicable specification and requirements specified herein.

3.4 Construction. The ice pick shall be constructed as specified herein and shall consist of a blade fixed in a handle.

3.4.1 Blade. The blade shall be formed from carbon steel. The blade shall be not less than 0.135-inch diameter at the handle tapered to a point for chipping ice. The blade shall be 5-1/2 inches, plus or minus 1/4 inch long and shall extend 4-1/2 inches, plus or minus 1/4 inch, from the handle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

The blade shall be inserted a minimum of one inch into the handle. The blade shall have a Rockwell C hardness between 50 and 60 when tested as specified in 4.4.1. The blade shall be securely fitted in the handle and shall not become detached when tested as specified in 4.4.2.

3.4.2 Handle. The handle shall be fabricated from any clear, straight-grained, seasoned hardwood such as maple, ash, hickory, beech or birch or other equally suitable species free from defects or fabricated from a plasticized cellulose acetate compound suitable for molding and extrusion conforming to type I, class 3 of L-P-397. The handle shall be not less than 3 inches in length. The handle shall be round or square and may be provided with flutes for gripping. Circular handles shall be not less than 1-1/8 inches in diameter and square handle shall be not less than 7/8 inch across flats with beveled edges. The handle shall have a hole through the axis to receive the tang of the blade. The end of the handle receiving the blade tang shall be fitted with a steel ferrule. The free end of the handle may be with or without a cap. When a cap is used, it shall be steel or plastic securely fastened to the handle and shall be dome shaped or flat with round edges.

3.5 Finish. The wood handle shall be sanded smooth and shall have a natural finish. The natural finish handle shall be given a coating of shellac or varnish to prevent moisture from entering the wood. The blade shall have a natural metal finish. Steel ferrules shall be nickel plated or have a chemically produced oxide finish to prevent corrosion.

3.6 Identification marking. Each ice pick shall be marked with the manufacturer's name or trademark, of such known character easily identifiable with said manufacturer, applied in accordance with MIL-STD-130.

3.7 Workmanship. The finished ice pick shall be clean and free from sharp edges except the point.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required, it shall be examined for defects listed in table I and dimensions specified, and tested as specified in 4.4.1 and 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:38Z
Check the source to verify that this is the current version before use.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The lot shall consist of all ice picks offered for inspection at one time. The sample unit shall be one completely fabricated ice pick.

4.3.2.1 Visual examination. Examination shall be made of the ice pick for defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of visual defects

Examine	Defect	Classification	
		Major	Minor
Finish	Wood handle not varnished, tacky.	X	
	Blade not natural steel finish.	X	
	Rough or sharp edges, burrs, or slivers, except point.	X	
	Ferrule not nickel finish.	X	
Construction and workmanship	Handle not straight grained wood, when applicable.		X
	Handle not secured to tang.	X	
	Handle without ferrule.	X	
	Ferrule loose on handle.		X
	Handle split or cracked	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (con.)

Examine	Defect	Classification	
		Major	Minor
Construction and workmanship (con.)	Tang loose in handle.	X	
	Handle not correctly shaped.		X
	Taper to point not even.		X
	Cap loose (when provided)		X
	Hole for tang in handle not centered.		X
Marking for identification	Missing, incomplete, illegible.		X

4.3.2.2 Dimensional examination. Examination shall be of the completed ice pick to determine compliance with dimensional requirements. Any dimension not within the specified requirement shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item. The end item shall be tested as specified in 4.4.1 and 4.4.2. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be scored as specified in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot shall consist of the number of containers offered for delivery at one time. The inspection level shall be S-2 and AQL shall be 4.0 defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:38Z
Check the source to verify that this is the currentversion before use.

TABLE II. Examination of preparation for delivery

Examine	Defect
Marking, exterior and interior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Material	Component missing, damaged, or otherwise defective
Contents	Number per container more or less than specified

4.3.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.4 Tests.

4.4.1 Hardness test. The steel blade shall be tested for hardness using the procedure outlined in method 243 of Fed. Test Method Std. No. 151 at a distance of 2 to 3 inches from the point of the blade to determine compliance with 3.4.1.

4.4.2 Pull test. The handle shall be gripped in a vise or a clamping device and a pull of 25 pounds shall be applied to the blade along its axis in a direction away from the handle to determine compliance with the handle security requirements of 3.4.1.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. Six picks shall be unit packaged in the following manner; The blade of each pick shall be inserted, full depth, into the void of the flute of a corrugated fiberboard B flute pad with the handles adjacent to each other. The fiberboard pad shall extend a minimum of 1/2 inch beyond the point of the blade and the first and sixth blades shall be inserted three convolutions from the edge of the pad. Alternatively, each pick blade shall be provided with a tight-fitting paperboard tube. The

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:38Z
Check the source to verify that this is the currenversion before use.

minimum thickness of the paperboard shall be 0.017 inch and the tube shall extend a minimum of 1/2 inch beyond the point of the blade.

5.1.1.2 Intermediate packaging. Twelve ice picks, unit packaged as specified in 5.1.1, shall be packed in a snug-fitting folding or setup paperboard box conforming to variety 1, style IV, type A or B, class a of PPP-B-566 or type I, variety 1, class A, style 4 of PPP-B-676, respectively. The picks shall be arranged in two layers with the handle in one layer adjacent to the blades in the other layer. Box closure shall be in accordance with the appendix of the applicable box specification.

5.1.2 Level C. The ice picks shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. One hundred and forty-four ice picks, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Closure, waterproofing by means of tape, and reinforcing with flat strapping or tape banding shall be in accordance with the appendix of PPP-B-636.

5.2.2 Level B. One hundred and forty-four ice picks, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the shipping container shall be V3c or V3s, fabricated and closed in accordance with PPP-B-636. The shipping container material may also be V4s of PPP-F-320.

5.2.3 Level C. Ice picks, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior pages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The ice pick covered by this specification is intended for use in troop feeding facilities, hospital kitchens, and galleys.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) When preproduction sample is required (see 3.1).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(d) When V3c or V3s fiberboard shipping containers are required for level B packing (see 5.2.2).

6.3 Level B civil agency packaging. When level B packaging is specified by civil agency procurement, the requirements of 5.1.1 level A packaging shall apply.

MILITARY CUSTODIANS:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - SA
Air Force - 84

User activities:

Navy - MC, CG

Preparing activity:

Army - GL

CIVIL AGENCIES INTEREST:

GSA
VA

☆U. S. GOVERNMENT PRINTING OFFICE: 1968 O - 302-512 (7150)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:38Z
Check the source to verify that this is the current version before use.

"to detach this form, cut along this line"

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

Pick, Ice - GGG-P-323c

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.