GGG-S-285b
AMENDMENT—2
December 31, 1964

SUPERSEDING
Int. Amendment-1
July 27, 1964

FEDERAL SPECIFICATION

SHEARS; PRUNING, HAND, (TWO-HAND OPERATED, LOPPING)

This amendment, which forms a part of Federal Specification GGG-S-285b dated May 22, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 2, paragraph 3.1.2, at end of paragraph: Add new sentence:

"There shall be no chipping or cracking of the blade when subjected to the toughness test specified in 4.4.4."

Page 7, after paragraph 4.4.3: Add new paragraph:

4.4.4 *Toughness of blades.* The toughness of blades shall be determined for compliance with the requirements of 3.1.2. The shears shall be disassembled and the blade secured to a suitable support, such as a vise, with the cutting edge up. One end of a rod, 24 inches long and one inch in diameter, shall be supported on a rest at approximately the same level as the cutting edge of the shear blade. The other end of the rod shall be elevated to a height of six inches above the cutting edge and released. The rod shall strike the cutting edge at a distance of two inches from the elevated end and at right angles to the plane of the blade. The rod shall be of No. 1020 steel.

DOD coordination has been waived.

FSC 3750

☆ U.S. GOVERNMENT PRINTING OFFICE: 1964— 783382/293

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:38Z
Check the source to verify that this is the current version before use.