GGG-T-330b
August 17, 1967
SUPERSEDING
Fed. Spec. GGG-T-330a
May 22, 1957

FEDERAL SPECIFICATION

THREADING SET, SCREW

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers sets of thread cutting tools (taps and dies) and the required accessory items (diestock or diestocks), tap wrench(es), set container, drills and gages. The screw-threading sets covered by this specification are also identified commercially as "screw plates".

1.1.1 Federal specification coverage. Federal specifications do not include all types of the commodity indicated by the titles of the specifications, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types. Threading sets furnished under this specification shall be of the following types, as specified (see 6.2):

Type I - Threading sets, screw with taper, plug and bottoming taps for each size included.
Type II - Threading set, navigation.
Type III - Threading sets, screw with one tap only for each size included.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

GG-G-86 - Gage; Sheet and Plate, Twist Drill, Drill Rod, and Wire.
GGG-D-296 - Die, Threadcutting and Rethreading; Collet, Threading Die; and Diestock (Bolt and Screw Threading; Unified, American National and Metric Form Threads).
GGG-D-751 - Drills, Twist (Taper-Square, Straight, and Taper-Round Shanks).
GGG-G-17 - Gages, General Purpose.
GGG-S-121 - Screwdriver and Screw Starter, Hand.
GGG-T-60 - Taps, Thread Cutting, Carbon Steel, Hand, Cut Thread, American National and Metric Thread Form, Screw and Bolt.
GGG-T-70 - Tap, Thread Cutting, (Standard, American National Form and Metric Spark Plug Thread, High-Speed Steel, Ground Thread, Hand).
GGG-W-680 - Wrenches, Tap and Reamer, Adjustable.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Ft. Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-H-15424 - Hand Tools; Packaging of.

Military Standard:

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Component items. Component items of the threading sets shall conform to the following requirements specified herein:

3.1.1 Dies. Unless otherwise specified (see 6.2), dies shall be right-hand, and shall conform to GGG-D-296.

3.1.2 Diestocks. The diestocks shall conform to GGG-D-296.

3.1.3 Drills. The drills shall conform to GGG-D-751.

3.1.4 Screw pitch gage. The screw pitch gage (see type II navigation threading set) shall conform to type V, class 1, style E of GGG-G-17.

3.1.5 Twist drill and drill rod gage. The twist drill and drill rod gage shall conform to type II, class 2 of GG-G-86.

3.1.6 Taps. Unless otherwise specified (see 6.2), all taps shall be high speed steel, ground thread, right hand cutting and shall conform to GGG-T-70. When carbon steel taps are specified (see 6.2), they shall conform to GGG-T-60. Metric taps shall be in accordance with GGG-T-60.

3.1.7 Wrenches, tap, and reamer. Tap and reamer wrenches shall conform to GGG-W-680.

3.1.8 Screwdrivers. The screwdrivers specified herein shall conform to GGG-S-121.

3.2 Cases. Each set shall be furnished in a metal or wooden case, and so arranged that the components cannot come in contact with each other, thus preventing any damage to the cutting edges and allowing for easy selection. If cases with trays or inserts are required, they shall be as specified (see 6.2). Wooden cases shall be of well-seasoned hardwood. The cases shall have a suitable protective, moisture-resistant coating of paint, or other suitable coating on both the interior and exterior surfaces.

3.3 Type I sets. Type I sets shall be furnished in the following set numbers 0 through 9, as specified (see 6.2).

3.3.1 Set No. 0. Set No. 0 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Coarse Thread Series sizes shown in table I.

(b) One 13/16-inch outside-diameter round split die for each of the National Coarse Thread series sizes shown in table I.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.

(c) One straight-shank drill for each of the drill sizes shown in table I.

(d) One diestock for 13/16-inch outside diameter dies.

(e) One tap wrench for 0-1/4-inch tap capacity, with T-handle.

(f) Case.

TABLE I. Taps, dies and drills for type I, set No. 0

Taps and dies National Coarse Thread series		Drills	
Size No.	Threads per inch	Size No.	Decimal equivalent
3 1/	48	47	0.0785
5	40	38	.1015
8	32	29	.1360
10	24	25	.1495
12	24	16	.1770

1/ Dies not standard in "HSS".

3.3.2 Set No. 1. Set No. 1 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Coarse Thread series sizes shown in table II.

(b) One round split die for each of the National Coarse Thread series sizes and outside diameters as shown in table II.

(c) One drill for each of the drill sizes and shank size as shown in table II.

(d) One diestock for 1-1/2-inch outside diameter dies.

(e) One diestock for 2-1/2-inch outside diameter dies.

(f) One tap wrench for 1/4- to 1/2-inch tap capacity, with T-handle.

(g) One tap wrench for 1/2- to 1-inch tap capacity, with straight handle.

(h) Case.

TABLE II. Taps, dies and drills for type I, set No. 1

Taps and dies National Coarse Thread series		Dies	Drills		
Size	Threads per inch	O.D.	Size	Decimal equivalent	Shank
Inch		Inches		Inch	
1/4	20	1-1/2	No. 7	0.2010	Straight
5/16	18	1-1/2	No. "F"	.2570	Straight
3/8	16	1-1/2	5/16 inch	.3125	Straight
7/16	14	1-1/2	No. U.	.3680	Straight
1/2	13	1-1/2	27/64 inch	.4219	Straight
9/16	12	2-1/2	31/64 inch	.4843	Straight
5/8 1/	11	2-1/2	17/32 inch	.5312	ASA (Morse) Taper ASA
3/4 1/	10	2-1/2	21/32 inch	.6562	(Morse) taper ASA
7/8 1/	9	2-1/2	49/64 inch	.7656	(Morse) taper ASA
1	8	2-1/2	7/8 inch	.8750	(Morse) taper ASA

1/ Dies not standard in "HSS".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

3.3.3 Set No. 2. Set No. 2 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Coarse Thread series sizes shown in table III.

(b) One round split die 3-inch outside diameter, for each of the National Coarse Thread series sizes shown in table III.

(c) One Morse taper-shank drill for each of the drill sizes as shown in table III.

(d) One diestock for 3-inch outside diameter dies.

(e) One tap wrench for 1- to 2-1/2-inch tap capacity, with straight handle.

(f) Case.

TABLE III. Taps, dies and drills for type I, set No. 2

Taps and dies National Coarse Thread series		Drills	
Size Inches	Threads per inch	Size Inches	Decimal equivalent Inches
1-1/8 1/	7	63/64	0.9844
1-1/4 1/	7	1-7/64	1.1094
1-1/2 1/	6	1-11/32	1.3438

1/ Dies not standard in "HSS".

3.3.4 Set No. 3. Set No. 3 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Fine Thread series sizes shown in table IV.

(b) One round split die, 1-1/2 inch outside diameter for each of the National Fine Thread series sizes shown in table IV.

(c) One straight-shank drill for each of the drill sizes shown in table IV.

(d) One diestock for 1-1/2-inch outside diameter dies.

(e) One tap wrench for 1/4- to 1/2-inch tap capacity, with T-handle.

(f) Case.

TABLE IV. Taps dies and drills for type I, set No. 3

Taps and dies National Fine Thread series		Drills	
Size No. Inch	Threads per inch	Size No.	Decimal equivalent Inch
1/4	28	3	0.2130
5/16	24	I	.2720
3/8	24	Q	.3320
7/16	20	25/64 inch	.3906
1/2	20	29/64 inch	.4531

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:39Z
Check the source to verify that this is the current version before use.

3.3.5 Set No. 4. Set No. 4 shall include the following:

(a) One taper, one plug and one bottoming tap for each of the National Coarse Thread series shown in table V.

(b) One round split die for each of the National Coarse Thread series sizes and outside diameters as shown in table V.

(c) One taper, one plug and one bottoming tap for National Special Thread series size 11/16 inch, 11 threads per inch, as shown in table V.

1/(d) One 2-1/2-inch outside diameter round split die for National Special Thread series size 11/16 inch, 11 threads per inch, as shown in table V.

(e) Diestocks and tap wrenches shall be furnished when specified (see 6.2).

(f) Case.

1/ Dies not standard in 2-1/2 inch outside diameter.

TABLE V. Taps and dies for type I, set No. 4

Taps and dies National Coarse Thread series		Dies, outside diameter
Size	Threads per inch	
		Inches
No. 1 1/	64	13/16
No. 2 1/	56	13/16
No. 3 1/	48	13/16
No. 4 1/	40	13/16
No. 5	40	13/16
No. 6	32	13/16
No. 8	32	13/16
No. 10	24	13/16
No. 12	24	13/16
1/4 inch	20	1-1/2
5/16 inch	18	1-1/2
3/8 inch	16	1-1/2
7/16 inch	14	1-1/2
1/2 inch	13	1-1/2
9/16 inch	12	1-1/2
5/8 inch 1/	11	2-1/2
11/16 inch 2/	11	2-1/2
3/4 inch 1/	10	2-1/2
7/8 inch 1/	9	2-1/2
1 inch 1/	8	2-1/2

1/ Dies not standard in "HSS".
2/ National Special Thread Series.

3.3.6 Set No. 5. Set No. 5 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Coarse Thread series sizes shown in table VI.

(b) One round split die for each of the National Coarse Thread series with outside diameters as shown in table VI.

(c) One diestock for 1-1/2-inch outside diameter die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

(d) One diestock for 2-1/2 inch outside diameter die.

(e) One tap wrench for 1/4- to 1-1/8 inch tap capacity, with straight handle.

(f) One tap wrench for 1/4 to 1/2 inch tap capacity, with T-handle.

(g) Case.

TABLE VI. Taps and dies for type I, set No. 5

Taps and dies National Coarse Thread series		Dies, outside diameter
Size	Threads per inch	
Inch		Inches
1/4	20	1-1/2
5/16	18	1-1/2
3/8	16	1-1/2
7/16	14	1-1/2
1/2	13	1-1/2
9/16 1/	12	1-1/2
5/8 1/	11	2-1/2
3/4 1/	10	2-1/2
7/8 1/	9	2-1/2
1	8	2-1/2

1/ Dies not standard in "HSS".

3.3.7 Set No. 6. Set No. 6 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Fine Thread series shown in table VII.

(b) One round split die for each of the National Fine Thread series sizes with outside diameters as shown in table VII.

(c) One taper, one plug and one bottoming tap for National Special Thread series size 11/16 inch, 16 threads per inch, as shown in table VII.

1/ (d) One round split die 2-1/2 inches in outside diameter for National Special Thread series size 11/16 inch, 16 threads per inch, as shown in table VII.

(e) Diestocks and tap wrenches shall be furnished when specified (see 6.2).

(f) Case.

1/ Dies not standard in 2-1/2 inch outside diameter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE VII. Taps and dies for type I, set No. 6

Taps and dies National Fine Thread series		Dies, outside diameter
Size	Threads per inch	
		Inches
No. 0 1/	80	13/16
No. 1 1/	72	13/16
No. 2 1/	64	13/16
No. 3 1/	56	13/16
No. 4 1/	48	13/16
No. 5	44	13/16
No. 6	40	13/16
No. 8	36	13/16
No. 10	32	13/16
No. 12	28	13/16
1/4 inch	28	1-1/2
5/16 inch	24	1-1/2
3/8 inch	24	1-1/2
7/16 inch	20	1-1/2
1/2 inch	20	1-1/2
9/16 inch	18	1-1/2
5/8 inch 2/	18	2-1/2
11/16 inch 1/	16	2-1/2
3/4 inch 1/	16	2-1/2
7/8 inch 1/	14	2-1/2
1 inch 1/	14 2/	2-1/2

1/ Dies not standard in "HSS".
2/ National Special Thread series.

3.3.8 Set No. 7. Set No. 7 shall include the following:

(a) One taper, one plug and one bottoming tap for each of the National Coarse and National Fine Thread Series sizes shown in table VIII.

(b) One adjustable round split die 1-1/2-inch outside diameter for each National Fine Thread series sizes shown in table VIII.

(c) One diestock for 1-1/2-inch outside diameter dies.

(d) One tap wrench for 1/4- to 1/2-inch tap capacity, with T-handle.

(e) Case.

TABLE VIII. Taps and dies for type I, set No. 7

Taps and dies National Coarse Thread series		Taps and dies National Fine Thread series	
Size	Threads per inch	Size	Threads per inch
Inch		Inch	
1/4	20	1/4	28
5/16	18	5/16	24
3/8	16	3/8	24
7/16	14	7/16	20
1/2	13	1/2	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

3.3.9 Set No. 8. Set No. 8 shall include the following:

(a) One taper, one plug, and one bottoming tap for each of the National Coarse and National Fine Thread series sizes shown in table IX.

(b) One adjustable round split die 2-1/2-inch outside diameter for each of the National Coarse and National Fine thread series sizes shown in table IX.

(c) One diestock for 2-1/2-inch outside diameter dies.

(d) One tap wrench for 1/2 to 1-inch tap capacity, with straight handle.

(e) Case.

TABLE IX. Taps and dies for type I, set No. 8

Taps and dies National Coarse Thread series		Taps and dies National Fine Thread series	
Size	Threads per inch	Size	Threads per inch
Inch		Inch	
9/16	12	9/16	18
5/8 1/	11	5/8	18
3/4 1/	10	3/4	16
7/8 1/	9	7/8	14
1 1/	8	1	14 2/

1/ Dies not standard in "HSS".
2/ National Special Thread series.

3.3.10 Set No. 9 (metric). Set No. 9 (metric) shall include the following:

1/ (a) One taper, one plug, and one bottoming tap for each of the Metric Screw Thread series sizes shown in table X.

1/ (b) One round split die, 20.6 mm. (13/16 inch) in outside diameter, for each of the Metric Screw Thread sizes shown in table X.

(c) Diestocks and tap wrenches shall be furnished when specified (see 6.2).

(d) Case.

1/ Metric taps and dies are special.

TABLE X. Taps and dies for type I, set No. 9

1/ Taps and dies Metric Screw Thread series	
Nominal size	Pitch
MM.	MM.
1.5	0.35
2	.45
2.5	.45
3	.60
3.5	.60
4	.75
4.5	.75
5	.90
5.5	.90
6	1.0

1/ Metric taps and dies are special.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:39Z
Check the source to verify that this is the current version before use.

3.4.1 Navigation threading set (screw) shall include the following:

(a) Two taper, two plug and two bottoming taps for each of the National Coarse Thread series sizes shown in table XI.

(b) One round adjustable split die 13/16 inch in outside diameter for each of the National Coarse Thread series sizes shown in table XI.

(c) Two drills in each size shown in table XI.

(d) One diestock for 13/16-inch outside diameter die.

(e) One tap wrench 0- to 1/4- inch hand tap, T-handle.

(f) One twist drill and drill rod gage.

(g) One screw pitch gage for gaging threads from 9 to 40 threads per inch. The gage shall contain among others the 24, 32, and 40 pitch sizes.

(h) Case.

TABLE XI. Taps, dies and drills for type II, navigation threading set

Taps and dies National Coarse Thread series		Drills			
Size No.	Threads per inch	Size No.	Decimal equivalent	Size	Decimal equivalent
4 1/	40	43	0.0890	No. 27	0.1440
6	32	36	.1065	No. 17	.1730
8	32	29	.1360	No. 9	.1960
10	24	25	.1495	No. 1	.2280
12	24	16	.1770	1/4 inch	.250

1/ Dies not standard in "HSS".

3.5 Type III, threading set (screw). Type III sets shall be furnished in the following set numbers 1 through 12, as specified (see 6.2).

3.5.1 Set No. 1. Set No. 1 shall include the following:

(a) One plug tap for each of the National Coarse Thread series sizes shown in table XII.

(b) One round split die, 1-1/2 inches in outside diameter, for each of the National Coarse Thread series sizes shown in table XII.

(c) One diestock for 1-1/2 inch outside diameter die.

(d) One tap wrench for 1/4- to 1/2-inch tap capacity, with T-handle.

(e) Case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE XII. Taps and dies for type III, set No. 1

Taps and dies National Coarse Thread series	
Size	Threads per inch
Inch	
1/4	20
5/16	18
3/8	16
7/16	14
1/2	13

3.5.2 Set No. 2. Set No. 2 shall include the following:

(a) One plug tap for each of the National Fine Thread series sizes shown in table XIII.

(b) One round split die, 1-1/2 inches in outside diameter, for each of the National Fine Thread series sizes shown in table XIII.

(c) One diestock for 1-1/2-inch outside diameter dies.

(d) One tap wrench for 1/4- to 1/2-inch tap capacity, with T-handle.

(e) Case.

TABLE XIII. Taps and dies for type III, set No. 2

Taps and dies National Fine Thread series	
Size	Threads per inch
Inch	
1/4	28
5/16	24
3/8	24
7/16	20
1/2	20

3.5.3 Set No. 3. Set No. 3 shall include the following:

(a) One plug tap for each of the National Coarse Thread series sizes shown in table XIV.

(b) One round split die, 2-1/2 inches in outside diameter for each of the National Coarse Thread series sizes shown in table XIV.

(c) One diestock for 2-1/2-inch outside diameter dies.

(d) One tap wrench for 1/4- to 1-inch tap capacity, with straight handle.

(e) Case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE XIV. Taps and dies for type III, set No. 3

Taps and dies National Coarse Thread Series	
Size	Threads per inch
Inch	
1/2 1/	13
5/8 1/	11
3/4 1/	10
7/8 1/	9
1 1/	8

1/ Dies not standard in "HSS".

3.5.4 Set No. 4. Set No. 4 shall include the following:

(a) One plug tap for each of the National Fine Thread series sizes shown in table XV.

(b) One round split die, 2-1/2 inches in outside diameter for each of the National Fine Thread series sizes shown in table XV.

(c) One diestock for 2-1/2-inch outside diameter threading die.

(d) One tap wrench for 1/4- to 1-inch tap capacity, with straight handle.

(e) Case.

TABLE XV. Taps and dies for type III, set No. 4

Taps and dies National Fine Thread series	
Size	Threads per inch
Inch	
1/2 1/	20
5/8 1/	18
3/4 1/	16
7/8 1/	14
1	14 2/

1/ Dies not standard in "HSS".
2/ National Special Thread series.

3.5.5 Set No. 5. Set No. 5 shall include the following:

(a) One plug tap for each of the National Coarse Thread Series sizes shown in table XVI.

(b) One round split die for each of the National Coarse Thread sizes shown in table XVI. The outside diameter of the dies shall be as shown in table XVI.

(c) One diestock for the 1-1/2-inch outside diameter dies.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the currentversion before use.

(d) One diestock for the 2-1/2-inch outside diameter dies.

(e) One tap wrench for 3/16- to 5/8-inch tap capacity, with T-handle.

(f) One tap wrench for 1/4 to 1-inch tap capacity, with straight handle.

(g) Case.

TABLE XVI. Taps and dies for type III, set No. 5

Taps and dies National Coarse Thread series		Dies, outside diameter
Size	Threads per inch	
Inch		Inches
1/4	20	1-1/2
5/16	18	1-1/2
3/8	16	1-1/2
7/16	14	1-1/2
1/2	13	1-1/2
9/16	12	1-1/2
5/8	11 1/	2-1/2
3/4	10 1/	2-1/2
7/8	9 1/	2-1/2
1	8 1/	2-1/2

1/ Dies not standard in "HSS".

3.5.6 Set No. 6. Set No. 6. shall include the following:

(a) One plug tap for each of the National Fine Thread series sizes shown in table XVII.

(b) One round split die for each of the National Fine Thread series sizes with outside diameters as shown in table XVII.

(c) One diestock for 1-1/2-inch outside diameter dies.

(d) One diestock for 2-1/2-inch outside diameter dies.

(e) One tap wrench for 3/16- to 5/8-inch tap capacity, with T-handle.

(f) One tap wrench for 1/4- to 1-inch tap capacity, with straight handle.

(g) Case.

TABLE XVII. Taps and dies for type III, set No. 6

Taps and dies National Fine Thread series		Dies, outside diameter
Size	Threads per inch	
Inches		Inches
1/4	28	1-1/2
5/16	24	1-1/2
3/8	24	1-1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

TABLE XVII. Taps and dies for type III, set No. 6 (continued)

Taps and dies National Fine Thread series		Dies, outside diameter
Size	Threads per inch	
Inches		Inches
7/16	20	1-1/2
1/2	20	1-1/2
9/16	18	2-1/2
5/8 1/	18	2-1/2
3/4 1/	16	2-1/2
7/8 1/	14	2-1/2
1 1/	14 2/	2-1/2

1/ Dies not standard in "HSS".
2/ National Special Thread series.

3.5.7 Set No. 7. Set No. 7 shall include the following:

(a) One plug tap for each of the National Coarse and National Fine Thread series sizes shown in table XVIII.

(b) One round split die, 13/16 inch in outside diameter, for each of the National Coarse and National Fine Thread series sizes shown in table XVIII.

(c) One diestock for 13/16-inch outside diameter die.

(d) One tap wrench for 1/16- to 1/4-inch tap capacity, with T-handle.

(e) Case.

TABLE XVIII. Taps and dies for type III, set No. 7

Taps and dies National Coarse Thread series		Tap and dies National Fine Thread series	
Size No.	Threads per inch	Size No.	Threads per inch
6	32	10	32
8	32	---	---
10	24	---	---
12	24	---	---

3.5.8 Set No. 8. Set No. 8 shall include the following:

(a) One plug tap for each National Coarse and National Special Thread series sizes shown in table XIX.

(b) One die and collet assembly 1-1/4-inch outside diameter for each National Coarse and National Special Thread series sizes shown in table XIX.

(c) One diestock for 1-1/4-inch outside diameter collet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

(d) One tap wrench for 0- to 1/4-inch tap capacity, with T-handle.

(e) Case.

TABLE XIX. Taps and dies for type III, set No. 8

Taps and dies 1/ National Coarse Thread series		Taps and dies National Special Thread series	
Size No.	Threads per inch	Size	Thread per inch
4	40	1/16	64
6	32	3/32	48
8	32	----	--
10	24	1/8	40
12	24	5/32	36
1/4 inch	20	----	--

1/ Dies not standard in "HSS".

3.5.9 Set No. 9. Set No. 9 shall include the following:

(a) One plug tap for each National Coarse Thread series sizes shown in table XX.

(b) One adjustable round split die 13/16-inch outside diameter, for each National Coarse Thread series sizes shown in table XX.

(c) One diestock for 13/16-inch outside diameter dies.

(d) One tap wrench for 0- to 1/4-inch tap capacity, tap wrench with T-handle.

(e) Case.

TABLE XX. Taps and dies for type III, set No. 9

Taps and dies National Coarse Thread series	
Size No.	Threads per inch
1 1/	64
2 1/	56
3 1/	48
4 1/	40
5	40
6	32
8	32
10	24
12	24

1/ Dies not standard in "HSS".

3.5.10 Set No. 10. Set No. 10 shall include the following:

(a) One taper tap for each of the National Coarse Thread and National Fine Thread series sizes shown in table XXI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

(b) One adjustable round split die 13/16-inch outside diameter for each National Coarse Thread and National Fine Thread series sizes shown in table XXI.

(c) One diestock for 13/16-inch outside diameter dies.

(d) One tap wrench for 1/16- to 1/4-inch tap capacity, with straight handle.

(e) One screwdriver, straight tip, extra light duty, 3-inch-length blade, in accordance with GGG-S-121.

TABLE XXI. Taps and dies for type III, set No. 10

Taps and dies National Coarse Thread series		Taps and dies National Fine Thread series	
Size No.	Threads per inch	Size No.	Threads per inch
4 1/	40	4	48
6	32	6	40
8	32	8	36
10	24	10	32
12	24	12	28

1/ Die not standard in "HSS".

3.5.11 Set No. 11. Set No. 11 shall include the following:

(a) One plug tap for each of the National Fine Thread series sizes shown in table XXII.

(b) One adjustable round split die 13/16-inch outside diameter for each of the National Fine Thread series sizes shown in table XXII.

(c) One diestock for the 13/16-inch outside diameter dies.

(d) One tap wrench for 0- to 1/4-inch tap capacity, with T-handle.

(e) Case.

TABLE XXII. Taps and dies for type III, set No. 11

Taps and dies National Fine Thread series		
Size No.		Threads per inch
0	1/	80
1	1/	72
2	1/	64
3	1/	56
4	1/	48
5		44
6		40
8		36
10		32
12		28

1/ Dies not standard in "HSS".

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:39Z
Check the source to verify that this is the current version before use.

3.5.12 Set No. 12 (metric). Set No. 12 (metric) shall include the following:

(a) One plug tap for each of the sizes shown in table XXIII.

(b) One round split die for each of the sizes shown in table XXIII.

(c) Diestock(s) and tap wrench(es) shall be furnished when specified (see 6.2).

(d) Case.

TABLE XXIII. Taps and dies for type III, set No. 12

Taps and dies 1/			
Nominal size	Pitch	Dies outside diameter	
MM.	MM.	MM.	Inches
2	0.45	20.6	13/16
2.5	.45	20.6	13/16
3	.60	20.6	13/16
3.5	.60	20.6	13/16
4	.75	20.6	13/16
4.5	.75	20.6	13/16
5	.90	20.6	13/16
5.5	.90	20.6	13/16
6	1.00	20.6	13/16
7	1.00	38.1	1-1/2
8	1.25	38.1	1-1/2
9	1.25	38.1	1-1/2
10	1.50	38.1	1-1/2
12	1.75	38.1	1-1/2
14	2.00	38.1	1-1/2
16	2.00	50.8	2
18	2.50	50.8	2
20	2.50	50.8	2
22	2.50	50.8	2
24	3.00	50.8	2

1/ Metric taps and dies are special.

3.6 Marking.

3.6.1 Component marking. Each component item in each set shall be marked in accordance with the applicable specification.

3.6.2 Cases. The outside cover of each case for type I, set numbers 0, 1, 2, 3, and type II threading sets shall be neatly lettered with a list of items included in the set. The remaining sets shall have the item listing on the inside of the case cover. The cover of each case shall be marked in a plain and permanent manner so that the source of supply can be easily determined.

3.7 Workmanship. Workmanship of the threading sets and cases shall be of the quality prevailing among manufacturers normally producing threading sets and cases of the sizes and types listed herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for quality conformance inspection.

4.2.1 Lot. All threading sets of the same type and set number offered for delivery at one time shall be considered a lot for purposes of quality conformance inspection.

4.2.2 Sampling for examination. One threading set shall be selected from each lot and each component shall be examined to verify compliance with the applicable document shown in 2.1.

4.3 Inspection of preservation, packaging, packing, and marking for shipment and storage. Preservation, packaging, packing, and marking for shipment and storage shall be examined to determine conformance with the documents referenced in section 5 or as specified in the contract or order.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging, and packing. Preservation, packaging, and packing shall be in accordance with MIL-H-15424. Levels of preservation and packaging and level of packing shall be as specified (see 6.2).

5.2 Marking.

5.2.1 Military agencies. In addition to any markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.2.2 Civil agencies. In addition to markings required by the contract or order, the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Intended use. The thread cutting sets covered by this specification are intended to be used for the manual cutting of internal and external screw threads.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.

(b) Type and threading set number required (see 1.2, 3.3.1 through 3.3.10, 3.4.1, and 3.5.1 through 3.5.12).

(c) When left hand cutting dies and taps are required (see 3.1.1 and 3.1.6).

(d) When carbon steel taps are required (see 3.1.6).

(e) Whether cases with trays are required (see 3.2).

(f) If die stocks and tap wrenches are required (see 3.3.5, 3.3.7, 3.3.10 and 3.5.11).

(g) Level of preservation and packaging required (see 5.1).

(h) Level of packing required (see 5.1).

(i) Special marking when required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - GL
Navy - SH
Air Force - 69

Review activities:

Army - GL
Navy - SH
Air Force - 69

User activities:

Army - CE, ME
Navy - MC, YD

Preparing activity:

Navy - SH

Civil Agency Interest:

GSA-PSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price of this specification 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:39Z
Check the source to verify that this is the current version before use.