INCH-POUND

MIL-C-44476(GL)
8 November 1993

MILTARY SPECIFICATION

CONTAINER, AERIAL DELIVERY, WEAPONS AND

EQUIPMENT, ADJUSTABLE

This specification is approval for use by the Natick Research, Development, and Emgineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of a parachutist's reinforced jump container. The container is fabricated from nylon duck cloth and nylon webbing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Amy Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | - Marking for Shipment and Storage |
| MIL-STD-147 | - Palletized Unit Loads |
| MIL-STD-2073-1 | - DoD Material Procedures for Development and Application of Packaging Requirements (Part 1 of 2 Parts) |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-6866 - Container, Aerial Delivery, Weapons and Equipment, Adjustable

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-IMD, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packing

(Application for copies should be addressed to the American society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

INCH-POUND

MIL-C-44476(GL)
8 November 1993

# MILITARY SPECIFICATION

# CONTAINER, AERIAL DELIVERY, WEAPONS AND EQUIPMENT, ADJUSTABLE

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This document covers one type and size of a parachutist's reinforced jump container. The container is fabricated from nylon duck cloth and nylon webbing.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | | |
|---|---|---|
| MIL-STD-105 | - | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | - | Marking for Shipment and Storage |
| MIL-STD-147 | - | Palletized Unit Loads |
| MIL-STD-2073-1 | - | DoD Material Procedures for Development and Application of Packaging Requirements (Part 1 of 2 Parts) |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

| | | |
|---|---|---|
| 11-1-6866 | - | Container, Aerial Delivery, Weapons and Equipment, Adjustable |

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: SATNC-IMD, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

| | | |
|---|---|---|
| D 3951 | - | Standard Practice for Commercial Packing |

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other information services.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shall conform to the requirements on the applicable drawings, to subsidiary specifications and standards applicable thereto and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction shall conform in all respects to the drawings listed in Section 2 and as specified herein.

3.3.1 Type 301 stitching. Ends of all type 301 stitching shall be backstitched or overstitched not less than 1/2 inch in accordance with the required stitch pattern. Thread tension shall be maintained so that there will be no loose stitching resulting in the puckering of the material sewn. The lock shall be embedded in the materials sewn.

3.3.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during the stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box-x and W-W stitching) from the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch from the defective area, (1/2 inch for box-x and W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box-x and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

3.4 Thread ends. All thread ends shall be trimmed to a maximum length of 1/4 inch.

3.5 Repairs. Repairs such as mends, darns, patches, or splices are not permitted on the container.

3.6 Workmanship. The finished and assembled containers shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable quality levels.

4. APPLICABLE DOCUMENTS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any nonconformance shall be cause for rejection of the first article.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of containers. The sample unit shall be one container. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Fabric | Any hole (except drill holes), cut, or tear, weak places or broken yarns | 101 | |
| | Exposed drill holes | | 201 |
| Felt | Any hole, cut, or tear | | 202 |
| Webbing, tape and cord | Not firmly and tightly woven; edge frayed or scalloped | 102 | |
| | Exposed end of tie down tapes not dipped in wax as required | | 203 |
| | Exposed end of nylon webbing or tape not seared smooth as required | | 204 |
| Fastener tape, hook and pile | Any hole, cut, or tear. Hooks missing or flattened, foreign matter or dirt impairing proper function | 103 | |
| Hardware | Broken or bent; corroded areas; burrs or sharp edges | 104 | |
| | Any required component not specified type or size | 105 | |
| | Any required component not functioning, improperly set or reversed | 106 | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Slide fastener | Not functioning properly, failing to effect closure or to open freely | 107 | |
| | Not specified type or size | 108 | |
| | Slider jams or fails to interlock | 109 | |
| | Thong omitted | 110 | |
| | Damaged teeth | 111 | |
| Open seams and run-offs | 1/2 inch or less | | 205 |
| | More than 1/2 inch | 112 | |
| NOTE: | A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more skipped stitches or run-offs occur. On a double stitching seam, a seam shall be considered open when either one or both sides of the seam are open. | | |
| Binding | Improperly or loosely applied showing raw edge of fabric | 113 | |
| | End of binding not finished as specified or overlapped less than 1 inch | | 206 |
| Seam and stitch type | Wrong seam or stitch type | 114 | |
| Stitch tension | Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in excessive tightness of fabric on seams | 115 | |
| Stitches per inch | One stitch less than minimum specified | | 207 |
| | Two or more stitches less than minimum specified | 116 | |
| | One or two stitches in excess of maximum specified | | 208 |
| | More than two stitches in excess of maximum specified | 117 | |
| NOTE: | Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| NOTE: (cont'd) | the fabric in order to sew over heavy places, heavy seams or in turning corners, shall be classified as follows:<br>a. Within the major defect classification - minor defect<br>b. Within the minor defect classification - no defect | | |
| Stitching margins | Larger than specified by more than 3/16 inch for more than 2 inches | | 209 |
| Thread breaks | Not overstitched as specified | | 210 |
| NOTE: | Thread breaks not overstitched shall be classified as open seams. | | |
| Stitching ends | Ends of stitching backstitched less than 1/2 inch (except where ends are turned under in a hem or held down by other stitching) | | 211 |
| | Ends of stitching not backstitched | 118 | |
| Stitching | Any required row of stitching omitted (except on WW stitching) | 119 | |
| | WW stitching:<br>One or more rows of stitching omitted | 120 | |
| | Length of stitching less than specified by more than 1/4 inch | 121 | |
| Components and assembly | Any component or required operation omitted or not as specified (unless otherwise classified herein) | 122 | |
| | Needle chews | 123 | |
| | Mends, darns, or patches | 124 | |
| | Any turn under on stitched ends of webbing not securely caught in WW stitching | 125 | |
| | Turn under on ends of straps, chapes, and loops less than specified by more than 1/8 inch | | 212 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

| Examine | Defect | Classification Major | Minor |
|---|---|---|---|
| Marking and identification | Omitted, incorrect, illegible, misplaced, or size characters not as specified | | 213 |
| Cleanness | Noticeable spots or stains, i.e., grease, oil, ink, dirt not removed; thread ends not trimmed to 1/4 inch or less | | 214 |

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of containers. The sample unit shall be one container. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

| Examine | Defect |
|---|---|
| Marking (exterior and interior) | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |
| Materials | Any component missing, damaged, or not as specified |
| Workmanship | Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling<br>Bulged or distorted container |
| Content | Number per container is more or less than required |

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

| Examine | Defect |
|---|---|
| Finished dimensions | Length, width, or height exceeds specified maximum requirement |
| Palletization | Pallet pattern not as specified<br>Load not bonded as specified |
| Weight | Exceeds maximum load limits |
| Marking | Omitted; incorrect; illegible; of improper size, location, sequence, or method of application |

5. PACKAGING

5.1 Preservation and packing. Levels of preservation and packing shall be in accordance with the procurement order/contract, or in accordance with MIL-STD-2073-1 and ASTM D 3951 (see 6.2).

5.2 Palletization. When specified (see 6.2), palletization shall be in accordance with the procurement order/contract, or MIL-STD-147.

5.3 Marking. Marking shall be in accordance with the procurement order/contract, or MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The jump container is intended to allow the individual parachutist to carry an assortment of weapons, during a parachute descent.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issues of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1).
e. When palletization is required (see 5.2).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-3. The first article should be a preproduction sample. The contracting officer should specify the appropriate



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Air delivery
Carrier
Weapons case

Custodian:

Army - GL

Review activity:

Army - AV

Preparing activity:

Army - GL

(Project 1670-A815)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

## INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

**NOTE:** This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1. DOCUMENT NUMBER | 2. DOCUMENT DATE (YYMMDD) |
|---|---|---|
| | MIL-C-44476(GL) | 931108 |

**3. DOCUMENT TITLE**
Container, Aerial Delivery, Weapons and Equipment, Adjustable

**4. NATURE OF CHANGE** *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

**5. REASON FOR RECOMMENDATION**

**6. SUBMITTER**

| a. NAME (Last, First, Middle Initial) | b. ORGANIZATION | |
|---|---|---|
| c. ADDRESS (Include Zip Code) | d. TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON (If applicable) | 7. DATE SUBMITTED (YYMMDD) |

**8. PREPARING ACTIVITY**

| a. NAME | b. TELEPHONE (Include Area Code)<br>(1) Commercial | (2) AUTOVON/DSN |
|---|---|---|
| U.S. Army Natick RD&E Center | 508-651-4531 | 256-4531 |
| c. ADDRESS (Include Zip Code)<br>Commander, U.S. Army Natick RD&E Center<br>ATTN: STRNC-UC<br>Natick, MA 01760-5017 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 | |

DD Form 1426, OCT 89 NATICK OP3, JUL 91 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.