INCH-POUND

MIL-DTL-44476A (GL)
9 September 1996
SUPERSEDING
MIL-C-44476 (GL)
8 November 1993

DETAIL SPECIFICATION

CONTAINER, AERIAL DELIVERY, WEAPONS AND EQUIPMENT, ADJUSTABLE

This specification is approved for use by the Natick Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of a parachutist's reinforced jump container. The container is fabricated from nylon duck cloth and nylon webbing.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Drawing. The following Government drawing forms a part of this document to the extent specified herein. Unless otherwise specified, the issue is that cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Natick Research, Development, and Engineering Center, Attn: SSCNC-UTE Natick, MA 01760-5017 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

11-1-6866 - Container, Aerial Delivery, Weapons and Equipment, Adjustable

(Copies of drawings are available from the U.S. Army Natick Research, Development and Engineering Center, ATTN: AMSSC-S-IMI, Natick, MA 01 760-5017).

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.2 Materials and components. Materials and components shall conform to the requirements on the applicable drawings, to subsidiary specifications and standards applicable thereto, and as specified herein.

3.2.1 Materials and components. Materials and components shall conform to the requirements environmentally preferable materials should be used to the maximum extent possible provided the material meets or exceeds the operational requirements, and promotes economically advantageous life cycle costs.

3.3 Construction. The construction shall conform in all respects to the drawing listed in Section 2 and all subsidiary drawings pertaining thereto, and as specified herein.

3.3.1 Stitching, machine. All machine stitching shall be as specified on the applicable drawings and as specified herein.

3.3.1.1 Type 301 stitching. Ends of all type 301 stitching shall be backstitched or overstitched not less than 1/2 inch in accordance with the required stitch pattern. Thread tension shall be maintained so that there will be no loose stitching resulting in the puckering of the material sewn. The lock shall be embedded in the materials sewn.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during the stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box-x and W-W stitching) from the end of the stitching. 1/

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch from the defective area, (1/2 inch for box-x and W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for box-x and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Automatic stitching. Automatic stitching machines mabe used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met; and at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3.2 Thread ends. All thread ends shall be trimmed to a maximum length of 1/4 inch.

3.4 Repairs. Repairs such as mends, darns, patches, or splices are not permitted on the container.

3.5 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in table I shall be removed from production and replaced with nondefective and properly matched components.

3.6 Workmanship. The finished and assembled containers shall conform to the quality of product established by this specification.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)
b. Conformance inspection (see 4.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. When a first article inspection is required (see 3.1 and 6.2) it shall be examined in accordance with 4.3. Sampling for first article inspection shall be as specified in the contractor purchase order (see 6.2).

4.3 Conformance inspection. Conformance inspection shall include the examination of 4.3.1,4 .3.2,4.3.3 and 4.3.4. Sampling for the inspections in 4.3.3 and 4.3.4 shall be as specified in the contractor purchase order (see 6.2).

4.3.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details and dimensional requirements which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.3.3 End item vsual examination. The end items shall be examined for visual defects. Each noncompliance shall be scored as a defect in accordance with table I.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Any hole (except drill holes), cut or tear, weak places or broken yarns	101	
	Exposed drill holes		201
Felt	Any hole, cut, or tear		202
Webbing, tape or cord	Not firmly and tightly woven; edge frayed or scalloped	102	
	Exposed end of tie-down tapes not dipped in wax as required		203
	Exposed end of nylon webbing or tape not seared smooth as required		204
Fastener tape, hook and pile	Any hole, cut, or tear. Hooks missing or flattened, foreign matter or dirt impairing proper function	103	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd.)

Examine	Defect	Classification Major	Minor
Hardware	Broken or bent; corroded areas; burrs or sharp edges	104	
	Any required component not specified type or size	105	
	Any required component not functioning, improperly set or reversed	106	
Slide fastener	Not functioning properly, failing to affect closure or to open freely	107	
	Not specified type or size	108	
	Slider jams or fails to interlock	109	
	Thong omitted	110	
	Damaged teeth	111	
Open seams and run-offs	1/2 inch or less		205
	More than 1/2 inch	112	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more skipped stitches or run-offs occur. On a double stitching seam, a seam shall be considered open when either one or both sides of the seam are open.		
Binding	Improperly or loosely applied showing raw edge of fabric	113	
	End of binding not finished as specified or overlapped less than 1 inch		206
Seam and stitch type	Wrong seam or stitch type	114	
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in excessive tightness of fabric on seams	115	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd.)

Examine	Defect	Classification Major	Minor
Stitches per inch	One stitch less than minimum specified		207
	Two or more stitches less than minimum specified	116	
	One or two stitches in excess of maximum specified		208
	More than two stitches in excess of maximum specified	117	
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places, heavy seams or in turning comers, shall be classified as follows: a. Within the major defect classification - minor defect b. Within the minor defect classification - no defect		
Stitching margins	Larger than specified by more than 3/1 6 inch for more than 2 inches		209
Thread breaks	Not overstitched as specified		210
	NOTE: Thread breaks not overstitched shall be classified as open seams.		
Stitching ends	Ends of stitching backstitched less than 1/2 inch (except where ends are turned under in a hem or held down by other stitching)		211
	Ends of stitching not backstitched	118	
Stitching	Any required row of stitching omitted (except on W-W stitching)		119
	W-W stitching:		
	One or more rows of stitching omitted	120	
	Length of stitching less than specified by more than 1/4 inch	121	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd.)

Examine	Defect	Classification Major	Minor
Components and assembly	Any component or required operation omitted or not as specified (unless otherwise classified herein)	122	
	Needle chews	123	
	Mends, dams, or patches	124	
	Any turn under on stitched ends of webbing not securely caught in W-W stitching	125	
	Turn under on ends of straps, chapes, and loops less than specified by more than 1/8 inch		212
Marking and identification	Omitted, illegible, incorrect, misplaced, or size of characters not as specified		213
Cleanness	Noticeable spots or stains, i.e., grease, oil ink, dirt not removed; thread ends not trimmed to 1/4 inch or less		214

4.3.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature which maybe helpful, but is not mandatory).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The container assembly is used by airborne personnel during parachute operations.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification
b. When first article is required (see 3.1)
c. Sampling plan, lot size, sample size (see 4.3)
d. Packaging requirements (see 5.1)

6.3 Subject term (key word) listing.

Air delivery
Carrier
Weapons case

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - GL

Review activity
Army - AV

Preparing activity:
Army - GL

(Project 1670-A854)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3 and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-DBL-44476A (GL)	2. DOCUMENT DATE(YYMMDD) 96-12-09
3. DOCUMENT TITLE	Container, Aerial Delivery, Weapons and Equipment, Adjustable	
4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)		
5. REASON FOR RECOMMENDATION		
6. SUBMITTER		
a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)
8. PREPARING ACTIVITY		
a. NAME U.S. Army Natick RD&E Center	b. TELEPHONE (Include Area Code) (1) Commercial (508) 233-5175 (2) AUTOVON 256-5175	
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SSCNC-WEF Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD FORM 1426, OCT 89 Previous editions are obsolete 198/290
NATICK OP1, 1 MAR 96 NATICK OP1,, Jul 91 IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:08Z
Check the source to verify that this is the current version before use.