INCH-POUND

MIL-E-44470
30 July 1993

MILITARY SPECIFICATION

EGGS, SCRAMBLED, COOKED, DEHYDRATED, (OPERATIONAL RATION COMPONENT)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers dehydrated, cooked, scrambled eggs for use by the Department of Defense as a component of operational rations (see 6.1).

1.2 Classification. The product shall be of the following types as specified (see 6.2).

Type I - Scrambled Eggs

Type II - Scrambled Eggs with Cheese and Bacon Pieces

Type III - Scrambled Eggs with Cheese, Western-style

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5018, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
QQ-A-1876	-	Aluminum Foil
PPP-B-26	-	Bag, Plastic (General Purpose)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-843	-	Cushioning Material, Cellulosic
PPP-C-1752	-	Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible
PPP-C-1797	-	Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam
PPP-T-60	-	Tape: Packaging, Waterproof

MILITARY

MIL-R-44471	-	Ranchero Sauce, Freeze-dehydrated, (Operational Ration Component)

STANDARDS

FEDERAL

FED-STD-595	-	Colors Used in Government Procurement

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations (9 CFR Parts 301-399)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

Regulations Governing the Inspection of Egg and Egg Products (7 CFR Part 59)

(Copies are available from the Chief, Standardization Branch, Poultry Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 3944, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

General Specifications for Dairy Plants Approved for USDA Inspection and Grading Service (7 CFR Part 58)

United States Standards for Grades of Cheddar Cheese

(Copies are available from the Dairy Standardization Branch, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2750, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Grades of Frozen Sweet Peppers

(Copies are available from the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 0709, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Grades of Sweet Peppers

(Copies are available from the Chief, Fresh Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2056, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS)
FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of documents cited in the solicitation (see 6.2).

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, One Maritime Plaza, 23rd Floor, San Francisco, CA 94111.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 1238 - Flow Rates of Thermoplastics by Extrusion Plastometer
D 1505 - Density of Plastics by Density Gradient Technique

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AOAC INTERNATIONAL

Official Methods of Analysis of the AOAC

(Application for copies should be addressed to the AOAC International, 2200 Wilson Boulevard, Suite 400, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

THE UNITED STATES PHARMACOPEIA CONVENTION, INC.

The United States Pharmacopeia (USP) and the National Formulary (NF)

(Application for copies should be addressed to the United States Pharmaceutical Convention, Inc., 12601 Twinbrook Parkway, Rockville, MD 20852.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

days prior to tray pack filling. IQF cooked meatballs shipped between plants

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First Article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Bacon pieces, shelf stable. The bacon pieces shall be 100 percent bacon. The bacon pieces shall be in the shape of a flake, not a bit. They shall have a maximum water activity of 0.60, a maximum moisture content of 10 percent, a maximum fat content of 25 percent, and be of such size that 80 percent or more shall be retained on a U. S. Standard No. 8 sieve (see 6.5.1).

3.2.2 Cheese, cheddar, sharp, dehydrated, uncolored. Dehydrated, uncolored, sharp cheddar cheese shall be derived from U.S. Grade A or better, cured (aged), uncolored cheddar cheese as defined in the U.S. Standards for Grades for Cheddar Cheese. The cheddar cheese shall be manufactured in a USDA approved plant that meets the requirements specified in the General Specifications for Approved Dairy Plants and Standards for Grades of Dairy Products, USDA Inspection and Grading Service (7 CFR Part 58). The dehydrated cheddar cheese shall be uncolored, uniform in composition and appearance, and free from burnt specks and from lumps that do not fall apart under light finger pressure. The dehydrated cheese shall contain not more than 4.0 percent moisture, not more than 6.0 percent salt, and not less than 50.0 percent milkfat when calculated as milkfat in solids (fat on a dry basis).

3.2.3 Eggs, whole, liquid or frozen. Whole eggs may be liquid or frozen and shall have been processed in accordance with the Regulations Governing the Inspection of Eggs and Egg Products (7 CFR Part 59). The whole eggs shall be egg whites and egg yolks in their natural proportions as broken directly from the shell as evidenced by a USDA Egg Products Inspection Certificate. The eggs shall be USDA certified Salmonella free. For liquid whole eggs, the certificate shall state the time of pasteurization. Liquid whole eggs shall be held at a temperature of 40°F or lower and not more than 72 hours from the time of pasteurization until the start of formulation

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

of the product in which they are used. Frozen whole eggs shall be held at 10°F or lower and used within 120 days. The whole eggs shall be in excellent condition, for example, free from objectionable odors, such as musty, sour, or fruity, and free from foreign material.

3.2.4 Flavoring, bacon, natural. The natural bacon flavor shall be a powder and shall have a flavor and odor typical of cooked bacon (see 6.5.2).

3.2.5 Flavoring, egg, natural. The natural egg flavor shall be a paste and shall have a flavor and odor typical of cooked, scrambled eggs (see 6.5.3).

3.2.6 Ham, canned or cooked. The ham shall not be labeled "water added", and shall not contain dextrose or smoke flavoring. The canned or cooked ham shall be maintained at an internal temperature of 28° to 40°F for a period of time not to exceed 90 days from date of pack until preparation of the finished product.

3.2.7 Maltodextrin. Maltodextrin shall be a white, free-flowing powder with a dextrose equivalent (D.E.) of 15. It shall have a maximum moisture content of 6 percent and a pH range of 4.0 to 4.7 (see 6.5.4).

3.2.8 Nitrogen. Nitrogen shall be U.S. Pharmacopoeia grade and shall be water or liquid nitrogen pumped.

3.2.9 Oil, vegetable. Vegetable oil shall possess a clean, bland flavor, and shall have a minimum stability of 25 hours (A.O.M.), have a free fatty acid value not to exceed 0.05 percent, have a moisture/volatile matter content not to exceed 0.06 percent, and shall pass a cold test of 5.5 hours (minimum). The oil may contain antioxidants in combinations and amounts permitted by FDA regulations.

3.2.10 Onions, dehydrated, chopped. Dehydrated chopped onions shall be Fancy Grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.11 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner covering have been removed. The ground pepper shall have a characteristic, penetrating odor, a hot, biting, pungent flavor, and a light color. The ground pepper shall contain not less than 1.0 mL of volatile oil per 100 grams of ground white pepper and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.12 Peppers, green, sweet, fresh. The fresh, sweet, green peppers shall be U.S. No. 1 or better of the U.S. Standards for Grades of Sweet Peppers. They shall be clean, sound, and of a similar variety. Frozen grade B or better may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

3.2.13 Peppers, red, sweet, fresh. The fresh, sweet red peppers shall be U.S. No. 2 or better of the U.S. Standards for Grades of Sweet Peppers. They shall be clean, sound, and of a similar variety. Frozen grade B or better may be used.

3.2.14 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this document. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formulation.

3.2.15 Salt. Salt shall be noniodized, white, refined sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.16 Stabilizer compound. The stabilizer compound shall be composed of 12 percent of sodium carboxymethylcellulose and 88 percent of microcrystalline cellulose. It shall be a free-flowing, off white powder and shall be easily dispersed when added to a water system (see 6.5.5).

3.2.17 Water. Water used for formulation, blanching, ice making, and washing shall conform to the National Primary Drinking Water Regulations.

3.2.18 Xanthan gum. Xanthan gum shall comply with the Food Chemicals Codex.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Preparation of ham. The ham shall be diced into 3/8 inch cubes. The ham cubes shall be frozen and then freeze-dehydrated in accordance with 3.4 and 3.4.1.

3.3.2 Preparation of sweet green and red peppers. The fresh green and red peppers shall be diced into 3/8 inch to 1/2 inch dices, and then blanched until firm and tender in accordance with acceptable commercial practices for peppers. The peppers shall be frozen and then freeze-dehydrated in accordance with 3.4 and 3.4.1.

3.3.3 Product preparation.

3.3.3.1 Preparation of scrambled eggs (type I). The scrambled eggs shall be formulated and prepared as follows:

Ingredients	Percent by weight
Eggs, whole, liquid or frozen 1/	78.50
Water	15.76

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

Oil, vegetable	2.00
Maltodextrin	1.50
Stabilizer compound	0.80
Salt	0.70
Flavoring, egg, natural	0.40
Xanthan gum	0.25
Pepper, white, ground	0.09

1/ Frozen whole eggs, if used, shall be completely thawed and held at a temperature of 40°F or lower, and shall be held for not longer than 24 hours prior to use.

The product shall be prepared as follows:

a. Blend together the water and all dry ingredients until as smooth as possible.

b. Add the oil and eggs, and blend with a high speed mixer until completely smooth and uniform.

c. Cook until an internal temperature of 180°F to 190°F is obtained.

d. The product shall be frozen and freeze-dehydrated in accordance with 3.4 and 3.4.1.

e. Pieces should be 1/2 inch to 1 inch in size.

3.3.3.2 Preparation of scrambled eggs with cheese (for use in type II and type III). The scrambled eggs with cheese shall be formulated and prepared as follows:

Ingredients	Percent by weight
Eggs, whole, liquid or frozen 1/	72.50
Water	18.41
Cheese, cheddar, sharp, dehydrated, uncolored	4.00
Oil, vegetable	2.00
Maltodextrin	1.00
Stabilizer compound	0.80
Flavoring, bacon, natural	0.50
Salt	0.45
Xanthan gum	0.25
Pepper, white, ground	0.09

1/ Frozen whole eggs, if used, shall be completely thawed and held at a temperature of 40°F or lower, and shall be held for not longer than 24 hours prior to use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

The product shall be prepared as follows:

a. Blend together the water and all dry ingredients until as smooth as possible.

b. Add the oil and eggs, and blend with a high speed mixer until completely smooth and uniform.

c. Cook until an internal temperature of 180°F to 190°F is obtained.

d. The product shall be frozen and freeze-dehydrated in accordance with 3.4 and 3.4.1.

e. Pieces should be 1/2 inch to 1 inch in size.

For type II only:

NOTE: For type II, eight 2 gram samples of freeze-dehydrated scrambled eggs prior to blending with the bacon pieces shall be selected at random from the lot and tested for moisture content in accordance with 4.5.8. The moisture shall be not greater than 2.0 percent.

f. The freeze-dehydrated scrambled eggs with cheese pieces and the shelf stable bacon pieces shall be combined and dry blended in the following proportions:

Ingredients	Percent by weight
Dehydrated scrambled eggs with cheese	84.0
Bacon pieces, shelf stable	16.0

For type III only:

g. The freeze-dehydrated scrambled eggs with cheese pieces and the dehydrated ham, green and red peppers, and onions shall be combined and dry blended in the following proportions:

Ingredients	Percent by weight
Dehydrated scrambled eggs with cheese	74.9
Dehydrated ham	22.0
Dehydrated green peppers	1.5
Dehydrated green red peppers	1.5
Dehydrated, onions, chopped	0.1

3.4 Freezing. The prepared product shall be spread on dehydrator trays and cooled immediately, placed in a freezer within 4 hours after cooking, and frozen to 0°F or below within 8 hours after placing in the freezer. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

frozen product shall be maintained at 0°F or below at all times prior to freeze dehydration, and shall be in the freeze dehydration process not less than 5 days after freezing.

3.4.1 Dehydration. The product shall be freeze-dehydrated at an absolute pressure not to exceed 1.5 mm of mercury for more than 5 minutes during the first three quarters or 10 minutes during the last quarter of the drying cycle. At no time shall there be evidence of thawing in the product. The product temperature shall not exceed 150°F. If the platen temperature is maintained at 155°F or below with radiant heating, the product temperature may be disregarded. After dehydration is completed, the pressure shall be equalized to atmospheric level with nitrogen. In no case shall more than 16 hours elapse between the time the chamber is opened to the time the product is completely packaged. During this interim period, the product shall be adequately protected from oxygen and moisture by either holding under a nitrogen atmosphere with 2.0 percent or less oxygen, or under a vacuum of at least 27 inches of mercury for the entire period. If vacuum is used, it shall be broken with nitrogen. Alternate product holding procedures may be used (see 6.6).

3.5 Pouch filling and sealing. The freeze-dehydrated product shall be packaged immediately in accordance with 5.1.

3.6 Finished product requirements. The finished product shall comply with the following requirements:

Dehydrated product:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. There shall be no evidence of incomplete dehydration such as wet or soft spots.

e. There shall be no evidence of faulty dehydration such as glazed surface areas measuring more than 0.5 inch in any dimension.

f. There shall be no evidence of faulty dehydration such as burnt areas measuring more than 0.5 inch in any dimension.

g. There shall be no evidence of faulty dehydration such as dark colored areas of any dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

h. A minimum of 70.0 percent for type I, or 58.0 percent for type II, or 65.0 percent for type III product shall be retained on a U.S. Standard 1/4 inch sieve.

i. The moisture content of the product shall be not greater than 2.0 percent (for type I and III). For type II, the moisture shall be determined by in-process testing (see 3.3.3.2) and shall be not greater than 2.0 percent.

j. The net weight of the product shall be not less than that specified below:

Product	Single service (grams)	Multi-service (grams)
Type I	75	255
Type II	88	300
Type III	75	255

k. The aerobic plate count shall be not greater than 75,000 per gram in four of five samples and not greater than 150,000 per gram in any sample.

l. The E. coli count shall be less than 3 per gram (no positive tubes in the standard three tube MPN technique) in four of five samples and not greater than 10 per gram in any sample.

m. Product shall be free of Salmonella.

Rehydrated product:

n. When the product is rehydrated (see 4.5.6), the product shall show complete water penetration.

o. The rehydrated product shall possess the odor, flavor, and texture of a freeze-dehydrated scrambled egg product. There shall be no scorched, burnt, or foreign flavor or odor.

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.2) in palatability and overall appearance.

3.7 Plant qualification. The ham and bacon components and the finished product shall originate and be produced, processed, and stored in plants regularly operating under the Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.2), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods such as the standard methods described in the Official Methods of Analysis of the AOAC International, and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

4.5.1.2 Material certification. A certificate of compliance may be accepted as evidence that the characteristics listed below conform to the specified requirements.

Material requirement	Requirement paragraph	Test procedure
Mixing bag.		
Material identification	5.1.2	Laboratory evaluation
Polyethylene film thickness	5.1.2	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378.
Color of material	5.1.2	Visual evaluation
Baseboard (when used).		
Material identification	5.1.2.2	Laboratory evaluation
Paperboard film thickness	5.1.2.2	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378.
Color of material	5.1.2.2	Visual evaluation
Pouch.		
Laminated material identification and construction	5.1.3 and 5.1.3.1	Laboratory evaluation
Polyethylene film and polyester film thickness	5.1.3	As specified in L-P-378, except that a machinist's micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

Aluminum foil thickness	5.1.3	As specified in QQ-A-1876
Color of laminated material	5.1.3	Visual evaluation

4.5.1.3 Unfilled mixing bag examination. The unfilled mixing bags shall be examined for the defects listed in table I. The lot size shall be expressed in bags. The sample unit shall be one mixing bag. The inspection level shall be S-4 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65.

TABLE I. Unfilled mixing bag defects

Category	Defect
Major	
101	Not formed as specified
102	Inside dimensions not as specified
103	Tear, hole, or open seal
104	Not material specified
105	Bags stick together
106	Not clean
107	Foreign odor

4.5.1.4 Unfilled mixing bag leakage testing. The unfilled mixing bag shall be tested for leakage as follows: Each sample of 5-1/2 (length) by 3-1/2 (depth) by 8 (height) inch size mixing bag shall be filled with 300 mL of boiling water. Each sample of 9 (length) by 3-1/2 (depth) by 12 (height) inch size mixing bag shall be filled with 1000 mL of boiling water. Care shall be taken to prevent spillage of water onto the outside of the bag. Each water filled bag shall be suspended 8 to 12 inches above a sheet of clean paper for 10 minutes. Any moisture on the paper attributable to bag leakage shall be classified as a major defect. The lot size shall be expressed in bags. The sample unit shall be one unfilled mixing bag. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation, or of other valid documents shall be cause for rejection of the involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

4.5.3 Filled and sealed pouch examination. The filled and sealed pouches shall be examined for the defects listed in table II. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 4.0 for minor defects.

TABLE II. Filled and sealed pouch defects 1/

Category		Defect
Major	Minor	
101		Tear, hole, or abrasion through one or more layers 2/
102		Not heat sealed as specified
103		Presence of foldover wrinkles and entrapped product that reduces the effective closure seal to less than 1/16 inch 3/
104		Evidence of delamination 4/
105		Not clean 5/
106		Required labeling or marking missing, incorrect, illegible, or that smudges
107		Any impression or design on the heat seal surface which conceals or impairs visual detection of seal defects 6/
108		Closure seal widths not as specified
	201	Evidence of delamination 4/
	202	Color of pouch not as specified
	203	Tear notch missing
	204	Tear notch not located as specified
	205	Depth of tear notch not as specified
	206	Serrations missing 7/
	207	Serrations not located as specified 7/
	208	Depth of serrations not as specified 7/

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

TABLE II. Filled and sealed pouch defects 1/ (cont'd)

Category		Defect
Major	Minor	
	209	Closure seal or top seal extends into or below tear notch

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

2/ Pinholes or breaks inherent to the manufacturing process of the aluminum foil shall not be scored as a defect.

3/ The effective closure seal is defined as any uncontaminated, fusion bonded, continuous path, minimum 1/16 inch wide from side seal to side seal that produces a hermetically sealed pouch.

4/ Delamination defect classification:

Major - Delamination of the outer ply in the pouch seal area that can be propagated to expose aluminum foil at the food product edge of the pouch after manual flexing of the delaminated area. To flex, the delaminated area shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delamination area shall then be rapidly flexed 10 times by rotating both hands in alternating clockwise - counterclockwise directions. Care shall be exercised when flexing delaminated area near the tear notch to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between the thumb and forefinger and gently lifted toward the food product edge of the seal or if the separated area is too small to be held between thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to the product edge of the seal with no discernible resistance to the gentle lifting, the delamination shall be scored as a major defect. Additionally, spot delamination of the outer ply in the body of the pouch that is able to be propagated beyond its initial borders is also a major defect. To determine if the delaminated area is a defect, use the following procedure: Mark the outside edges of the delaminated area using a bold permanent marking pen. Open the pouch and remove the contents. Cut the pouch transversely not closer than 1/4 inch (± 1/16 inch) from the delaminated area. The pouch shall be flexed in the are area in question using the procedure described above. Any propagation of the delaminated area, as evidenced by the delaminated area exceeding the limits of the outlined borders, shall be scored as a major defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

Minor - Minor delamination of the outer ply in the pouch seal area is acceptable and shall not be scored as a minor defect unless it extends to within 1/16 inch of the food product edge of the seal. All other minor outer ply delamination in the pouch seal area or isolated spots of delamination in the body of the pouch that do not propagate when flexed as described above shall be scored as a minor defect.

5/ Outer packaging shall be free from foreign matter which is unwholesome, has the potential to cause pouch damage (for example, glass, metal fillings) or generally detracts from the clean appearance of the pouch. The following examples shall not be scored as defects for unclean:

a. Foreign matter which presents no health hazard or potential pouch damage and which can be readily removed by gently shaking the pouch or by gently brushing the pouch with a clean dry cloth.

b. Dried product which affects less than 1/8 of the total surface area of one pouch face (localized and aggregate).

c. Water spots.

6/ If doubt exists as to whether or not the sealing equipment leaves an impression or design on the closure seal surface that could conceal or impair visual detection of seal defects, samples shall be furnished to the contracting officer for a determination as to acceptability.

7/ Applicable only to pouches made on machinery that produces serrations.

4.5.4 Pouch vacuum examination. Not less than 96 hours after filling and sealing, the pouches shall be visually examined for conformance to the vacuum requirements in 5.2. The sealed pouch shall continue to exhibit tight adherence to the surface contours of the contents when a pulling force is applied at the center of each side seal. This force shall be applied by holding each side seal between thumb and forefinger of each hand, simultaneously exerting a slight pull with both hands. Any evidence of loss of vacuum shall be classified as a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.5.5 Net weight examination. The net weight of the filled and sealed pouches shall be determined by weighing each sample unit on a suitable scale tared with a representative empty mixing bag and pouch. Any individual net weight of less than that specified in 3.6 shall be classified as a minor defect. The results shall be reported to the nearest gram. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed mixing bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than that specified in 3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

4.5.6 Product examination. The finished product shall be examined for the defects listed in table III. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

TABLE III. Product defects 1/ 2/

Category		Defect
Major	Minor	
101		Pouch or mixing bag has foreign odor
		Dehydrated product
102		Presence of incomplete dehydration such as wet or soft spots
103		Presence of glazed surface areas measuring more than 0.5 inch in any dimension
104		Presence of burnt areas measuring more than 0.5 inch in any dimension
105		Presence of dark colored cores in any dimension
	201	Less than 70.0 percent for type I, or 58.0 percent for type II, or 65.0 percent for type III product retained on a U.S. Standard 1/4 inch sieve 3/
		Rehydrated product 4/
107		Product shows incomplete water penetration
108		The rehydrated product does not possess the odor, flavor, or texture of freeze-dehydrated scrambled eggs

1/ The presence of foreign material (for example, dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (for example, burnt, scorched, stale, sour, rancid, moldy), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot (see 3.6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

4.5.7 The dry pack product shall be free from foreign material (such as

3/ One pouch of the multi-service pouch or two pouches of the single service pouch shall be manually shaken on a U.S. Standard 1/4 inch sieve for 30 seconds.

4/ The product shall be rehydrated as follows:

a. Single service pouch - Add 300 mL of hot water (180°F to 200°F) to mixing bag and allow to rehydrate for 10 minutes prior to examination.

b. Multi-service pouch - Add 1000 mL of hot water (180°F to 200°F) to mixing bag and allow to rehydrate for 10 minutes prior to examination.

4.5.7 Internal pressure test. The pouches shall be emptied prior to testing (remove dehydrated product and mixing bag) for use with three-seal tester only. Internal pressure resistance shall be determined by pressurizing the pouches while they are restrained between two rigid plates spaced 2-3/4 inches (± 1/8 inch) apart. If a three-seal tester (one that pressurizes the pouch through an open end) is used, the closure seal shall be cut off for testing the side and bottom seals of the pouch; for testing of the closure seal, the bottom seal shall be cut off. If a four-seal tester (designed to pressurize filled pouches by use of a hypodermic needle through the pouch wall) is used, all four seals can be tested simultaneously. Pressure shall be applied at the approximate uniform rate of 1 pound per square inch gage (psig) per second until 14 psig pressure is reached. The 14 psig pressure shall be held constant for 30 seconds and then released. The pouches shall then be examined for separation or yield of the heat seals. Any rupture or evidence of seal separation greater than 1/16 or seal separation that reduces the effective closure seal width to less than 1/16 inch shall be considered a test failure. The lot size shall be expressed in pouches. The sample unit shall be one pouch. The inspection level shall be S-1. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.8 Moisture content testing. For type I and III, eight filled and sealed pouches shall be selected at random from the lot regardless of lot size. For type II, eight 2 gram samples of freeze-dehydrated scrambled eggs prior to blending with the bacon pieces (see 3.3.3.2) shall be selected at random from the lot regardless of lot size. The product shall be individually tested for moisture content in accordance with the Official Methods of Analysis of AOAC, method 925.45, using a sample containing about 2 grams at a temperature of 70°C for 16 hours at a pressure of 100 mm of mercury. The results shall be reported to the nearest 0.1 percent. Any result not conforming to the moisture content requirement in 3.3.3.2 (type II) or 3.6 (types I and III) shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.9 Microbiological testing. Five filled and sealed pouches of finished product shall be selected at random from the lot regardless of lot size. The product shall be individually tested for microbiological levels in accordance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

with the Official Methods of Analysis of AOAC, methods 966.23 and 966.24. The diluent shall be added to each sample and allowed to stand for 15 minutes before blending sample. Salmonella testing shall be in accordance with the Official Methods of Analysis of AOAC, method 967.26. Any result not conforming to the microbiological requirements in 3.6 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.10 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: Markings missing, incorrect, or illegible.
Cushioning material missing or not as specified.

Minor: More than 35 pounds packed in a box.
Bags not packed flat in layers.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A preservation. The product shall be filled into mixing bags as specified in 5.1.2 and sealed in pouches as specified in 5.1.3.

5.1.2 Mixing bag. The mixing bag shall be fabricated from 0.003 inch thick polyethylene made in accordance with type I bags of PPP-B-26, except that the bag shall be made from food grade polyethylene. The mixing bags shall be approved by the FDA for food use and shall not impart any undesirable odor or flavor to the product. The bottom seal shall maintain its strength and integrity when tested as specified in 4.5.1.4. The inside dimensions of the single service bag shall be 5-1/2 inches (± 1/8 inch) in length by 3-1/2 inches (± 1/8 inch) in depth by 8 inches (± 1/8 inch) in height, with the 5-1/2 inch dimension being the opening of the bag. The inside dimensions of the multi-service bag shall be 9 inches (± 1/8 inch) in length by 3-1/2 inches (± 1/8 inch) in depth by 12 inches (± 1/8 inch) in height, with the 9 inch dimension being the opening of the bag. Alternatively, for single service bags, polyethylene bags conforming to type II of PPP-B-26, with inside dimensions of 9 inches (± 1/8 inch) in width by 8 inches (± 1/8 inch) in length, with the 9 inch dimension being the opening of the bag with the open end of the bag may be used. When type II bags are used, they shall be formed over a baseboard on a mandrel as specified in 5.1.2.1 before filling. While the bag is positioned on the mandrel, the two bag ears shall be taped down over a 5-1/2 by 3-1/2 inch baseboard constructed in accordance with 5.1.2.2. An 8 inch long strip of 1 inch wide tape complying with type III, class 2 of PPP-T-60 shall be applied across both ears to fasten them securely to the baseboard. Alternatively, both type I and type II mixing bags may be fabricated from unpigmented 0.003 inch thick

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

high density 0.941 to 0.965 g/cm food grade, flat polyethylene tubing. The bottom seal of type I and type II mixing bags fabricated from the alternate material shall maintain its strength and integrity when tested as specified in 4.5.1.4.

5.1.2.1 Mandrel. The mandrel face shall be 5-3/8 inches in length by 3-3/8 inches in width and the height shall not be less than 12 inches. All corners and edges of the mandrel shall be rounded and all surfaces finished to prevent damage to the bag material.

5.1.2.2 Baseboard. The baseboard shall be constructed from unbleached and uncoated solid sulfate or sulfite paperboard not less than 0.022 inch thick. Alternatively, the baseboard may be constructed from 0.022 inch thick food grade paperboard made from recycled fibers. If paperboard made from recycled fibers is used, it shall be natural color ranging from brown to grey. The baseboard shall be 5-1/2 inches (± 1/8 inch) in length by 3-1/2 inches (± 1/8 inch) in width and shall have all corners rounded to form a smooth contour.

5.1.3 Pouch material. The pouch shall be fabricated from a 3-ply flexible laminate material consisting of an outer ply of 0.0005 inch (± 0.0001 inch) thick polyester bonded to an intermediate ply of 0.0007 inch (± 0.00014 inch) thick aluminum foil with 10 pounds per ream pigmented polyethylene and bonding the opposite side of the aluminum foil to 0.003 inch (± 0.0006 inch) thick ionomer (inner ply) or a blend of not less than 50 percent linear low density polyethylene and polyethylene. The linear low density polyethylene portion of the blend shall be the copolymer of ethylene and octene-1, having a melt index range of 0.8 to 1.2 grams per 10 minutes in accordance with ASTM D 1238 and a density range of 0.918 to 0.922 g/cm in accordance with ASTM D 1505. The complete exterior of the pouch shall be uniformly colored in the range of 34079 through 34087, or in the range of 24052 through 24087, or in the range of 30045 through 30118, excluding color 30109 of FED-STD-595. The color application process shall not adversely affect the material performance. The material shall be suitably formulated for food packaging and shall not impart an odor or flavor to the product being packaged. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches.

5.1.3.1 Pouch construction. The preformed pouch shall be a flat style pouch having inside dimensions of 6 inches (± 1/8 inch) in width by 9 inches (± 1/8 inch) in length for the single service pouch, with the 6 inch dimension being the opening of the pouch between the heat sealed sides. The multi-service pouch shall have inside dimensions of 12 inches (± 1/8 inch) in width by 13 inches (± 1/8 inch) in length, with the 12 inch dimension being the opening of the pouch between the heat sealed sides. The pouch shall be made by heat sealing three edges (two sides and bottom) with 3/8 inch (± 1/8 inch) wide seals. The pouch shall withstand an internal pressure of 14 psig for 30 seconds without rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

1/16 inch when tested as specified in 4.5.7. A V-shaped, C-shaped or U-shaped tear notch at least 1/32 inch deep, located 1 to 1-1/4 inches from the top edge of the pouch (excluding the lip) shall be made in one or both side seals. The distance between the inside edge of the tear notch and the inside edge of the seal shall be not less than 3/16 inch. One side of the open end of the pouch may be provided with an extended or foldover lip, extended not more than 5/16 inch (± 1/16 inch) to facilitate opening and filling. Tear notch location shall be measured from the top of the pouch, excluding the extended or foldover lip. Alternatively, if the pouch has serrated edges, the serrations may be used as tear notches provided that the serrations are sharp (no plastic tailing exists) and the serration depth and the minimum seal width at the serrated edges are in accordance with the above tear notch requirements. The pouch shall be constructed with square or rounded corners at all four corners (radius approximately 3/8 inch).

5.2 Filling and sealing. The product shall be filled into the mixing bag as specified in 5.1.2 in accordance with the net weight requirements of the applicable product type as specified in 3.6. After filling, the end panel of the bag (corresponding to the 3-1/2 inch dimension) shall be folded in, and the bag shall be closed by folding over its open end. Where required by the bulkiness of the product, the bulk of the contents within the bag shall be compressed such that the product thickness is not more than 2-1/4 inches by applying a constant uniform pressure over the entire top surface of the product. The filled bag with the open end folded over to prevent spillage of the product shall be inserted into the bottom of the pouch as specified in 5.1.3 in such a manner to avoid puncturing the pouch material or contaminating the heat seal area. The filled pouches shall be sealed under a vacuum level of 23 inches of mercury, and applying a continuous heat seal. The filled pouches shall have a 3/8 inch (± 1/8 inch) heat seal. If thermal impulse closure seals are used, a seal width of 1/8 inch will be acceptable. The closure seal shall be free of foldover wrinkles, delamination, or entrapped product that reduces the effective closure seal to less than 1/16 inch wide. The filled and sealed pouches shall withstand an internal pressure of 14 psig for 30 seconds without rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch, when tested as specified in 4.5.7. The filled and sealed pouch shall show no loss of vacuum when examined as specified in 4.5.4.

5.3 Packing for shipment to ration assembler. Not more than 35 pounds of product shall be packed flat in a fiberboard box constructed and closed in accordance with style RSC-L, class domestic, variety SW, grade 200 of PPP-B-636. Cushioning material not less than 1/8 inch thick, conforming to type II class B of PPP-B-843 or cushioning material not less than 1/6 inch thick, conforming to PPP-C-1797 or cushioning material conforming to type 7, class 1 of PPP-C-1752 shall be placed between each of the layers and in the bottom and top of the box to minimize movement of the individual packages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

5.4 Labeling and marking.

5.4.1 Pouch. Each pouch shall be clearly printed or stamped, in a manner that does not damage the pouch, with permanent black ink which is free of carcinogenic elements or ingredients. The information shall be located on the body of the pouch not closer than 1/16 inch to any seal. All pouches shall be coded. If a non-contact type printer is used, the information may be located anywhere on the pouch (in one complete print), except in the closure seal area. The label must include the following information:

Product name (letters not less than 7/32 inch high)
Rehydration instructions (letters not less than 3/32 inch high)
Ingredients (letters not less than 3/32 inch high)
Date of production/lot number 1/ (letters not less than 1/8 inch high)
Net weight (letters not less than 1/8 inch high)
USDA Inspection Marking (letters not less than 1/8 inch high)
Name and address of producer (letters not less than 1/8 inch high)

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year (Example, March 19, 1993 would be coded as 3078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code.

5.4.1.1 Rehydration instructions. Each pouch label shall display the rehydration instructions as follows:

a. For single service pouches (letters not less than 1/8 inch high):

To rehydrate add 7 ounces (about 1/3 canteen cup) hot water, mix thoroughly, wait 5 to 10 minutes.

b. For multi-service pouches (letters not less than 1/8 inch high):

To rehydrate add 22 to 24 ounces hot water, mix thoroughly, wait 10 minutes.

Yield: Serves 9 portions of a 1/2 cup of scrambled eggs.

5.4.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The scrambled egg products may be eaten by themselves or may have ranchero sauce added to them as a condiment. Ranchero sauce requirements are specified in MIL-R-44471.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Type (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).
d. When a first article is required (see 3.1, 4.4, and 6.3).
e. Provisions for approved preproduction samples (see 3.6.1 and 6.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.5 Ingredient information.

6.5.1 Bacon pieces, shelf stable. It has been found that "OM Ingredient 2730" manufactured by Oscar Mayer Company, P.O. Box 398, Memphis, TN 38101 meets the requirements of 3.2.1 and performs satisfactorily in this product. Other equivalent bacon pieces may be used.

6.5.2 Flavoring, bacon, natural. It has been found that Natural Bacon Flavor #101162 manufactured by F & C International, 890 Redna Terrace, Cincinnati, OH, 45215 meets the requirements of 3.2.4 and performs satisfactorily in this product. Other equivalent bacon flavors may be used.

6.5.3 Flavoring, egg, natural. It has been found that Natural Egg Flavor #097867 manufactured by F & C International, 890 Redna Terrace, Cincinnati, OH, 45215 meets the requirements of 3.2.5 and performs satisfactorily in this product. Other equivalent egg flavors may be used.

6.5.4 Maltodextrin. It has been found that "Star-Dri 15" manufactured by A.E. Staley Manufacturing Company, Starch and Specialty Products Group, 220 E. Eldorado Street, Decatur, IL, 62525 meets the requirements of 3.2.7 and performs satisfactorily in this product. Other equivalent ingredients may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

6.5.5 Stabilizer compound. It has been found that "Avicel RC-591F" manufactured by FMC Corporation, Food and Pharmaceutical Products Division, 1735 Market Street, Philadelphia, PA 19103 meets the requirements of 3.2.16 and performs satisfactorily in this product. Other equivalent stabilizers may be used.

6.6 Alternate product holding procedures. The contracting officer may authorize alternate contractor-recommended product holding procedures if the the alternate procedures are approved by the U.S. Army Natick Research, Development and Engineering Center.

6.7 Subject term (key word) listing.

Combat field feeding
Food processing
Freeze-dehydrated food

Custodians:

Army - GL
Navy - MC

Preparing activity:

Army - GL

(Project 8940-0756)

Review activities:

Army - MD, QM
Navy - SA
Air Force - 50
DLA - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.

or more

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-E-44470	1993 July 30

3. DOCUMENT TITLE

EGGS, SCRAMBLED, COOKED, DEHYDRATED, (OPERATIONAL RATION COMPONENT)

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4501	(2) AUTOVON/DSN 256-4501
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WTP Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP4, JUL 91 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:07Z
Check the source to verify that this is the current version before use.