MIL-R-25535A(USAF)
AMENDMENT 1
26 June 1959

MILITARY SPECIFICATION

ROCKET MOTORS, AERONAUTICAL,
PRELIMINARY FLIGHT RATING TEST FOR

This amendment forms a part of Military Specification MIL-R-25535A(USAF) dated 6 April 1959.

Page 2, Paragraph 3.1.1.2.1: In the second line delete "free" and substitute "ambient".

Page 3, Figure 1, Item IV: Delete "Crated - pendulum, incline (specify) from _____ inches." and substitute "Crated - pendulum, incline (specify) impact from _____ inches."

Page 4, Figure 1, Item V: Delete "Rocket Motor Conditioning Temperature _____."

Page 11, Paragraph 4.4.1.2.2: Delete the fifth sentence and substitute "The igniters in groups IV and V shall be removed from individual containers, installed in simulated rocket motors, and subjected to the required tests immediately before firing."

Page 16, Paragraph 4.4.1.3.4.5: Delete "termination" and substitute "reversal".

Page 20, Paragraph 4.4.2.8: In the fourth line delete "could" and substitute "would".

Page 23, Paragraph 4.5.2.3.2: Delete the second sentence and substitute "The burst pressure for each assembly shall be determined."

HWL/mes
WCLPTDS

FSC 1336
FSC 1340

THE REPUBLICAN PRESS, Hamilton, Ohio
November 3, 1961 400

Source: https://assist.dla.mil -- Downloaded: 202640-20T06:38Z
Check the source to verify that this is the currentversion before use.