NOTICE OF
CHANGE

DOD-STD-35-48A(MI)
NOTICE 1
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

TRANSDUCERS

TO ALL HOLDERS OF DOB-STB-35-48A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-48A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	31 AUGUST 1987 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	31 AUGUST 1987
3	18 SEPTEBER 1992	3	31 AUGUST 1987
4	18 SEPTEMBER 1992	4	31 AUGUST 1987
5	18 SEPTEMBER 1992	5	31 AUGUST 1987
6	18 SEPTEMBER 1992	6	31 AUGUST 1987
55	31 AUGUST 1987 (Reprinted without change)		
56	18 SEPTEMBER 1992	56	31 AUGUST 1987
57	18 SEPTEMBER 1992	57	31 AUGUST 1987
58	31 AUGUST 1987 (Reprinted without change)		
69	31 AUGUST 1987 (Reprinted without change)		
70	18 SEPTEMBER 1992	70	31 AUGUST 1987
71	18 SEPTEMBER 1992	71	31 AUGUST 1987
72	31 AUGUST 1987 (Reprinted without change)		

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-48A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together- with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Amy-AT, AV, CR, ER
ME, MR, SC

User activity
Army – AR

Preparing activity:
Army - MI

(Project EGDS-A420)

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Transducers.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSF; shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be code a part of the Title Index.

One of the six-digit codes listed in the Title Index entered on a SRS, specifies that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index, is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user-s reference. When more than one document is listed for a MSE title, this information will be useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
TRANSDUCER, ACCELEROMETER	085011	MIL-A-38307	POTENTIOMETER SENSOR
		MIL-A-22145	ELECTROMAGNETIC SENSOR
		MS25447	COUNTING, ELECTROMAGNETIC SENSOR
TRANSDUCER, ANGULAR POSITION, STRAIN GAGE SENSOR	085002	MIL-T-83460	ANGULAR STRAIN GAGE SENSOR
TRANSDUCER, DIFFERENTIAL PRESSURE, DIAPHRAGM SENSOR	085009		DIFFERENTIAL PRESSURE SENSOR
TRANSDUCER, FORCE, STRAIN GAGE SENSOR	085003	MIL-T-83460	FORCE, STRAIN GAGE SENSOR
TRANSDUCER, HEAT TRANSFER, THERMOCOUPLE	085004	MIL-T-8346O	THERMOCOUPLE, HEAT TRANSFER

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T20:57Z
Check the source to verify that this is the currentversion before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
TRANSDUCER, PRESSURE, BELLOWS SENSOR, GASES OR LIQUIDS	085007	MIL-P-82459	BELLOW SENSOR GASES OR LIQUID
TRANSDUCER, PRESSURE, DIAPHRAGM, SENSOR GASES OR LIQUIDS	085008	MIL-P-82459	DIAPHRAGM SENSOR GASES OR LIQUID
TRANSDUCER, PRESSURE, STRAIN GAGE SENSOR	085012	MIL-T-83460	PRESSURE SENSOR STRAIN GAGE
TRANSDUCER, PRESSURE, STRAIN GAGE SENSOR, PNEUMATIC	085010	MIL-T-83460	PRESSURE SENSOR PNEUMATIC
TRANSDUCER, PRESSSURE SEALED, AMPLIFIED	085019	MIL-T-83460	PRESSURE SEALED AMPLIFIED
TRANSDUCER, SHAFT ROTATION, ELECTROMAGNETIC SENSOR	085013	MIL-A-22145	ELECTROMAGNETIC SENSOR
TRANSDUCER, SHOCK AND VIBRATION	085014	MIL-A-38307	SHOCK AND VIBRATION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE NUMBER	DOCUMENT COVERAGE
TRANSDUCER, TORQUE, SHAFT ROTATION, STRAIN GAGE SENSOR	085016	MIL-T-83460	TORQUE STRAIN GAGE SENSOR
TRANSDUCER, WEIGHT, STRAIN GAGE SENSOR	085018	MIL-T-83460	WEIGHT STRAIN GAGE SENSOR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCJMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are three listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-C-915	Cable and Cord, Electrical, for Shipboard Use, General Specification for
MIL-C-5015	Connectors, Electrical, Circular Threaded, AN Type, General Specification for
MIL-P-5315	Packing, Preformed, Hydrocarbon Fuel Resistant
MIL-P-5510	Packing, Preformed, Straight Thread Tube Fitting Boss, Type I Hydraulic
MIL-P-5516	Packing, Preformed, petroleum Hydraulic Fluid Resistant
MIL-A-22145	Accelerometer Group, Counting Type Designation MS25447 and MS25448
MIL-C-26500	Connectors, General Purpose, Electrical, Miniature, Circular, Environment Resistant, General Specification for
MIL-A-38307	Accelerometer, Aircraft

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:57Z
Check the source to verify that this is the current version before use.

MIL-P-82459	Pressure Transducer
MIL-T-83460	Transducer, Motional Pickup Tru-1641A
MS3102	Connector, Receptacle, Electric, Box Mounting, Solder Contacts, AN Type
MS24264	Connector, Receptacle, Electric, Flange Mount, Miniature
MS33649	Bosses,Fluid Connection-Internal Straight Thread

STANDARD

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electrical and Electrical Component Parts
MIL-STD-461	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	Electromagnetic Interference Characteristics, Measurements of
MIL-STD-810	Enviromental Test Methods and Engineering Guidelines

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, Pa 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4813	DC CURRENT LEAKAGE SHALL BE NOT GREATER THAN 4813 MILLIAMPERE(S) AT HIGH HUMIDITY.
4803	DC CURRENT LEAK SHALL BE NOT GREATER THAN 4803 MILLIAMPERE(S) AFTER DRYING.
4788	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4788.
4853	HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 103 OF MIL-STD-202.
4890	TEST INDITION LETIER 4890 SHALL, APPLY.
4793	MAGNITUDE OF THE POLARIZING VOLTAGE SHALL BE 4793 VOLT (S), DC.
4790	DURATION OF APPLICATION OF VOLTAGE SHALL BE 4790 HOURS(S).
	POINTS OF APPLICATION OF THE TEST VOLTAGE SHALL BE AS FOLLOWS:
4969	BETWEEN MUTUALLY INSULATED PARTS.
4970	BETWEEN ALL INSULATED PARTS AND GROUND.
4971	BETWEEN CURRENT CARRYING PARTS AND THE CASE.
6202	BETWEEN CURRENT CARRYING PARTS AND GROUND.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AT HIGH HUMIDITY.	6207
PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AFTER DRYING.	6206
HYDROSTATIC PRESSURE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2222
NO EVIDENCE OF DAMAGE.	2224
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2192
PER MIL-T-82459.	2196
TEST PRESSURE (SELECT ONE)	
(PSIG)	2198
(PASCALS)	2582

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6207	DIELECTRIC WITHSTANDING VOLTAGE TEST SHALL BE PERFORMED AT HIGH HUMNIDITY.
6206	DIELECTRIC WITHSTANDING VOLTAGE TEST SHALL BE PERFORMED AFTER DRYING.
2222	HYDROSTATIC PRESSURE. REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT EXCEPT 2222.
2224	HYDROSTATIC PRESSURE. THE TRANSDUCER SHALL SHOW NO EVIDENCE OF DEMAGE THAT WILL ADVERSELY AFFECT FORM, FIT, OR FUNCTION.
2192	HYDROSTATIC PRESSURE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2192.
2196	HYDROSTATIC PRESSURE. TESTING SHALL BE PERFORMED IN WITH THE MIL-STD-82459.
2198	TEST PRESSURE SHALL BE 2198 POUNDS PER SQUARE INCH GAUGE.
2582	TEST PRESSURE SHALL BE 2582 PASCAL(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST SPECIMEN TEMPERATURE (DEGREE CELSIUS)	2204
TEST MEDIA (DES)	2210
PER (DOC DES)	2212
TEST DURATION (MINUTES)	2214
TEST MEDIA TEMPERATURE (DEGREE CELSIUS)	2215
HYSTERESIS	
REQUIREMENTS (SELECL ONE)	
PER BASE DOCUMENT EXCEPT _____	2052
FULL SCALE OUTPUT DIFFERENCE (PERCENT)	2054
TEST METH0DS (SELECT ONE)	
PER BASE DOCUMENT ____	2042
PER (DOC DES)	2043
TEST MEASUREMENT INCREMENTS (PERCENT)	2044
TIME ELAPSED BETWEEN READINGS (MINUTES)	2046

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T20:57Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
2232	REDUCED PRESSURE l TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2232.
2234	REDUCED PRESSURE (VACUUM). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2234.
2236	TEST PRESSURE SHALL BE 2236 TORR.
2600	TEST PRESSURE SHALL BE 2600 PASCAL(S) .
2242	TEST CONDITION LETTER 2242 SHALL. APPLY.
2244	METHOD OF MOUNTING THE TEST SPECIMEN SHALL BE ANY SUITABLE METHOD.
2246	METHOD OF MOUNTING THE TEST SPECIMEN SHALL BE THE NORMAL. METHOD.
2248	TEST PRESSURE DURATION SHALL BE 2248 MINUTE(S).
2126	REPEATABILITY. REQUIREMENT(S) SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2126.
2127	REPEATABILITY. REPEATABILITY SHALL NOT BE GREATER THAN 2127 PERCENT OF FULL SCALE OUTPUT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2112
PER MIL-P-82459.	2114
AS FOLLOWS:	2602
DATA POINTS (NUMBER)	2115
TEST LOADS (CYCLES)	2116
TEST SPECIMEN TEMPERATURE (DEGREE CELSIUS)	2117
RESOLUTION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	2142
RESOLUTION (PERCENT OF FULL SCALE OUTPUT)	2144
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	2132
PER MIL-T-83460.	2133
TEST POINTS (PERCENT OF RATED STIMULUS)	2134

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2112	REPEATABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2112.
2114	REPEATABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-P-82459.
2602	REPEATABILITY. TESTING SHALL BE PERFORMED AS FOLLOWS:
2115	THE NUMBER OF DATA POINTS TAKEN OVER THE OPERATING RANGE SHALL BE 2115.
2116	THE NUMBER OF TEST LOAD CYCLES SHALL BE 2116.
2117	TEST SPECIMEN TEMPERATURE SHALL BE NOT GREATER THAN 2117. DEGREE(S) CELSIUS .
2142	RESOLUTION. REUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2142.
2144	RESOLUTION. RESOLUTION SHALL BE NOT LESS THAN 2114 PERCENT OF FULL. SCALE OUTPUT.
2132	RESOLUTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2132.
2133	RESOLUTION. TESTING SHALL BE IN ACCORDANCE WITH MIL-T-83460.
2134	INCREMENTAL TEST POINTS SHALL BE 2134 PERCENT OF RATED STIMULUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST SPECIMEN TEMPERATURE	
MININUM (DEGREES CELSIUS)	2136
MAXIMUM (DEGREES CELSIUS)	2138
SALT SPRAY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT	4878
NO EVIDENCE OF CORROSION, PHYSICAL DAMAGE, OR DEGRADATION OF PERFORMANCE.	4782
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT	4770
PER MIL-STD-202, METHOD 101.	4771
* TEST CONDITION (LETTER)	4772
MOUNTING (SELECT ONE)	
SPECIAL MOUNTING PER DOCUMENT (DOC DES)	4773
MOUNTING SHALL BE BY NORMAL METHOD .	4765
MOUNTING SHALL BE BY ANY SUITABLE METHOD.	4766

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.