MILITARY STANDARD

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

ANTENNAS

TO ALL HOLDERS OF MIL-STD-35-43(MI)

1. The following pages of MIL-STD-35-43(MI) have been revised and supersede the pages listed:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	15 January 1975	v	1 May 1974
vi	15 Januay 1975	vi	1 May 1974
vii	15 January 1975	Vii through X	1 May 1974
5	15 January 1975	5	1 May 1974
6	15 January 1975	6	1 May 1974
7	15 January 1975	7	1 May 1974
8	15 January 1975	8 through 18	1 May 1974
21	15 January 1975	21 through 24	1 May 1974
49	1 May 1974	Reprinted without change	
50	15 January 1975	50 through 56	1 May 1974
57	15 January 1975	57	1 May 1974
58	1 May 1974	Reprinted without change	
65	15 January 1975	65	1 May 1974
66	1 May1974	Reprinted without change	
109	1 May1974	Reprinted without-change	
110	15 January 1975	110 through 124	1 May 1974
125	15 January 1975	125 and 1-26	1 May 1974
127	15 Januay 1975	127 through 142	1 May 1974
157	15 January 1975	157 through 162.	1 May 1974

2. Retain this notice page and insert before the Table of Contents.

3. Holders of MIL-STD-35-43(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publicati on. Each notice is to be retained by stocking points until the Military Standard is completely revised or Cancelled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User Activity:
Army-MI

Preparing Activity:
Army-MI
Project EDS-A080

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
1.0	Antennas	1
1.1	Specification Title Index	3
7.2	Specification Requirements Instructions	5
1.2.1	General	5
1.2.2	Approved Item Name Code	6
1.2.3	Figure Ntier	6
1.2.4	Dimensions	6
1.2.5	Tabulation	6
1.2.6	Deleted	
1.2.7	Deleted	
1.2.8	Del eted	
1.2.9	Applicable Documents	7
	NOTE: Paragraphs 1.2.10 through 1.2.19 have been deleted.	
1.2.20	Body Style	19
1.2.21	Design and Construction	19
1.2.22	Operating Parameters	20
1.2.23	Frequency Range	20
1.2.24	Del eted	
1.2.25	Deleted	
1.2.26	Radiation Pattern	21
1.2.27	Gain	25
1.2.28	Insulation Resistance	26

Supersedes page v of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF COTENTS (CONT)

SECTION	TITLE	PAGE
1.2.29	Impedance	26
1.2.30	Voltage Standing Wave Ratio (VSWR)	27
1.2.31	Power Capability	28
1.2.32	Radio Interference	29
1.2.33	Continuity	30
1.2.34	Feed System Efficiency	30
1.2.35	Admittance	31
1.2.36	Orientation	32
1.2.37	Flight Test	32
1.2.38	Impact	33
1.2.39	Air-Seal	34
1.2.40	Leakage	35
1.2.41	Bounce	35
1.2.42	Flexural Strength	36
1.2.43	Static Load	37
1.2.44	Altitude	38
1.2.45	Wind	38
1.2.46	Ice	39
1.2.47	Sand and Dust	40
1.2.48	Rain	40
1.2.49	High Temperature	41
1.2.50	Low Temperature	42

Supersedes page vi of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS (CONT)

SECTION	TITLE	PAGE
1.2.51	Thermal Shock	43
1.2.52	Shock	44
1.2.53	Fungus Resistance	45
1.2.54	Salt Fog	45
1.2.55	Humidity	46
1.2.56	Moisture Resistance	47
1.2.57	Random Vibration	48
1.2.58	High Frequency Vibration	48
1.2.59	Low Frequency Vibration	49
	Specification Requirements List (SRL)	57
1.3	Configuration and Drawings	143
	Figures 092-01-l through - 092-02-l	149-155

Supersedes pages vii through x of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SECTION 1.2

SPECIFICATION REQUIREMENTS INSTRUCTIONS

1.2.1 General

The purpose of these instructions is to establish the procedures to be followed, and the format to be used, for submission of, requirements to obtain a computer generated procurement document.

The requester will find it impossible to comlete an SRS using only this dash numbered part of MIL-STD-35. Information which is standard for all generic families has been included in the master document at the issuance of MIL-STD-35C. This information is not repeated for each dash numbered part. The following list contains the subjects which are pertinent to every family unless othewise excepted.

General Description of AEDPS
Part Numbering
Specification Requirements Sheet
Writing Methodology
Mandatory Specification Requirements
General Specification Requirements
Dimensions and Drawings
Applicable Documents
Materials
Finishes
Inspections
Single and Multi-Item Specification (Tabulation)
Sources
Search
General Instructions for SRL
Tables A through S

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1.2.2 Approved Item Name Code

The item name code for an antenna, to be entered on the SRS with Code 1007, is selected from the Item Name Code column of the following list.

Approved Item Name	Item Name Code
Antenna	00749
Unapproved Names	77777

1.2.3 Figure Number

Code 1009 must show the figure number selected from Section 1.3.

1.2.4 Dimensions

MIL-STD-35 must be used In conjunction with this dash numbered part to completely delineate the dimensions for an antenna.

The figures and corresponding legends, representing different configurations of antennas, are located at the end of Section 1.3. The figure number (representing the selected figure) is mandatory and shall be entered on the SRS with Code 1009, The figure legends in this document (AA,AB, AC, etc.) representing dimensions shall be employed with corresponding legends in Table A of MIL-STD-35.

The remaining instructions for dimensioning antennas are located in MIL-STD-35.

1.2.5 Tabulation

The explanation of, and the instructions for using tabulation are found in MIL-STD-35. Candidates for tabulaton for this part are the dimensional codes shown in Table A of MIL-STD-35 and the following.

TABULATION CANDIDATES FOR ANTENNAS

Characteristic Code	Title
	Beanwidth (degrees maximum)
1620	E plane
1622	H plane

Supersedes page 6 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABULATION CANDIDATES FOR ANTENNAS (CONT)

Characteristic Code	Title
	Frequency (Megahertz)
1635	Lower limit
1636	Upper limit
1684	Gain (db minimum)
1727	VSWR
1736	Power (watts)

NOTE: Paragraphs 1.2.6, 1.2.7, and 1.2,8 have been deleted.

1.2.9 Applicable Documents

In addition to the documents contained in the Applicable Document List of MIL-STD-35, the documents that follow shall be entered on the SRS with appropriate codes from Table B of MIL-STD-35:

Document	Code	Related Subject
MIL-STD-167	1434	Random Vibration
MIL-STD-169	1983	High Temperature
	1999	Low Temperature
MIL-STD-170	1396	Moisture Resistance
MIL-STD-202	1392	Moisture Resistance
	1443	High Frequency Vibration
	1458	Low Frequency Vibration
MIL-STD-810	1427	Random Vibration
	1498	Shock
	1851	Leakage
	1907	Altitude
	1947	Sand and Dust
	1967 or 1968	Rain
	1969	Rain
	1977	High Temperature
	1994	Low Temperature
	4714	Thermal Shock
	4755	Fungus
	4771	Salt Fog
	4789	Humidity

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

(Cont)

Document	Code	Related Subject
MIL-S-901	1502	Shock
MIL-I-6051	1752	Radio Interference
MIL-E-16400	1982	High Temperature
	1998	Low Temperature
	4791	Humidity

Supersedes pages 8 through 18 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

NOTE: Paragraphs 1.2.24 and 1.2.25 have been deleted.

1.2.26 Radiation Pattern

If the test procedure shown in the document referenced with Code 1006 is sufficient, enter Code 1651 on the SRS followed by an "X".

If it is desired to take exception to the test procedure shown in the document referenced with Code 1006, enter Code 1652 on the SRS and complete the sentence shown with Code 1652 in the SRL, using 189 characters or less including punctuation and spaces.

To specify that testing shall be performed in accordance with an existing document, enter Code 1653 on the SRS followed by the number of the document (see 1.2.9 for a list of applicable documents). If Code 1653 is used, the number of the document must also be entered again on the SRS with an appropriate code from Table B of MIL-STD-35,

If the requirement shown in the document referenced with Code 1006 is sufficient, enter Code 1660 on the SRS followed by an "X".

If it is desired to modify the requirement shown in the document referenced with Code 1006, enter Code 1661 on the SRS and complete the sentence shown with Code 1661 in the SRL, using 189 characters or less including punctuation and spaces.

If it is desired to specify the angle between the half power points of the maximum lobe, it is mandatory to enter Codes 1662 and 1663 on the SRS followed by the average value and the maximum value, respectively, in degrees.

If it is desired to specify beam tilt, enter Code 1664 and/or 1665 on the SRS followed by the average value and/or the maximum value, respectively, in degrees.

Supersedes pages 21 through 24 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

If it is desired to specify that testing shall be in accordance with Method 204 of MIL-STD-202, enter Code 1443 on the SRS followed by the test condition letter. If Code 1443 is used, enter MIL-STD-202 on the SRS with an appropriate code from Appendix B (see 1.2.9). If Code 1443 is used, it is possible to specify the method of mounting the test specimen by using Code 1444, 1445, or 1446 followed by the appropriate SRS entry. If Code 1443 is used, the electrical load maybe specified by entering Code 1447 on the SRS followed by the desired value in ohms. If Code 1443 is used, it is possible to specify the method of determining mechanical resonance by entering Code 1448 or 1449, as appropriate, on the SRS followed by an "X".

If the requirement shown in the document referenced by using Code 1006 is sufficient, enter Code 1450 on the SRS followed by an "X".

If it is desired to modify the requirement shown in the document referenced by using Code 1006, enter Code 1451 on the SRS and complete the sentence shown with Code 1451 in the SRL, using 189 characters or less including punctuation and spaces.

If it is desired to specify the insulation resistance, enter Code 1452 on the SRS followed by the minimum allowable insulation resistance in megohms. If it is desired to specify the requirement shown with Code 1453 in the SRL, enter Code 1453 on the SRS followed by an "x" If it is desired to specify the power handling capability, enter Code 1454 on the SRS followed by the nominal power handling capability in watts. If it is desired to specify the requirement shown with Code 1455 in the SRL, enter Code 1455 on the SRS followed by an "X".

1.2.59 Low Frequency Vibration

If the test procedure shown in the document referenced by using Code 1006 is sufficient, enter Code 1456 on the SRS followed by an "X".

If it is desired to take exception to the test procedure shown in the document referenced by using Code 1006, enter Code 1457 on the SRS and complete the sentence shown with Code 1457 in the SRL, using 189 characters or less including punctuation and spaces.

If it is desired to specify that testing shall be in accordance with Method 201 of MIL-STD-202, enter Code 1458 on the SRS followed by the duration of application per axis in hours. If Code 1458 is used, enter MIL-STD-202 on the SRS with an appropriate code from Appendix B (See1.2.9). If Code 1458 is used, it is possible to specify the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

number of axes, the method of mounting, the direction of motion, and the electrical load. To specify the number of axes, enter Code 1459 on the SRS followed by the number. To specify the method of mounting, enter Code 1460, 1461, or 1462 on the SRS followed by the appropriate SRS entry. To specify the direction of motion, enter Code 1463, 1464, 1465 or 1466 on the SRS followed by the appropriate SRS entry. (See 1.2.9 if Code 1466 is used,) To specify the electrical load, enter Code 1467 on the SRS followed by the desired value in ohms.

If the requirement shown in the document referenced with Code 1006 is sufficient, enter Code 1468 on the SRS followed by an "X".

If it is desired to modify the requirement shown in the document referenced with code 1006, enter Code 1469 on the SRS and complete the sentence shown with Code 1469 in the SRL, using 189 characters or less including punctuation and spaces.

If it is desired to specify the insulation resistance, enter Code 1470 on the SRS followed by the minimum allowable value in megohms. If it is desired to specify the requirement shown with Code 1471 in the SRL, enter Code 1471 on the SRS followed by an "X". If it is desired to specify the power handling capability, enter Code 1472 on the SRS followed by the nominal power handling capability in watts. If it is desired to specify the VSWR, enter Code 1473 on the SRS followed by the desired VSWR rating.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-MI
Army-MR
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI
Project EDS-A080

Supersedes pages 50 through 56 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.1	Enter on the SRS, requiements from MIL-STD-35. NOTE: Reference paragraphs 1,2.12 through 1.2.19 have been deleted. These characteristic names and codes are now contained in MIL-STD-35.	
1.2.20	*Body Style Number _____	1562

*INDICATES MANDATORY REQUIREMENTS
Supersedes page 57 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF, PARA,	CHARACTERISTIC NAME	CODE
1.2.21	Design and Construction	
	Antenna Termination Type (Select one)	
	Wire leads	1563
	or	
	Terminal studs	1564
	or.	
	Coaxial connector	1565
	or	
	Waveguide flange	
	Rectangular	1566
	Round	1567
	Input Coaxial Connector	
	*Series	1568
	*Specification	1569
	*End Design _____ (Male or female)	1570

INDICATES MANDATORY REQUIREMENTS

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.26	Radiation Pattern Test procedure (Select one if required) Test per specification shown with Code 1006 or	1651

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN,

REF, PARA,	CHARACTERISTIC NAME	CODE
1.2.26 Cent.	Test per specification shown with Code 1006 except _____	1652
	or	
	Test per _____ (see 1.2.9)	1653
	Requirement (Select one if required) (Man- if either Code 1651, 1652, or 1653 is selected)	
	Requirements per specification shown with Code 1006	1660
	or	
	Requirements per specification shown with Code 1006 except _____.	1661
	or	
	Requirements as follows:	
	The angle between the half power points of the maximum lobe shall be	
	*degrees (average) -	1662
	* _____ degrees (maximum)	1663
	Beam tilt	
	_____ degrees (average)	1664
	_____ degrees (maximum)	1665
	Horizontal omnidirectional pattern to within + decibels,	1666

INDICATES MANDATORY REQUIREMENTS

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS

SEE MIL-STD-35 FOR EXAMPLE OF VALUE FILL-IN.

REF, PARA,	CHARACTERISTIC NAME	CODE
1.2.59	Direction of motion (Select one)	
	On centerline of most sensitive axis.	1463
	or	
	Ninety degrees from centerline of most sensitive axis.	1464
	or	
	In each of three mutually perpendicular axes.	1465
	or	
	Direction in accordance with _____ (See 1.2.9)	1466
	Electrical load (Ohms)	1467
	Note: Measurements after the test shall be in accordance with the requirements selected.	
	Requirement (Select one) (Mandatory if either Code 1456, 1457 or 1458 is selected)	
	Requirements per specification shown with	1468
	or	
	Requirements per specification shown with Code 1006 except _____.	1469
	or	

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CHARACTERISTIC CODE
1.2.59 Cent	Requirements after the test:	
	Insulation resistance (Megohms) minimum	1470
	No allowable damage that will affect form, fit or function.	1471
	The power handling capabilities shall be _____ watts (Nominal)	1472
	The VSWR shall be.	1473

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

APPENDIX A

DIMENSION CHARACTERISTICS

NOTE: The Dimension Characteristic Table now appears as Table A in MIL-STD-35.

Supersedes pages 125 and 126 of 1 May 1974

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

APPENDIX B

APPLICABLE DOCUMENTS

NOTE: The Applicable Documents Table now appears as Table B in MIL-STD-35.

Supersedes pages 127 through 142 of 21 December 1973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY

LEFT BLANK

Supersedes pages 157 through 162 of l May 1974

*U.S GOVERNMENT PRINTING 0FFICE:1975-603-126/921

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.