INCH-POUND
MS18196F
04 June 2012
SUPERSEDING
MS18196E
03 June 1972


DETAIL SPECIFICATION SHEET

JACKSCREW, ELECTRICAL CONNECTOR, MALE AND FEMALE, FIXED

Reinstated after 10 July 2009 and may be used for new and existing designs and acquisitions.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28748.



Inches	mm
.002	0.05
.016	0.41
.135	3.43
.320	8.13
.417	10.59
.812	20.62

FIGURE 1. Fixed jackscrew male and female.


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.

Fixed jackscrew designator	Gender	Connector size (number of contacts)	A Thread class 2	B Thread class 2	C dia max
M18196-1	Male	7, 9, 14, 18, 20, 26, 34, 42, 50, 66, 75	4-40 UNC-2A .112-40 UNC	6-32 UNC-2A .138-32 UNC	.190 (4.83)
M18196-2	Female	7, 9, 14, 18, 20, 26, 34, 42, 50, 66, 75	4-40 UNC-2A .112-40 UNC	6-32 UNC-2B .138-32 UNC	.190 (4.83)
M18196-3	Male	104	6-32 UNC-2A .138-32 UNC	8-32 UNC-2A .164-32 UNC	.137 (3.48)
M18196-4	Female	104	6-32 UNC-2A .138-32 UNC	8-32 UNC-2B .164-32 UNC	.137 (3.48)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.016 inch (0.41 mm).
4. Material corrosion resistance steel in accordance with ASTM A276, ASTM A473, ASTM A581/A581M, ASTM A582/A582M, SAE AMS5636, SAE AMS5639, SAE AMS5648, classes 302, 303, 303Se, 304 or 316 except for aluminum alloy knob and .040 inch (1.02 mm) flat washer.
5. Finish passivated in accordance with ASTM A967 or SAE AMS2700 except for anodized knob.
6. Jackscrew may have .005 inch (0.13) minimum vertical float.

FIGURE 1. Fixed jackscrew male and female – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.



MINIATURE SELF-LOCKING NUT
(NYLON INSERT)

Self-locking nut dimensions

Self-locking nut Part or Identify Number (PIN) (See note 9)	Connector size (number of contacts)	D		E ref	F		G ref	H Thread class 3
		min	max		min	max		
MS21044-C04	7, 9, 14, 18, 20, 26, 34, 42, 50, 66, 75	.181 (4.60)	.190 (4.83)	.205 (5.21)	.095 (2.41)	.125 (3.18)	.070 (1.78)	4-40 UNC-3B .112-40 UNC
MS21044-C06	104	.240 (6.10)	.252 (6.40)	.275 (6.99)	.133 (3.38)	.153 (3.89)	.081 (2.06)	6-32 UNC-3B .138-32 UNC

NOTES:
1. Self-locking nut shown for reference purposes only.
2. Dimensions are in inches.
3. Metric equivalents are given for information only.
4. Unless otherwise specified, tolerances are ±.016 inch (0.41 mm).
5. Material corrosion resistance steel in accordance with ASTM A276, ASTM A473, ASTM A581/A581M, ASTM A582/A582M, SAE AMS5636, SAE AMS5639, SAE AMS5648, classes 302, 303, 303Se, 304 or 316.
6. Finish passivated in accordance with ASTM A967 or SAE AMS2700.
7. Not to be used where temperatures exceed 250°F (121°C).
8. Do not reuse nylon nut after removal.
9. National Aerospace Standard NASM21044. Not to be ordered with this slash sheet.
10. Copies of NASM21044 are available online at http://www.aia-aerospace.org/, or may be purchased from Aerospace Industries Association, 1000 Wilson Boulevard, Suite 1700, Arlington, VA 22209-3901.

FIGURE 2. Self-locking nut.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.

Fixed jackscrew male and female. See figure 1.
Self-locking nut. See figure 2.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-28748, this document references the following:

ASTM A276
ASTM A473
ASTM A581/A581M
ASTM A582/A582M
ASTM A967
NASM21044
SAE AMS2700
SAE AMS5636
SAE AMS5639
SAE AMS5648

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AM, AR, AT, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 99

(Project 5935-2009-163)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:16Z
Check the source to verify that this is the current version before use.