
FED. SUP CLASS
1670



ASSEMBLY

DASH NO.
-1
-2

NOTES:

1. MATERIAL: HOOK - STEEL, MIL-S-5626 OR MIL-S-6049.
   GUARD - STEEL, QQ-S-598, COMMERCIAL QUALITY.
   SPRING - STEEL, QQ-W-470.
   RIVET - CORROSION-RESISTANT, FF-S-536, TYPE XII, CLASS 3, GRADE C, DIAMETER AND LENGTH TO SUIT.
2. METHOD OF FORMING: HOOK, HOT FORGE.
3. HEAT TREATMENT: HOOK - HEAT TREAT 170,000 TO 190,000 LBS/SQ IN. TENSILE STRENGTH IN ACCORDANCE WITH MIL-H-6875.
   GUARD - NONE.
   SPRING - AS REQUIRED BY FINISH SPECIFICATION.
4. FINISH: HOOK, SPRING AND GUARD BEFORE ASSEMBLY -
   -1, CADMIUM PLATE QQ-P-416, CLASS 1, TYPE I.
   -2, PHOSPHATE COAT, MIL-C-16232, TYPE 2, CLASS 4B FOLLOWED BY WAX EMULSION MIL-W-3683. (OPTIONAL FINISH FOR SPRING: -1 AS ABOVE.)
5. DIMENSIONS IN INCHES: EXCEPT AS OTHERWISE SPECIFIED HEREIN, TOLERANCES: DECIMALS, ± .03, ANGLES ± 2°.
6. PROOF LOAD: HOOK SHALL BE SUBJECTED TO THE PROOF LOAD SPECIFIED AND AS INDICATED BY ARROWS IN ACCORDANCE WITH THE PROCUREMENT SPECIFICATION.
7. SNAP HOOK ASSEMBLY SHALL PASS FREELY OVER A .281 DIAMETER ROD.
8. SURFACE ROUGHNESS, UNLESS OTHERWISE SPECIFIED HEREIN, SHALL BE $125\sqrt{}$ MAX. IN ACCORDANCE WITH ASAI B46.1.
9. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
10. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

(A) ENTIRE STANDARD REVISED

APPROVED 12 MAY 61 REVISED (A) 17 JUL 75

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.


User activities: NAVY - MC
Review activities: ARMY - AV, USAF - 11


P.A.	TITLE	MILITARY STANDARD
Other Cust: USAF - 82, NAVY - AS, ARMY - GL	SNAP HOOK-COILED SPRING, PARACHUTE, QUICK FIT	MS22043
PROCUREMENT SPECIFICATION: MIL-H-7195	SUPERSEDES: AN6509	SHEET 1 OF 3

DD FORM 672-1 (Coordinated)


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:44Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
1670






HOOK




SECTION A-A




SECTION B-B



SECTION C-C



SECTION D-D



SECTION E-E

APPROVED 12 MAY 61 REVISED (A) 17 JUL 75

P.A. USAF - 82 Other Cust NAVY - AS ARMY - GL	TITLE SNAP HOOK - COILED SPRING, PARACHUTE, QUICK FIT	MILITARY STANDARD MS22043
PROCUREMENT SPECIFICATION MIL - H - 7195	SUPERSEDES: AN6509	SHEET 2 OF 3

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.


Using activities:
NAVY - MC

Review activities:
ARMY - AV
USAF - 11


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:44Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
1670



GUARD



SPRING

APPROVED 12 MAY 61 REVISED (A) 17 JUL 75

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

User activities: NAVY - MC

Review activities: ARMY - AV, USAF - 11

P.A. USAF - 82 Other Cust NAVY - AS ARMY - GL	TITLE SNAP HOOK - COILED SPRING, PARACHUTE, QUICK FIT	MILITARY STANDARD MS22043
PROCUREMENT SPECIFICATION MIL-H-7195	SUPERSEDES AN6509	SHEET 3 OF 3

DD FORM 672-1 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:44Z
Check the source to verify that this is the current version before use.