
FED. SUP. CLAS
4720




| DASH NO. | CODE LETTER | TUBING O.D. REF. | HOSE I.D. REF. |
|---|---|---|---|
| -4 | E | 1/4 | 7/32 |
| -6 | G | 3/8 | 5/16 |
| -8 | H | 1/2 | 7/16 |
| -10 | J | 5/8 | 9/16 |
| -12 | K | 3/4 | 11/16 |
| -16 | M | 1 | 7/8 |
| -20 | N | 1-1/4 | 1-1/8 |

SWIVEL NUTS MUST HAVE HEX DIMENSIONS IN ACCORDANCE WITH MS21921, AND MUST BE INCAPABLE OF BEING REMOVED FROM THE FITTING ASSEMBLY

FITTING END TO MATE WITH MS33514.

HOSE ASSEMBLIES TO BE SPECIFIED AS:
12 INCHES LONG AND UNDER – INCREMENTS NOT LESS THAN 1 8 INCH (TOLERANCE ± 1 8 INCH)
12 INCHES TO 18 INCHES LONG – INCREMENTS NOT LESS THAN 1 4 INCH (TOLERANCE ± 1/8 INCH)
18 INCHES TO 36 INCHES LONG – INCREMENTS NOT LESS THAN 1 2 INCH (TOLERANCE ± 1 4 INCH)
OVER 36 INCHES LONG – INCREMENTS NOT LESS THAN 1 INCH (TOLERANCE ± 1% OF LENGTH)

**THE PART NO. SHALL BE FORMULATED TO REFLECT THE BASE ASSEMBLY NUMBER, SIZE AND LENGTH.**

(E) CANCELLED - FOR PROCUREMENT USE AS115 AND AS621

APPROVED 2 Apr 65 REVISED (A) 7 Dec 66 (B) 21 Nov 67 (C) 18 Aug 72 (D) 15 DEC 76 (E) 20 JUNE 1986

| | | |
|---|---|---|
| P. A. USAF - 11<br>Other Cust: Army – ME<br>Navy – AS | TITLE<br>HOSE ASSEMBLY, TETRAFLUOROETHYLENE, HYDRAULIC AND PNEUMATIC, (3000 P.S.I.) FLARELESS | MILITARY STANDARD<br>MS27369 |
| PROCUREMENT SPECIFICATION<br>MIL-H-38360 | SUPERSEDES: | SHEET 1 OF 2 |

4720-0738

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.
This military standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.
User activities:
Review activities:
Army - ME, AV, MI
Navy - AS
USAF - 11, 32

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
4720

EXAMPLE OF PART NUMBER

MS 27369 J * 16 4

- 4 — LENGTH IN EIGHTHS OF AN INCH
- 16 — LENGTH IN INCHES
- * — CODE LETTER SEE BELOW
- J — SIZE DESIGNATION FOR -10

* ADD CODE LETTER BELOW FOR ADDITIONAL FEATURES (IF REQUIRED)

"A" AS 1072-XX-SIL SLEEVE, FIRE PROTECTION (SILICONE) (-65°F (-54°C) THRU +500°F (+260°C)) SECURE WITH CRES BANDS AS REQUIRED

"B" AS 1073-XX-A/B SLEEVE, HEAT SHRINKABLE (-65°F (-54°C) THRU +250°F (121°C)XA DESIGNATES TRANSPARENT COVER FOR I.D. BANDS, ETC., MATERIAL IRRADIATED POLYOLEFIN, NOT FLAME RESISTANT) (B DESIGNATES OPAQUE BLACK COVER FOR ABRASION PROTECTION, SELF-EXTINGUISHING IN FLAME)

"C" AS 1291-XX-A/B SLEEVE, CHAFEGUARD, TFE (-65°F (-54°C) THRU +500°F (+232°C))(A DESIGNATES WHITE EXTRUDED AND SEAMLESS) (B DESIGNATES BLACK EXTRUDED AND SEAMLESS) WITH CRES BANDS, AS REQUIRED

"D" AS 1291-XX-C SLEEVE, CHAFE GUARD, FEP (-65°F (-54°C) THRU +350°F(+177°C))(C DESIGNATES TRANSPARENT FEP) SECURE WITH CRES BANDS AS REQUIRED

"E" AS 1291-XX SLEEVE, HEAVY WALL, CHAFE GUARD, TFE (-65°F (-54°C) THRU +450°F (+232°C)) SECURE WITH CRES BANDS

"L" LOCKWIRE HOLE

"F" CODE A + L

"G" CODE B + L

"H" CODE C + L

"J" CODE D + L

"K" CODE E + L

THE CUT ENDS OF THE FIRE PROTECTION SLEEVE (CODE A) SHALL BE COATED WITH RTV SILICONE RUBBER, PRIOR TO INSTALLATION TO PREVENT WICKING OF FLUIDS. AFTER INSTALLATION, CRACKS OR VOIDS IN THE FIRE PROTECTION SLEEVE, WHICH EXPOSE THE ASBESTOS, SHALL BE COATED WITH RTV RUBBER.

DIMENSIONS IN INCHES.

FOR DESIGN PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

APPROVED 2Apr65 REVISED (A) 7Dec66 (B) 21Nov67 (C) 18Aug72 (D) 15Dec76 (E) 20 Jun 86

USER ACTIVITIES

REVIEWER ACTIVITIES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

| P. A. | INTERNATIONAL INTEREST | TITLE | MILITARY STANDARD |
|---|---|---|---|
| AIR FORCE - 11<br>Other Cust<br>ARMY - ME<br>NAVY - AS | | HOSE ASSEMBLY, TETRAFLUOROETHYLENE, HYDRAULIC AND PNEUMATIC, (3000 P.S.I.) FLARELESS | MS 27369 |
| PROCUREMENT SPECIFICATION<br>MIL-H-38360 | SUPERSEDES: | | SHEET 2 OF |

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T15:22Z
Check the source to verify that this is the current version before use.