MILITARY SPECIFICATION

AIR CONDITIONER: BASE MOUNTED, AIR-COOLED,

208-VOLT, 3-PHASE, 50- AND 60-HERTZ, AC,

SINGLE-PACKAGE, 36,000 BTU/HR

This amendment forms a part of MIL-A-52435D(ME), dated 5 September 1984, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, under SPECIFICATIONS, MILITARY, add the following:

"MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant."

PAGE 8

3.17, delete in its entirety and substitute:

"3.17 Treatment and painting. All parts shall be cleaned, treated and painted in accordance with MIL-T-704, type F or G, as applicable, with the following exceptions:

a. Internal components previously painted by the manufacturer need not be repainted when they conform to the salt fog requirements (see 3.7).

b. Coils, refrigerant tubing, electrical components, or other components whose operation will be impaired by painting shall not be painted.

c. Unless otherwise specified (see 6.2), top coat shall be camouflage green 383 conforming to MIL-C-46168."

PAGE 18

4.6.2.12, delete in its entirety and substitute:

"4.6.2.12 Humidity. Subject the air conditioner to the humidity test specified in MIL-STD-810, method 507.2, procedure III (aggravated exposure), figure 507.2-3. The duration of the test shall be 10 cycles. Do not operate the air conditioner during the test, except at the end of the fifth and tenth cycle

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

as indicated in MIL-STD-810. The air conditioner shall be operated in accordance with 4.6.2.4 prior to and after the exposure period to determine satisfactory functioning of controls and components. The front side of the control box shall be covered and sealed during exposure. Do not expose the air conditioner to extreme temperature prior to the test. After exposure, the junction box may be removed and the magnetic iron in the relays may be cleaned with a wire brush to remove rust and scale from the laminated surfaces. Nonconformance to 3.7 shall constitute failure of this test."

4.6.2.13, delete the first sentence and substitute: "Subject the air conditioner to the salt fog test as specified in MIL-STD-810, method 509.2, procedure I. The salt fog exposure shall be a continuous 48-hour period."

PAGE 19

4.6.2.14.2, delete the first sentence and substitute: "Place the air conditioner in an ambient temperature of 70 °F ±5 °F for 24 hours."

PAGE 29

6.2.e, delete in its entirety and substitute:

"e. Color required when other than camouflage green (see 3.17)."

PAGE 30

6.8, delete in its entirety.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4120-A312

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.