MILITARY SPECIFICATION

BARREL, MACHINE GUN, CAL .50, RECOIL AMPLIFIER, PRACTICE, M3

This specification is approved for use within the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department Of Defense.

1. SCOPE

1.1 Scope. This specification covers the M3 Recoil Amplifier for use on machine, gun, Cal .50: Browning, P12, Heavy Barrel, Flexible.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications, standards and handbooks form a partr of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, Cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-W-13855-	Weapons: Small Arms and Aircraft Armament Subsystems, General Specification for
MIL-W-63150-	Weapons and Support Materiel Standard Quality Assurance Provisions for

STANDARDS

MIL-sTD-l05-	Sampling Procedures and Tables for Inspection by Attributes
MIL-sTD-l09-	Quality Assurance Terms and Definitions

Beneficial comments (recommendations, AdditioNS, deletions and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S Army Armament Munitions and Chemical Command. Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardized Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those listed in effect on the date of solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9370140	-Discriminator
9370141	-Wrench, Spanner
9370142	- Barrel, Machine Gun, Caliber 50, Recoil Amplifier, Practice, M3
P9370142	- Packaging Data Sheet

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (eXCePt for associated detail specifications, Specification Sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with applicable drawings, specifications and standards.

3.3 Recoil amplifier. The recoil amplifier shall comply with all requirements specified on drawing 9370142, all associated drawings, and with all requirements specified in the applicable specifications and standards.

3.4 Assembleability. The recoil amplifier and discriminator shall readily attach and detach from the M2 Machine gun. When attached, the recoil amplifier and discriminator shall be securely retained on the M2 Machine gun.

3.5 Functioning. When assembled to the M2 Machine Gun, the recoil amplifier and discriminator shall cause the weapon to function properly. The M2 Machine Gun with attached recoil amplifier and discriminator shall maintain an average rate of fire of 450 to 600 shots per minute. There Shall be no stoppages or malfunctions directly attributable to the recoil amplifier or discriminator. Testing shall be as specified in 4.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

3.6 Marking. The recoil amplifier and wrench spanner shall be clearly marked in accordante with the applicable drawing and the marking provisions of MIL-W-13855.

3.7 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to a first article inspection in accordance with the technical provisions herein (see 4.3).

3.8 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges cracks, surface defects, dirt, oil, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. See MIL-w-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection " requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material,

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (4.3)
b. Quality Conformsnce Inspection (4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Barrel, Machine Gun, Cal .50 Recoil		
Amplifier, Practice, M3	9370142	32
Discriminator	9370141	64

4.3.2 Inspections to be performed. First Article assemblies shall be subjected to all the examinations and tests specified in Table 1, quality assurance provisions, and such other inspection as necessary to determine compliance with contract requirements.

4.3.3 Rejection. If any assembly fails to comply with any of the applicable requirements, the First Article Sample shall be rejected. The government reserves the right to terminate its inspection upon any failure of an assembly in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

TABLE 1. First article inspection

CLASSIFICATION or **DEFECTS** & TESts

aMmA?u	Recoil Amplifier		sheet 1 of 1		DRAWIr 937 next h
		No. of SAMPLe UNITS	AQL	REQUIREMENT pARAGRAPH	
	Barrel, Machine Gun, cAl .5O, Recoil Amplifier, Practice, M3 (DwG. 9370142)				
	Assembleability 1/	32	aCC 0 Rej 1	3.4	4.5
	Functioning 1/ 2/	32	Acc 0 **Rej 1**	3.5	4.5
	Any part cracked	32	Acc-O Rej-1	3.3	Vis
	.036 Maximum clearance between gas cylinder and block toggle	32	Acc-C) Rej-1	3.3	SM
	Incorrect assembly or missing parts	32	Acc-0 Rej-1	3.3	Vis
	Poor workmanship (except for cracks)	32	Acc 0 Rej 1	3.8	Vis

NOTES: 1/ These test shall be performed concurrently.
Occasionally, the last round of a continuous belt, due to the light weigh
cartridge case, will not fully eject from the weapon. Failure to eject shall
as a weapon stoppage nor shall it be recorded as a defect chargeable to the re

Replaces DRDAR-QA Form 1 Jun, 1 Jun,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process? using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.2 Examination. The examinations listed in the Classification of Defects and Test tables shall be performed-on inspection lots as defined in 4.4.1 of this specification. Prior to these examinations, the parts and assemblies comprising the recoil amplifier shall have been inspected in accordance with the

Critical defects. Unless otherwise specified, inspection for critical defects shall be 100 percent.

b. Major and minor defects. Examination for major and minor characteristics shall be performed in accordance with the classification of quality conformance inspections specified herein. Inspection Level 11 shall be used and individual AQL's applied in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL

PARAGRAPH	TITLE			DRAWING
4 .4.2.1	Barre]., **Machine Gun, Cal .50, Recoil Amplifier, Practice, M3**	sheet 1 of 1		937 next hi

	EXAMINATION OR TEST	No. of SAMLE UNITS	AQL &	RCOUIRCUCMT paragraph	PARAGRA
Critical :		**None**	**de** f ined		
Major:					
101.	**Any** part cracked		100%	3.3	Vi
102.	Assembleability 1/		0.65	3.4	4.5
103.	Functioning 1/ 2/		0.65	3.5	4.5
104.	Incorrect assembly or **missing** parts		0.65	3.3	Vis
105.	.036 **Maximum clearance** between gas cylinder and block toggle		**0.65**	**3.3**	**SM**
Minor:					
201.	**Poor workmanship (except for cracks)**		**2.5**	**3.8**	**Vis**

NOTES: **1\ These test shall be performed concurrently.**

2/ Occasionally, the last round of a continuous **belt, due to the light wei cartridge** case, will **not fully eject from the weapon. Failure to eject shall** as a weapon stoppage nor shall it be recorded as a defect chargeable to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Assembleability. The recoil amplifier and discriminator (right and left) shall readily attach to and detach from M2 Machine Gun. Wrench spanner (part 9370141) shall be used to tighten gas cylinder to toggle block.

4.5.2 Functioning test. The recoil amplifier shall be assembled to a MZ Machine Gun. Government standard .50 Caliber M858 ball plastic cartridges shall be used for the test. The M2 Machine Gun with attached recoil amplifier and discriminator shall be fired 50 rounds right side feed and 50 rounds left side feed. . Each 50 round segment shall be fired 25 rounds spasmadic and 25 rounds continuous burst. The cyclic rate of fire for the 25 round continuous burst shall be recorded.

5. PACKAGING

5.1 Levels A and B. The recoil amplifier shall be packaged in accordance with packaging data sheet P9370142 and as specified in the contract.

5.2 Marking. Marking shall be in accordance with the applicable packaging data sheet and as specified in the contract.

5.3 Shipping. when components from more than one lot are shipped at one time, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The assembly covered by this specification is intended for use with Machine, Gun Cal. .50: Browning, M2, Heavy Barrel, Flexible.

6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Serialization requirements, if applicable.

d. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

e. First Article sample requirements, if other than specified in Section 4 of this specification.

f. Packaging requirements, if other than specified in Section 5 of this specification.

g. Responsibility for furnishing test machine gun, ammunition and links. (See 3.4 and 3.5)

6.3 Submission of inspection equipment designs for approval. See MIL-W-63150. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, NJ, 07806-5000.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as U.S. Army Armament Research and Development Center (ARDC), U.S. Army Armament Research and Development Command (ARRADCOM, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.5 Subject term (key word) listing.

Caliber .50 Cartridge, Short Range Training Ammunition
Machine Gun M2
Recoil Amplifier
Small Arms Ammunition

Custodian:
Army-AR

Preparing activity:
Army-AR

(project 1005-A635)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In ● continuing ● ffort to make our *standardization documents* better, the DoD provides this *form* for use in submitting comments and suggestions for improvement. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge (DO NOT *STAPLE),* and mailed. In block 5, *be as specific as possible* about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous or was incompatible, and give wording changes which would alleveviate the problem.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

Fold along this Line)

DEPARTMENT OF THE ARMY

NO ● OSTAGE NECESSARY IF WAILED IN THE united STATES

OFFICIAL BUSINESS
● ENALTY FOR private use $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 wASHINGTON O C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN : AMSmC-QA
PICATINNY ARSENAL, nJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMpROvEMENT pROPOSAL

(SEE INSTRUCTIONS - *Reverse SIDE*}

. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-7044S	BARREL, MACHINE GUN, CAL .50, RECOIL AMPLIFIER, PRACTICE, M3

3k NAME OF SUBMITTIN0 ORGANIZATION	4. TYPE OF ORGANIZATION (MARK ONE)
	• 1 VENDOR
I. ADDRESS (Ctfy. 8t, ZiP CODE)	• 1 USER
	MANUFACTURER
	• 1

b .

c .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.