MIL-C-63112A(AR)
AMENDMENT 5
4 JANUARY 1985
SUPERSEDING
AMENDMENT 4
14 September 1984

MILITARY SPECIFICATION

CARTRIDGE, 22MM, SUB-CALIBER PRACTICE
M744, M745, M746, M747
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-63112A(AR) dated 22 May 1981, and is approved for use by the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.2.1.1

a. Delete "155" and "133" and substitute "158" and "130".

b. Delete "176" and "142" and substitute "174" and "144".

d. Delete "233" and "214" and substitute "245" and "202".

PAGE 5

4.3.3.d Delete "One or more duds occur" and substitute "Two or more duds occur."

PAGE 7

TABLE I, Wing (Before forming): Delete "Examination for defects 15 3.2 4.4.2.11".

PAGE 9

TABLE I, Cartridge, 22MM Sub-Caliber Practice M744, M745, M746, M747 (Dwg. 9299079). Number of samples units for examination for defects: Delete "5 ea" and substitute "25 ea".

TABLE I, First Article Inspection. Cap, Protective change drawing: From: 9299097
To: 9369942

FSC 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

Paragraph reference/inspection method for examination for defects: Delete "(a)".

Examination or Test column, Transportation Vibration Test: delete: Delete "(b)".

Reference/Inspection Method Column, 4.4.2.35(a): Add: "(b)".

Notes: Delete Note (a) in its entirety and substitute: "(a) The proving ground test shall be performed on the same units that were subjected to the transportation vibration test."

Notes: Delete Note (b) in its entirety and substitute: "(b) The excess units subjected to TV test shall be placed in stock and utilized for conditioning/spotting rounds".

PAGE 10

TABLE I, First Article Inspection. Cap, Percussion (Dwg. 9299091): Delete in its entirety.

PAGE 11

TABLE I, First Article Inspection. Anti-Creep Device (Dwg. 9344301): Delete in its entirety.

		No. of Samples	Ref Para	Para Req
Add:	Anti-Creep Device (Dwg. 9369943) Examination for defects	15	3.2	4.4.2.36
Add:	Disc-Adhesive (Dwg. 9369941) Examination for defects	15	3.2	4.4.2.37
Add:	Disc Assembly (Dwg. 9369940) Examination for defects	15	3.2	4.4.2.38

PAGE 18

* 4.4.2.6 MAJOR: Add: "107 Primer seating chamber improper 0.40%, 3.2, Gage".

PAGE 24

4.4.2.11 Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

PAGE 25

4.4.2.12 Major

Add "106	Width of wing	0.40%	3.2	Gage"
Add "107	Thickness	0.40%	3.2	Gage"
Add "108	Angular cutoffs improperly located or incorrect (4 places)	0.40%	3.2	Gage"
Add "109	Radii missing or improper (4 places)	0.40%	3.2	Visual"
Add "110	Presence of holes	0.40%	3.2	Visual"

PAGE 30

4.4.2.16

Major 104, delete: "Aft" and substitute: "forward"

Major 107, delete: "forward" and substitute: "percussion cap"

Major 108, delete: "forward" and substitute: "Aft"

Major 109, delete: "forward" and substitute: "percussion cap"

Major 110, delete: "true position of forward outside diameter with inside diameter" and substitute: "true position of aft outside diameter with forward inside diameter"

Major 112, delete: "Aft" and substitute: "forward"

Minor 201, delete: "forward" and substitute: "percussion cap"

PAGE 33

4.4.2.19

Major 101, delete: "Crimp inadequate or cracked" and substitute: "Crimp improper or missing"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

4.4.2.21 Change drawing number: From - 9299097
To - 9369942

PAGE 41

4.4.2.26 Delete in its entirety.

PAGE 42

4.4.2.27 Change next higher assembly block:
From - 9299080/9331155
To - 9369940

PAGE 51

4.4.2.36 Change drawing number block: From - 9344301
To - 9369943

Add: New 4.4.2.37, Page 51A included.

Add: New 4.4.2.38, Page 51B included.

PAGE 53

4.5.2.3 Cleaning cannon M29A1 or M29. Before firing apply rifle bore cleaner, solvent cleaning compound to wiping cloths gripped in proper cleaning staff. Insert it into bore and thoroughly scrub all surfaces with a push-pull action the entire length of barrel. Make certain to clean firing pin using clean wiping cloths on cleaning rod and dry the bore thoroughly. Examine firing pin for cleanliness and that the pin is free of residue during firing. After every tenth firing, the bore should be cleaned with rifle bore cleaner and wiped dry with clean wiping cloths.

4.5.2.4 Cleaning M1 sabot. Before firing, the sabot is cleaned using a cleaning wick positioned in the slot of the end staff and saturated with rifle bore cleaner. Then dry thoroughly with a clean dry wick. During firing, the M1 Sabot should be cleaned after each round is fired with a water detergent solution to remove any dirt or dust, then wiped dry including the bore.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INCPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63112A(AR)
AMENDMENT 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.37	Disc - Adhesive Backed				9369941
					NEXT HIGHER ASSEMBLY 9369940
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Adhesive missing or incomplete		0.40%	3.2	Visual
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Thickness of foil		0.65%	3.2	Gage
203	Poor workmanship		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63112A(AR)
AMENDMENT 5

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.38	Disc, Assembly				9369940
					NEXT HIGHER ASSEMBLY 9299080/9331155
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Offset		0.40%	3.2	Visual
Minor 201	Poor workmanship		0.65%	3.6	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendments were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A671)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:14Z
Check the source to verify that this is the current version before use.