INCH-POUND

MIL-F-48637A (AR)
AMENDMENT 1
09 May 1995

MILITARY SPECIFICATION

FUZE, POINT DETONATING, PRACTICE, M751
WITH PYROTECHNIC SIGNATURE CARTRIDGE

This Amendment forms a part of MIL-F-48637A (AR), dated 8 September 1992, and is approved for use by the U.S. Army Armaments Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Drawings: Delete:

"12630600 - Packing and Marking for Container, PA149
12630601 - Packing and Marking For Box, Wirebound".

Add:

"12961098 - Packing for 12 Meter Drop Test of Fuze, PD, Practice, M751".

PAGE 7

4.3.1, Part Description: Delete:

"Packing Preformed AMS 3303 O-Ring ... 12929048 ... 10".

PAGE 13

Table I, Section pertaining to the Packing Preformed AMS 3303 O-Ring: Delete in its entirety.

PAGE 19

4.4.2.1, Major 111: Delete:

"True position of minor striker hole to rear cavity", and substitute: "Location of minor striker hole".

PAGE 22

4.4.2.2, Minor 204: Delete in its entirety.

AMSC N/A **FSC 1390**
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

PAGE 35

4.4.2.15, Major 103: Delete: "Major diameter of cavity", and substitute: "Major diameter of thread".

PAGE 38

4.4.2.18: Add:

"Major 110 Diameter of center column ... III ... 3.2 ...Gage

Major 111 Distance between forward face and forward face of rear flange ... III ... 3.2 ... Gage".

PAGE 39

4.4.2.18, Minor 203: Delete in its entirety.

PAGE 42

4.4.2.21: Delete in its entirety.

PAGE 44

4.4.2.22, Major 102: Delete in its entirety.

PAGE 49

4.5.7: Delete in its entirety and substitute:

"4.5.7 Ballistic test. This test shall be performed by the government at a government proving ground in accordance with the applicable USA TECOM Acceptance Test Procedure.

Eighty (80) fuzes from the Transportation Vibration Test shall be subjected to this test. All fuzes shall be fired from a complete M252 81mm mortar. The fuze carrier shall be an M879, 81mm practice round. All rounds shall be fired onto a flat, nongrassy earthen surface that is not marshy or frozen. With the exception of the first article and the first production lot, all rounds shall be fired at ambient temperature. For the charge "1" phase of the first article and the first production lot forty (40) rounds shall be fired at 0 degrees F. For the charge "4" phase of the first article and the first production lot forty (40) rounds shall be fired at +110 degrees F. Video camera coverage shall be set 1500 meters from the point of impact. Video camera speed shall be 120 frames per second minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

The following firing schedule shall be used:

a. Forty (40) rounds at charge "1" at a gun elevation of forty-five (45) degrees. Muzzle velocity data is required via radar.

b. Forty (40) rounds at charge "4" with the gun elevation set so that the viewing distance of the observer is at least 1500 meters. Muzzle velocity data is required via radar.

The following acceptance/rejection criteria applies:

For the charge "1" and charge "4" firings, two or more duds (total duds for both groups combined) constitutes cause for lot rejection. All duds shall be recovered (if possible) for further examination.

A dud is defined as an unobservable signature upon ground impact of the round. Observable is defined as both visible and audible."

PAGE 50

4.5.8, Line 7: Delete: "dwgs 12630601 and 12630600", and substitute: "dwg 12961098".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-0818)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:35Z
Check the source to verify that this is the current version before use.