INCH-POUND

MIL-G-53082/3(ME)
14 August 1989

MILITARY SPECIFICATION SHEET

GENERATOR SETS, DIESEL ENGINE DRIVEN

3KW, 28 VOLT, DIRECT CURRENT

This specification is approved for use within the USA Belvoir Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-G-53082.

REQUIREMENTS

1. Drawings. This specification covers the detail requirements of the 3 KW Mode IV Set, Model MEP-026B. The set shall be in accordance with Top Assembly TA 84-026 and as specified herein.

2. Voltage transient performance. With the set initially operating at rated speed and load, the instantaneous voltage shall not dip more than 30 percent of rated voltage, and shall reach stable conditions within three seconds. With the set initially operating at rated speed and voltage and following any sudden change in load from rated load to no load, the instantaneous voltage rise shall not exceed 40 percent of rated voltage and shall reach stable conditions within three seconds.

3. Field current. With the generator temperature stabilized at ambient conditions, the exciter field current for rated voltage shall not exceed 0.25 ampere at no load and 0.77 ampere at rated load.

4. Generator efficiency. The generator, including excitation system, shall have a minimum efficiency of 72 percent.

5. Voltage ripple. The output voltage ripple shall not exceed 5.5 percent of rated voltage.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 6115-A529

AMSC N/A

FSC 6115

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:00Z
Check the source to verify that this is the current version before use.