MIL-M-48261(AR)
AMENDMENT 4
30 August 1983
SUPERSEDING
AMENDMENT 3
17 AUGUST 1983

MILITARY SPECIFICATION

MINES, M718/M741 SYSTEM, METAL PARTS

This Amendment forms a part of Military Specification MIL-M-48261(AR), dated 4 May 1977, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: Delete the following dwgs.:

9277743 - Simulant
9277820 - Simulant, Modified
9277763 - Booster, Simulant

PAGE 3

4.3.1: Delete the following parts:

Simulant	-	Dwg. 9277743
Simulant, Modified	-	Dwg. 9277820
Booster, Simulant	-	Dwg. 9277763

PAGE 5

TABLE I: Delete the following parts and the corresponding examinations and tests:

Simulant	-	Dwg. 9277743
Simulant, Modified	-	Dwg. 9277820
Booster, Simulant	-	Dwg. 9277763

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

PAGE 8

Add the following major defect to paragraph 4.4.2.1:

Category	Examination or Test	AQL	Requirement Paragraph	Inspection Method
Major 114	Radius from ID to flange, above max.	0.40%	3.2	4.5.2

PAGE 9

4.4.2.2: Add under Major Category "111", add under Examination or Test, "Flats along the outside and bottom edges not present", add under AQL "0.40%", add under Requirement Paragraph "3.2", add under Inspection Method "Visual".

PAGE 12

4.4.2.5: Simulant. Delete paragraph in its entirety.

PAGE 13

4.4.2.6: Simulant, Modified. Delete paragraph in its entirety.

PAGE 14

4.4.2.7: Add Major 105 "Chamfer above max. 0.40%, 3.2, Gage"

PAGE 15

4.4.2.8: Booster, Simulant. Delete paragraph in its entirety.

PAGE 19

* 4.4.2.12: Pad spherical. Add Major 101 "Material improper/Hardness improper, - -, 3.1, Certification"

PAGE 26

4.4.3.2: Density of the simulant. Delete paragraph in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

PAGE 27

4.5.2: Density of simulant. Delete paragraph in its entirety.

PAGE 27

Add paragraph 4.5.2:

"4.5.2 Inspection of radius. The internal radius between the body inner diameter and the flange shall be measured on an optical comparator, after having obtained a mold of the interfacing surface using a quick setting plaster of similar material."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liabiity whatsoever for any inacuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A295

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.